

Declare.

Ultima® Ceiling Panels Armstrong World Industries, Inc.

Final Assembly: Pensacola, Florida, USA; Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.449 kg CO2 eq. 

Declared Unit: 1 square foot of product

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Clay; Corn Starch; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Calcium carbonate; Calcium magnesium carbonate; Glass, oxide, chemicals; Polyvinyl acetate; Titanium dioxide; Dolomite; Amorphous Silica; Acrylic Acid; Propanol; 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-; Zinc borate; Polyvinyl alcohol; Starch; Quartz; Fatty acids, coco, polymers with benzoic acid, pentaerythritol and phthalic anhydride; Kaolin; White Tint; Polyethylene; Paraffin Wax; Polyethylene Wax; Benzenesulfonic acid, 5-benzoyl-4-hydroxy-2-methoxy-; Sodium Salt; Styrene Polymer; Silicic Salt; Water; Citric Acid; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Ester; Poly ether salts; Methyl Polymer; Attapulgitic Clay; Ethyl Acetate; Hydrogenated Naphtha; Proenoate

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0026

EXP. 01 JUN 2024

Original Issue Date: 2016