

CANYON®  
 Square Lay-in & Tegular  
 smooth texture



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)

Canyon Beveled Tegular panels with Prelude XL 15/16" suspension system

Smooth-texture panel with both Sustain® and Total Acoustics® panel performance for flexible spaces.

**KEY SELECTION ATTRIBUTES**

- Get total noise control and floor plan versatility with Total Acoustics ceiling panels: NRC + CAC = Total Acoustics Performance
- Canyon® is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- Smooth, white surface
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Good combination of acoustical performance; NRC 0.65 and CAC 35
- 30-Year Limited System Warranty against visible sag, mold, and mildew



- 10-Year replacement panel available for items 1490, 1491, 1492, 1493, 1494, 1495

**COLOR**



White (WH)

**DETAILS** (Other Suspension Systems compatible. Refer to listing on next page.)



1. Canyon Square Lay-in
2. Canyon Square Lay-in with Prelude® XL 15/16" suspension system

# CANYON®

## Square Lay-in & Tegular smooth texture



Declare.

GREENGUARD Gold Certified (details below)

LEED® WELL™ LBC

UP TO 44% RECYCLED CONTENT

Calculate sustainability with Green Genie® [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

energy management, construction waste mgmt, regional materials, design for flexibility, EPD, recyclable/producer resp., biobased materials, recycled content, sourcing of raw materials, material ingredient reporting, low emitting materials, lighting quality, acoustics

### VISUAL SELECTION

### PERFORMANCE SELECTION

Dots represent high level of performance.


\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics (NRC + CAC)	Total Acoustics (NRC CAC)	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty		
CANYON® 15/16" Square Lay-in	1	1490	24 x 24 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
		1491	24 x 48 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
15/16" Beveled Tegular	15	1492	24 x 24 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
		1493	24 x 48 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
9/16" Beveled Tegular	44, 48, 29, 52, 56	1494	24 x 24 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
		1495	24 x 48 x 5/8" □	0.65 + 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*		
Made-to-Order Sizes			5/8" Thick – 15/16" Square Lay-in, 15/16" & 9/16" Beveled Tegular													
			Width	Length	N/A	N/A	N/A	Class A	0.80	*	*	*	Std	Std	*	*
			12" – 24"	18" – 72"												

4-6 WEEKS order to ship

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Mineral fiber with acoustically transparent membrane.

**Surface Finish**  
Acoustically transparent membrane with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type IV, Form 2, Pattern E; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted on Silhouette suspension system

**Insulation Value**  
R Factor – 1.5 (BTU units)  
R Factor – 0.26 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Cleaning and Disinfecting**  
Cleaning and CDC-approved disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**Weight; Square Feet/Carton**  
0.76 lbs/SF; 64 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

