



Lyra® PB Ceiling Panels Armstrong World Industries

Final Assembly: Hilliard, Ohio, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.681 kg CO2 eq.

Declared Unit: 1 square foot

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Glass, oxide, chemicals; Starch, polymer with 2-propenoic acid, graft, sodium salt; Aluminum; Fats and Glyceridic oils, vegetable, polymd., oxidized; Calcium Carbonate; Tetra Hydro Ester; Aluminum hydroxide; Mineral Wool; Caprolactum; Phosphine oxide; 2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-; Silicon; Polyvinyl acetate; Siloxane; Limestone; Acrylic Acid; Propanol; Magnesium; Nickel (Metallic); Blue Tint; Copper; Glycol acrylate; Aluminum Trihydrate; Propenoic Copolymer; Polyvinyl alcohol; Proprietary Ingredient (< 1%)¹; Titanium dioxide; Water; Manganese; Clay; Calcium carbonate; Tetrahydrofurfuryl alcohol; Quartz; Diatomaceous Earth; Mica; Silica; 2-Propenoic acid, 2-phenoxyethyl ester; Sodium Salt; Black Tint; Iron; Attapulgitic Clay; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Citric Acid

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0015

EXP. 01 JUL 2024

Original Issue Date: 2016