

**new** ULTIMA® Templok®

Tegular  
fine texture



**TOTAL  
ACOUSTICS®**  
Sound Absorption (NRC)  
+ Sound Blocking (CAC)

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Learn How Templok   
Ceilings Save Energy!\*



Ultima Templok Beveled Tegular panels with Suprafine® 9/16" suspension system

Fine texture mineral fiber ceiling combines exceptional acoustical performance, energy savings and enhanced thermal comfort using advanced Phase Change Material (PCM) technology.

**KEY SELECTION ATTRIBUTES**

- Saves up to 15% energy\*
- Improve thermal comfort with ceilings that help regulate indoor temperatures
- Provides up to 35 BTUs/SF of passive cooling\*
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance

- Exceptional sound-blocking performance for enhanced speech privacy: CAC 39
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Non-directional visual reduces installation time
- Energy-saving, high light-reflective finish
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

\* Measured cooling energy savings in lab test. Results may vary. See Templok Technical Guide.

**TYPICAL APPLICATIONS**

- Office
- Education
- Transportation
- Healthcare

**COLOR**



White  
(WH)

**DETAILS** (Other suspension systems compatible. Refer to listing on next page.)



1. Ultima® Templok® Beveled Tegular panel
2. Ultima Templok back of panel
3. Ultima Templok with Silhouette® XL® 9/16" suspension system with 1/4" reveal

**LEED® WELL | LBC**



Up to **41% RECYCLED CONTENT**

Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/repurposed producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

**VISUAL SELECTION**

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
		<b>1912TEMP</b> (Field Panel Only – cannot be cut)	24 × 24 × 1" <input type="checkbox"/>
		<b>1912</b> Use 1912 for borders and cutting needs. See Ultima Tegular Data Page for Product Details	24 × 24 × 3/4" <input type="checkbox"/>
		<b>1" Thick – 15/16" Square Lay-in or 15/16" Beveled Tegular</b>	

Made-to-Order Ultima® Templok® Panels

**4-6 WEEKS**  
order to ship

1,000 SF minimum order quantity applies to Items 1910TEMP and 1911TEMP. 1910TEMP and 1911TEMP are the only made-to-order panels available. Custom sizes are not available.

**1910TEMP**  
24" × 24" 15/16" Square Lay-in  
Field Panel Only – cannot be cut. Use 1910 for borders and cutting needs. See Ultima Lay-in Data Page for product details


**1911TEMP**  
24" × 24" 15/16" Beveled Tegular  
Field Panel Only – cannot be cut. Use 1911 for borders and cutting needs. See Ultima Tegular Data Page for product details

**PERFORMANCE SELECTION** Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program
0.75	39	BETTER Class A**	0.88	*	*	*	Fog Wash Impact Scratch Soil	30-Yr Warranty	
0.75	35	BETTER Class A	0.88	*	*	*			

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)  
\*\* Consult a code official in your jurisdiction for mechanical code compliance.

**SUSPENSION SYSTEMS**



**Blizzard White – Suspension System Finish**  
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

**PHYSICAL DATA**

**Material**  
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane and virgin PVC with salt hydrate

**Surface Finish**  
DuraBrite with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 450 or less.

**ASTM E1264 Classification**  
Type IV, Form 2, Pattern E

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

**Thermal Performance**  
Stores up to 35 BTU/SF per ASTM C1784

**VOC Emissions**  
Compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted using Silhouette® suspension system for 9/16" edge detail.

**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

**Ten (10) Year Limited Thermal Energy Storage Capacity Warranty**

**Weight; Square Feet/Carton**  
1912TEMP – 2.1 LBS/SF; 24 SF/CTN

**Minimum Order Quantity**  
1 carton

