

Declare. SM

AcoustiBuilt® Ceiling and Wall Panels Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.449 kg CO₂e/ft² ▼

Declared Unit: square foot

End of Life Options: Take Back Program (Armstrong Ceilings Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Corn Starch; Clay; Cellulose; Glass, oxide, chemicals; Calcium Carbonate; Polyvinyl acetate; Limestone; Polyvinyl alcohol; Acrylic Acid; Starch; Aluminum Trihydrate; Fatty acids, coco, polymers with benzoic acid, pentaerythritol and phthalic anhydride; Propanol; Titanium dioxide; Calcium carbonate; Mica; Quartz; Sodium Salt; Polyethylene Wax; Citric Acid; Silica; Amorphous Silica; Diatomaceous Earth; Oxirane, 2-phenyl-, polymer with oxirane, mono(dihydrogen phosphate), decyl ether

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0070

EXP. 01 DEC 2024

Original Issue Date: 2021