

# CIRRUS® Second Look®

Scored Tegular  
medium texture



**TOTAL  
ACOUSTICS®**  
Sound Absorption (NRC)  
+ Sound Blocking (CAC)



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Cirrus® Second Look® III panels with Suprafine® XL® 9/16" suspension system

See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)

Medium texture panels with a scored plank visual: Offer both Sustain® and Total Acoustics® panel performance.

## KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Classic Cirrus texture
- Excellent score line painting for a clean visual
- Mold- and mildew-resistant surface
- USDA-Certified Biobased Product – 91%

## COLOR



White  
(WH)



Custom Colors  
Available

## FACE VIEW



Cirrus® Second Look® I panel –  
Scoring creates nominal 12" x 12" squares



Cirrus® Second Look® II panel –  
Scoring creates nominal 24" x 24" squares



Cirrus® Second Look® III panel –  
Scoring creates nominal 6" x 48" linear planks

**DETAILS** (Other Suspension Systems compatible. Refer to listing on next page.)



1



2

1. Cirrus® Second Look® III
2. Cirrus® Second Look® III with Suprafine® 9/16" suspension system

# CIRRUS® Second Look®

Scored Tegular  
medium texture

USDA  
CERTIFIED  
BIOBASED  
PRODUCT  
PRODUCT 91%

**SUSTAIN\***  
High Performance  
Sustainable Ceiling Systems

Declare.

**GREENGUARD**  
Gold Certified  
(details below)

**LEED® WELL™ LBC**

UP TO **77%** RECYCLED CONTENT

Calculate sustainability with Green Genie®  
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

## PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
CIRRUS® Second Look® I 15/16" Beveled Tegular	14	512	24 x 48 x 3/4"	0.65	35	GOOD Class A	0.85	*	Std	*	Std	*	*	10-Yr
CIRRUS® Second Look® II 9/16" Beveled Tegular	28	510	24 x 48 x 3/4"	0.65	35	GOOD Class A	0.85	*	Std	*	Std	*	*	10-Yr
15/16" Beveled Tegular	14	513	24 x 48 x 3/4"	0.65	35	GOOD Class A	0.85	*	Std	*	Std	*	*	10-Yr
CIRRUS® Second Look® III 9/16" Beveled Tegular	28	511	24 x 48 x 3/4"	0.65	35	GOOD Class A	0.85	*	Std	*	Std	*	*	10-Yr
15/16" Beveled Tegular	14	514	24 x 48 x 3/4"	0.65	35	GOOD Class A	0.85	*	Std	*	Std	*	*	10-Yr

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).  
ASTM E1264 Classification  
Type III, Form 1, Pattern E I K  
Fire Class A

**Humidity/Sag Resistance**  
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Primary (Embodied) Energy**  
See all LCA information on our EPDs.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS**  
UL.COM/GG  
UL 2818



**Insulation Value**  
R Factor - 1.9 (BTU units)  
R Factor - 0.33 (Watts units)

**Design Consideration**  
Do not mix Cirrus® Second Look® with standard Cirrus items in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

**Warranty**  
Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
1.09 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton

**Metric Items Available**  
512M, 510M, 513M, 511M, 514M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.