

INVISACOUSTICS™

Wall Panels
smooth texture



Declare™

GREENGUARD
Gold Certified
(details below)

UP TO **84%** RECYCLED CONTENT

For LEED contribution contact TechLine

energy management	construction waste mgmt	regional materials	design for flexibility	EPD	recyclable/extended producer resp.	biobased materials	recycled content	sourcing of raw materials	material ingredient reporting	low emitting materials	lighting quality	acoustics
-------------------	-------------------------	--------------------	------------------------	-----	------------------------------------	--------------------	------------------	---------------------------	-------------------------------	------------------------	------------------	-----------

LEED WELL | LBC

LOCATION DEPENDENT




InvisAcoustics™ 24" x 48" panels

Smooth-textured, hidden acoustical solution that installs directly to walls using ceiling adhesive.

KEY SELECTION ATTRIBUTES




- InvisAcoustics™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today (white and field paintable panels only)
- Wall installation – 6' from the ground or higher
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning)
- Good acoustical absorption – NRC up to 0.75
- Field paintable panels can be sprayed same color as wall
- Smooth, clean durable finish –
Impact-resistant
Scratch-resistant
Soil-resistant
- Panels cut easily to fit into any space

PANEL COLORS*



*NOTE: Ceiling Panels are dye-lotted and should be separated by dye lot. Do not mix.

VISUAL SELECTION

Item No.	Dimensions (Inches)
INVISACOUSTICS™ Standard Sizes 3/4" Square  (on 48" sides)	24 x 48 x 3/4"
3/4" Square  (on 24" sides)	1212BL* 24 x 48 x 3/4"
3/4" Square 	1212FP 24 x 48 x 3/4"

PERFORMANCE

Dots represent high level of performance.

	Fire Rating (White only)	Light Reflect	Anti-Mold/Mildew	Sag Resist	Certified Low VOC Emissions	Humi-Guard+	Bio-Block	CleanAssure™ Disinfectable Walls	Fog	Impact	Scratch	Soil	Recycle Program	10-Yr Warranty
Class A	N/A	*	*	*	*	*	*	*	*	*	*	*	*	*

ACOUSTICAL INFORMATION

Panel Thickness	NRC	Mounting Methods
3/4"	0.75	D-20
3/4"	0.70	A

1 Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

* Tech Black panels are not included in the Sustain® portfolio

PHYSICAL DATA: (Refer to InvisAcoustics product page in the Direct-to-Structure section)



PARTITIONS & WALLS