

OPTIMA™ & PAINTED NUBBY™

Wall Panels

24
DEFEND™
Solutions for Healthier,
Safer Spaces

Declare.
GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC

UP TO **71%** RECYCLED CONTENT

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT



▲ Painted Nubby™ Acoustic Wall Panels

Wall panels with a bright surface that provide excellent sound absorption.

KEY SELECTION ATTRIBUTES

- | | |
|--|----------------------|
| Optima | Painted Nubby |
| • Smooth surface | • Bright surface |
| new | |
| • CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning) | |
| • Durability | |
| Washable | |
| Scratch-resistant | |
| Soil-resistant | |

COLOR



VISUAL SELECTION

	Substrate	Finish	Item No.	Dimensions (Inches)
Optima™	Fiberglass	DuraBrite®	3154	48 x 96 x 1"
Painted Nubby™	Fiberglass	Woven Cloth	3104	48 x 96 x 1"

PERFORMANCE

Dots represent high level of performance.

CleanAssure™ Disinfectable Walls	NRC RATING	
	Fog	D Mount
•	0.80	0.90
	0.70	0.80

For performance and physical data, armstrongceilings.com/optimawalls

INSTALLATION ACCESSORIES

	Description	Item No.	Dimensions (Inches)	Color
C Channel	Extruded PVC Plastic	3107	1 x 96 x 1"	White
H Channel	Extruded PVC Plastic	3108	1-5/8 x 96 x 1"	White

A Mounting – Mounting directly against existing surface D-20 Mounting – Mounting spaced 3/4" from existing surface using 1" x 4" furring strips



PARTITIONS & WALLS