





CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



plus capabilities
to do more



WoodWorks® wall panels 24" x 48" on Z-Clips and WoodWorks® Vector® ceiling panels 24" x 48" with custom perforation (running parallel to the short side of the panel) in custom Vertical Grain Douglas Fir

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Wall system available in a variety of wood species, stains, sizes, and perforation options.

KEY SELECTION ATTRIBUTES

- Coordinate veneer choice with WoodWorks® ceilings
- Install panels horizontally or vertically using clips or splines
- Perforated panel with acoustical backing improves sound quality and reduces reverberation time within a space
- USDA-Certified Biobased Product 100% (preferred for government projects)
- Select products included in the FAST134 program – ready to ship in 4 weeks or less

VENEERS Due to printing limitations, shade may vary from actual product.

Natural Variations™
(Real Wood Veneers)




Constants™
(Real Wood Veneers)



Custom Veneers and Finishes Available (extended lead times)

PERFORATION OPTIONS (Actual 1:6 scale shown)



Custom Perforations Available

NOTE: Slotted perforations run parallel to the length of the panel.

WOODWORKS®

Standard Wall Panels



92% RECYCLED CONTENT

For LEED contribution contact TechLine

energy management	construction waste mgmt.	regional materials	design for flexibility	EPD	recyclable/extended producer resp.	biobased materials	FSC® (for wood)	recycled content	sourcing of raw materials	material ingredient reporting	low emitting/low materials	lighting quality	acoustics
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

VISUAL SELECTION

Item No. ♦	Dimensions W x L x H * (Inches)	Custom Sizes Available	Perforations	Installation Options	Finish Options
FSC® certified WOODWORKS® Wall Panels (with acoustical fleece)	5814	23-3/4 x 47-3/4 x 3/4"	W1, W2, W3, W4, W5, W6	X (Z-Clip installation) K (Spline installation - 4 panel sides kerfed)	NMP, NLC, NDC
	5818	23-3/4 x 95-3/4 x 3/4"	W1, W2, W3, W4, W5, W6	X (Z-Clip installation) K (Spline installation - 4 panel sides kerfed)	NMP, NLC, NDC
	5819	23-3/4 x 107-3/4 x 3/4"	W1, W2, W3, W4, W5, W6	X (Z-Clip installation) K (Spline installation - 4 panel sides kerfed)	NMP, NLC, NDC
	5820	23-3/4 x 119-3/4 x 3/4"	W1, W2, W3, W4, W5, W6	X (Z-Clip installation) K (Spline installation - 4 panel sides kerfed)	NMP, NLC, NDC



FAST134 program items ready to ship from manufacturer in 4 weeks or less. Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

♦ When specifying or ordering, include the appropriate perforation, installation, and finish suffixes. (e.g., 5814 W1 K N M P)
NOTE: For veneers and sizes available as special order, call TechLine at 1 877 276-7876.
* Panels will be installed with 1/4" or larger gap between panels. When using spline installation, module will be 24".

ACOUSTICAL INFORMATION


Dots represent high level of performance.

Perforation	NRC	NRC Rating	
		D-20 Mounting with acoustical fleece	C-20 Mounting with 1" fiberglass infill *
W1 Unperforated		N/A	N/A
W2 Round Straight		0.50	0.65
W3 Round Diagonal		0.50	0.65
W4 Round Straight		0.55	0.80
W5 Oval Straight Slotted		0.45	0.70
W6 Oval Straight Slotted		0.45	0.60

* Fiberglass Infill Panel Item 8200T10

WoodWorks® Walls perforations align with the following ceiling panels:

Perforation	WoodWorks® Vector®	WoodWorks Concealed
W2	yes	yes
W3	yes	yes
W4	yes	no
W5	yes	no
W6	yes	no



ACCESSORIES

For corners, splines, Z-Clips, and infill panel options, see Pgs 621-622.

PHYSICAL DATA

Material
FSC® certified fire-retardant particle board with face-cut veneers (SW-COC-003601). For more information about FSC certified products, or to view our FSC certification letter, visit armstrongceilings.com/woodworksfsc

Surface Finish
Clear or tinted semigloss coating

Fire Performance
Class A: ASTM E84 surface burning characteristics.
Flame Spread Index 25 or less. Smoke Developed Index 50 or less.
CAN/ULC S102 surface burning characteristics.
Flame Spread Rating 25 or less. Smoke Developed Classification 50 or less.

Application Considerations
Variation among panels may occur due to the natural characteristics of the wood and grain (special order panels available).

It is very important that WoodWorks panels be climatized prior to installation. Relative humidity between 25% and 55% and temperatures between 50°F and 86°F must be maintained throughout the life of the product.

Design Considerations
The reveal width on WoodWorks Tegular panels and WoodWorks Walls is different. For an application with the same size reveal in the ceiling and on the wall, order custom-cut panels or use Vector® ceiling panels Z-clipped to the wall.

Specification Consideration
Attention: For FSC-certified wood products to maintain their CoC certification, products must be sold to a CoC-certified distributor or directly to the installing contractor. Failure to do so breaks the CoC.

FAST134 Program Considerations

Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.
Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.
Distributor Truck Schedule Matters: We rely on distribution to help move products around the Country. When speed matters, work with your local distributor to ensure FAST134 service.
Stock vs Made-to-Order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.
Warranty
Details at armstrongceilings.com
Weight; Square Feet/Carton
Panels - 2.75 lbs/SF; bulk packaged per order.