


▶ CERAMAGUARD



▲ Ceramaguard



Ceramaguard Board

CERAMAGUARD



CERAMAGUARD

BOARD



Prelude TL/NC 24mm



600 x 600 x 15 mm 607 M
600 x 1200 x 15 mm 608 M




EEA	A1
A	Klasse A (Ö-Norm B 3800)
B + L	Klasse A1 (NBN S 21-203)
CH	6q3 (TA VKF)
CZ	B (GSN 730823)
D	Klasse A1 (DIN 4102/1)
E	M0 (NFP 92-510)
F	M0 (NFP 92-510)
I	Classe 1 (D.M. 26/06/84)
NL	Klasse 2 (NEN 6065-6066)
PL	Niezapałny (PN-B-02874:1996)
RUS	Hard combustible (G-1): GOST 30244-94
SK	B (STN 730823)
UK	Non combustible/Class 0 (BS 476)



EN 20354 & EN 11654

α_w	NRC	Hz					
		125	250	500	1000	2000	4000
0.55(MH)	0.60	0.25	0.30	0.50	0.80	0.85	0.75



EN 20140-9 & EN 717-1

Dncw = 39 dB	Hz					
	125	250	500	1000	2000	4000
	20.0	29.9	32.7	44.7	48.5	45.3



$\lambda = 0.052 - 0.057 \text{ W/m}^2\text{K}$



84 %



100 % RH



$\approx 7 \text{ kg/m}^2$
20 kg/m² if wet



- Please contact our Internal Technical Sales Group for further details.
- Pour de plus amples informations merci de contacter notre Service Information Plafonds.
- Weitere Informationen erhalten Sie von unserem Kundenservice. Änderungen vorbehalten.
- Voor meer informatie kunt u contact opnemen met Market Service Center.
- Per ulteriori dettagli consultare il nostro Ufficio Commerciale.
- Para más detalles, por favor, contacte con el Servicio de Información de Techos.
- W razie dodatkowych pytań prosimy kontaktować się z biurem Armstrong w Warszawie.

www.armstrong-europe.com