




ACOUSTIBuilt Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA
Life Expectancy: 30 Year(s)
Embodied Carbon: 4.49E-01 kg CO2 eq. 
Declared Unit: 1 square foot of product
End of Life Options: Take Back Program (Armstrong Ceilings Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Corn Starch; Cellulose; Clay; Limestone; Titanium dioxide; Calcium carbonate; Glass, oxide, chemicals; Aluminum Trihydrate; Calcium Carbonate; Diatomaceous Earth; Quartz; White Tint; Vinyl Polymer; Polyvinyl acetate; Polyvinyl alcohol; Amorphous Silica; Water; Aluminum hydroxide; Starch; Fatty acids, coco, polymers with benzoic acid, pentaerythritol and phthalic anhydride; Propanol; Methylpropanoate; Sulfuric acid magnesium salt; Fatty acids oil; Glycerides; Sorbitan; Mica; Silica; Oxirane, 2-phenyl-, polymer with oxirane, mono(dihydrogen phosphate), decyl ether; Citric Acid; surfactant; Poly(oxy-1,2-ethanediyl), α,α' -[1,4-dimethyl-1,4-bis(3-methylbutyl)-2-butyne-1,4-diyl]bis[ω -hydroxy-; Hectorite

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0070
EXP. 01 JAN 2024
Original Issue Date: 2021