



CALLA PrivAssure™ Ceiling Panels Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

End of Life Options: Take Back Program, Recyclable (100%)

Ingredients:

Mineral Wool; Kaolinite ($\text{Al}_2(\text{OH})_4(\text{Si}_2\text{O}_5)$); Perlite; Mica; Quartz; Corn Starch; Cellulose; Aluminatesilicate; Clay; Feldspar; Aluminum hydroxide; Calcium Carbonate; Glass, oxide, chemicals; Polyvinyl acetate; White Pigment; Titanium dioxide; Propanol; Starch; Calcium carbonate; Vinyl Polymer; Limestone; Aluminum Trihydrate; Polyvinyl alcohol; Silica; Diatomaceous Earth; Amorphous Silica; Acrylic Acid; Proprietary (0.014-0.016%)¹; Attapulgitite Clay; Citric Acid; Hydroxyethylcellulose; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.98% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0042

EXP. 01 APR 2024

Original Issue Date: 2019