



GRAPHIS® Finetex™ & Rustex™ Ceiling Panels

Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA; Pensacola, Florida, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.355 kg CO2eq 

Declared Unit: 1 sq. ft

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Amorphous Silica; Cellulose; Glass, oxide, chemicals; Corn Starch; Distillates (petroleum), hydrotreated middle; Clay; Calcium Carbonate; Titanium dioxide; Starch; Silica; Diatomaceous Earth; Acrylic Acid; Calcium carbonate; Kaolin; Quartz; Aluminum hydroxide; Polyethylene Wax; Sodium Salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0086

EXP. 01 APR 2025

Original Issue Date: 2023