Declare.

MetalWorks™ Linear - Classics, Synchro®, & Diverge® in Std Painted, Sequels™, or Effects™ finish
Armstrong World Industries

Final Assembly: Montreal, Canada; Johnstown, Ohio, USA; Guangdong, China
Life Expectancy: 30 Year(s)
End of Life Options: Salvageable/Reusable in its Entirety, Recyclable (100%)

Ingredients:

Iron; Zinc; Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with 1,3-butanediol; Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with ammonia-ethylene oxide reaction product distn. residues, compds. with diethylenetriamine and triethylenetetramine; 1,3-Benzenedicarboxylic acid, polymer with 2,2-dimethyl-1,3-propanediol and hexanedioic acid; Manganese; Silicon; Titanium dioxide; Tint; Graphite; Nickel (Metallic); Nepheline syenite; Naphtha; Chromium, metallic; Acetic acid ethenyl ester, polymer with 1-ethenyl-2-pyrrolidinone; Polyurethane foams; Silica, amorphous, fumed, cryst.-free; Hexanedioic acid, bis(2-methoxyethyl) ester; Cellulose pulp; Mica; Copper; Cellulose; 1,2,4-Trimethylbenzene; Glass oxide; Molybdenum; Aluminum; Linseed Oil; Titanium; 1,3-Benzenedicarboxylic acid; Petroleum distillates; 2-Oxepanone, homopolymer; ethyl 2-cyano-3-ethoxyacrylate; 1,3,5-Triglycidyl-s-triazinetrione; Mineral Wool; PVA; Barium sulfate; Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-; Black Tint; 2-Butoxyethanol; 2-Propenoic acid, polymer with ethenylbenzene; 2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate and methyl 2-methyl-2-propenoate; Phosphate; 2-Propanol, 1-methoxy-, acetate; Phosphorus; Amorphous Silica; 2-Pentanone, 4-hydroxy-4-methyl-; Glass, oxide, chemicals; Xylene; Aluminum Powder; Phenol, 4,4′-(1-methylethylidene)bis[2,6-dibromo-, polymer with (chloromethyl)oxirane and 4,4′-(1-methylethylidene)bis[phenol]; Octadecane, 1-isocyanato-; 1,3,5-Trimethylbenzene; C.I. Pigment Brown 24; C.I. Pigment Yellow 42; Polyacrylic acid; Glycol Ether; Mica-group minerals; Undisclosed (< 0.06%)[1]; Carbon black; Undisclosed (< 0.05%)[1]; Sulfur, Elemental; Urethane (Ethyl carbamate); C.I. Pigment Black 1; Amorphous silica; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-; 2(3H)-Benzothiazolethione, zinc salt; Aluminum hydroxide; Isophorone Diisocyanate; Polyethylene Terephthalate; Isopropyl alcohol; 2-Ethyl-1-Hexanol; Cumene; Silica gel, pptd., cryst.-free; Diiron Trioxide; Boron; Undisclosed (< 0.02%)[1]; Undisclosed (< 0.02%)[1]; Vanadium; Talc; Ethanone, 2-hydroxy-1,2-diphenyl-; bis(2,4-dicumylphenyl) neopentyl diphosphite; 3,9-bis[2,4-bis(1-methyl-1-phenylethyl)phenoxy]-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane

[1]LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- ☐ LBC Red List Free
- ■ LBC Red List Approved
- ☐ Declared

% Disclosed: 99.85% at 100ppm
VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

ARM-0102
EXP. 01 SEP 2025
Original Issue Date: 2024

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare