Declare.

WoodWorks™ - Solid Wood
Armstrong World Industries

Final Assembly: Morristown, Tennessee, USA; Beverly, West Virginia, USA
Life Expectancy: 30 Year(s)
Embodied Carbon: 0.583 kg CO2eq
Declared Unit: 1 square foot of product
End of Life Options: Salvageable/Reusable in its Entirety, Landfill (100%)

Ingredients:

Kiln dried wood; Titanium dioxide; Triethanolamine; Undisclosed (< 0.51%)[1]; 2-Propanol, 1-methoxy-; Water; 2-Propenoic acid, 1,6-hexanediyl ester; oxybis(methyl-2,1-ethanediyl) diacrylate; Ethanol, 2-propoxy-; Black Tint; Glycol Ether; 2-Propanol, 1-methoxy-, acetate; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Amorphous Silica; Chromate(1-), hydroxy[2-hydroxy-3-[[(2- hydroxy-3-nitrophenyl)methylene]amino]-5-nitrobenzenesulfonato (3-)]-, hydrogen, compd. with 3-[(2-ethylhexyl)oxy]-1-propanamine (1:1); Isopropyl alcohol; Tint; White Tint; Chromium, 2-[2-(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)diazenyl]benzoate 2-[2-(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)diazenyl]-5-sulfobenzoate lithium sodium complexes; 2-Butoxyethanol; Chromate(3-), bis[3-hydroxy-4-[(2-hydroxy- 1-naphthalenyl)azo]-7-nitro-1-naphthalenesulfonato (3-)]-, trisodium; Ethanol; Methanone, (1-hydroxycyclohexyl)phenyl-; Talc; Trimethylolpropane Triacrylate/2-Hydroxypropyl Acrylate; 1-Propanone, 2-hydroxy-2-methyl-1-phenyl-; 1,3-Propanediol, 2,2-bis(hydroxymethyl)-, polymer with 2-methyloxirane and oxirane, 2-propenoate; Poly(oxy-1,2-ethanediyl), α-hydro-ω-[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1); Silica Gel; 1,3-Propanediol, 2,2-bis(hydroxymethyl)-, polymer with (chloromethyl)oxirane, 2-propenoate; Amines, C10-14-branched and linear alkyl, [1-[(2-hydroxy-4-nitrophenyl) azo]-2-naphthalenolato(2-)][1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]chromate(1-); ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate; phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide; Phosphine oxide; Poly[oxy(methyl-1,2-ethanediyl)], α,α′,α″- 1,2,3-propanetriyltris[ω-[(1-oxo-2-propenyl)oxy]-; Undisclosed (< 0.015%)[1]; 1,2-Propanediol, diacetate; 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-

[1]LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- ☐ LBC Red List Free
- ■ LBC Red List Approved
- ☐ Declared

% Disclosed: 99.48% at 100ppm
VOC Content: Not Applicable

I-10 Interior Performance: Not Applicable
I-14 Responsible Sourcing: Product Available with FSC Chain of Custody; Low Risk Wood

ARM-0081
EXP. 01 MAY 2026
Original Issue Date: 2022