



CALLA® Templok®

Tegular and Square Lay-in
smooth texture




**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Learn How Templok 
Ceilings Save Energy!



Calla® Templok Square Tegular panels with Suprafine® 9/16" suspension system

Maximize the comfort of your indoor spaces with this smooth-textured mineral fiber ceiling that combines exceptional acoustical performance, energy savings, and sustainability attributes — all in one panel.

KEY SELECTION ATTRIBUTES

- Saves up to 15% energy*
- Improve thermal comfort with ceilings that help regulate indoor temperatures
- Calla® Templok® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Provides up to 50 BTUs/SF of passive cooling*
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels:
NRC + CAC = Total Acoustics performance
- Exceptional sound-blocking performance for enhanced speech privacy: CAC 39
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Energy-saving, high light-reflective finish
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

* Measured cooling energy savings in lab test. Results may vary. See Templok Technical Guide.

TYPICAL APPLICATIONS

- Office
- Education
- Transportation
- Healthcare

COLOR



White
(WH)




Save up to 50% in Tax Credits

Templok® ceilings may qualify for Investment Tax Credits (ITC) under Inflation Reduction Act of 2022, Section 48E

Learn more at armstrongceilings.com/saveontemplok 

DETAILS (Other suspension systems compatible. Refer to listing on next page.)



1. Calla® Templok® Square Tegular panel
2. Calla Templok back of panel
3. Calla Templok with Suprafine® 9/16" suspension system

TechLine 877 276-7876

armstrongceilings.com/callatemplok

Armstrong®
World Industries



CALLA® Templok®

Tegular and Square Lay-in
smooth texture

Declare.

RECYCLED
CONTENT

UP TO
41%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health

Declare Label

Climate Health

EPD

HPD

Ecosystem Health

EPD

3rd Party CDPH

Circular Economy

✓

OCCUPANT EXPERIENCE

Acoustics

✓

ENERGY AND ATMOSPHERE

Reduced Peak Thermal Loads

✓

Energy Efficiency

✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CALLA® Templok® Field Panel*	29, 44, 48, 52, 56	2824TEMP	24 × 24 × 1-1/4"
9/16" Square Tegular		2825TEMP	24 × 48 × 1-1/4"
CALLA Border Panel*		2824	24 × 24 × 1"
9/16" Square Tegular		2825	24 × 48 × 1"
CALLA Templok Field Panel*		2822TEMP	24 × 24 × 1-1/4"
15/16" Square Tegular		2823TEMP	24 × 48 × 1-1/4"
CALLA Border Panel*		2822	24 × 24 × 1"
15/16" Square Tegular		2823	24 × 48 × 1"
CALLA Templok Field Panel*		2820TEMP	24 × 24 × 1-1/4"
15/16" Square Lay-in		2821TEMP	24 × 48 × 1-1/4"
CALLA Border Panel*		2820	24 × 24 × 1"
15/16" Square Lay-in		2821	24 × 48 × 1"

* Specify field and border panels together. Field panels cannot be cut.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)


PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$\$

NRC	CAC	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	39	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*
0.85	35	BEST	Class A	0.85	*	*	*	*	*	*	*	*	*	*	*

SUSPENSION SYSTEMS



Blizzard White – Suspension System Finish

A color and texture coordinated suspension system to complement Calla® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material

Wet-formed mineral fiber with acoustically transparent membrane and metalized film with salt hydrate

Surface Finish

Acoustically transparent membrane with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification

Type A, Form A2.2, Pattern G; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Thermal Energy Storage Capacity

Stores a minimum of 50 BTUs/SF from 62°F to 83°F per ASTM C1784-20

VOC Emissions

Compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system for 9/16" edge detail.

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Twenty (20) Year Limited Thermal Energy Storage Capacity Warranty

Weight; Square Feet/Carton

2824TEMP, 2822TEMP, 2820TEMP, 2825TEMP, 2823TEMP, 2821TEMP – 1.9 LBS/SF; 16 SF/CTN

Minimum Order Quantity

1 carton

TechLine / 877 276-7876
armstrongceilings.com/callatemplok
BPCS-7362-1025

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute; WELL® and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard