

CANYON®
Square Lay-in & Tegular
smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

Canyon Beveled Tegular panels with Prelude XL 15/16" suspension system

Smooth-texture panel with both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics ceiling panels: NRC + CAC = Total Acoustics Performance
- Canyon® is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- Smooth, white surface
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Good combination of acoustical performance; NRC 0.65 and CAC 35
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- 10-Year replacement panel available for items 1490, 1491, 1492, 1493, 1494, 1495



COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Canyon Square Lay-in
2. Canyon Square Lay-in with Prelude® XL 15/16" suspension system

CANYON®

Square Lay-in & Tegular

smooth texture



Declare.

RECYCLED
CONTENT
UP TO
44%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CANYON®	1	1490	24 × 24 × 5/8" □
15/16" Square Lay-in		1491	24 × 48 × 5/8" □
15/16" Beveled Tegular	15	1492	24 × 24 × 5/8" □
		1493	24 × 48 × 5/8" □
9/16" Beveled Tegular	44, 48, 29, 52, 56	1494	24 × 24 × 5/8" □
		1495	24 × 48 × 5/8" □
Made-to-Order Sizes			
		5/8" Thick – 15/16" Square Lay-in, 15/16" & 9/16" Beveled Tegular	
		Width	Length
		12" – 24"	18" – 72"

4-6
WEEKS
order to ship

PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =	NRC + CAC	Fire Class		Anti-Mold/Mildew	Sag Resistant					
0.65 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*
0.65 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*
0.65 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*
0.65 35	GOOD	Class A	0.80	*	*	*	Std	Std	*	*
N/A N/A	N/A	Class A	0.80	*	*	*	Std	Std	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Mineral fiber with acoustically transparent membrane.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type A, Form A2.2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted on Silhouette suspension system

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong Suspension System. Details at armstrongceilings.com/warranty

Cleaning and Disinfecting
Cleaning and CDC-approved disinfecting options available on armstrongceilings.com/cleaning

Weight; Square Feet/Carton
0.76 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton, excludes made-to-order panels

TechLine / 1 877 276-7876
armstrongceilings.com/canyon
BPCS-4912-925

LEED® is a trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are trademarks of the International Living Future Institute; WELL® and WELL Building Standard are trademarks of the International WELL Building Institute; Revit® is a registered trademark of Autodesk, Inc.; UL is a registered trademark of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard