

CIRRUS® Second Look®

Scored Tegular
medium texture




**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Cirrus® Second Look® III panels with Suprafine® XL® 9/16" suspension system

See more photos at:
armstrongceilings.com/photogallery
SEARCH: cirrus

Medium texture panels with a scored plank visual: Offer both Sustain® and Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES


- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Classic Cirrus texture
- Excellent score line painting for a clean visual
- Mold- and mildew-resistant surface
- USDA-Certified Biobased Product – 91%

COLOR




White
(WH)

FACE VIEW



Cirrus® Second Look® I panel –
Scoring creates nominal 12" x 12" squares



Cirrus® Second Look® II panel –
Scoring creates nominal 24" x 24" squares



Cirrus® Second Look® III panel –
Scoring creates nominal 6" x 48" linear planks

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Cirrus® Second Look® III
2. Cirrus® Second Look® III with Suprafine® 9/16" suspension system

CIRRUS® Second Look®

Scored Tegular
medium texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 91%

SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC

UP TO 67% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CIRRUS® Second Look® I 15/16" Beveled Tegular	14	512	24 x 48 x 3/4"	
CIRRUS® Second Look® II 9/16" Beveled Tegular	28	510	24 x 48 x 3/4"	
15/16" Beveled Tegular	14	513	24 x 48 x 3/4"	
CIRRUS® Second Look® III 9/16" Beveled Tegular	28	511	24 x 48 x 3/4"	
15/16" Beveled Tegular	14	514	24 x 48 x 3/4"	

PERFORMANCE SELECTION


Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	10-Yr
0.65	35	GOOD	Class A	0.85	•	Std	•	Std	•	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 1, Pattern E I K
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Insulation Value
R Factor – 1.9 (BTU units)
R Factor – 0.33 (Watts units)

Design Consideration
Do not mix Cirrus® Second Look® with standard Cirrus items in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1.09 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
512M, 510M, 513M, 511M, 514M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER – Standard