

CIRRUS® High NRC CIRRUS®

Square Lay-in
medium texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFLEX®
A New World of Choice
for Ceiling Systems



▲ Cirrus Square Lay-in panels with Prelude XL 15/16" suspension system



See more photos at:
armstrongceilings.com/photogallery

Medium-texture panels offer both Sustain® and Total Acoustics® panel performance; good noise reduction and sound blocking in one panel.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Cirrus® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Refined visual
- Excellent combination of acoustical performance NRC up to 0.75 and CAC 35
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- High NRC items feature Articulation Class 170, helpful to control sound over wall partitions
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 574HRC and 533HRC. 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 91%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

DETAILS



1. Cirrus® Square Lay-in
2. Cirrus® Square Lay-in with Prelude® XL® 15/16" suspension system

TechLine 877 276-7876
armstrongceilings.com/cirrus

Armstrong®
World Industries

CIRRUS® High NRC

CIRRUS®

Square Lay-in
medium texture



Declare®

RECYCLED
CONTENT
UP TO
87%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CIRRUS® High NRC	1	563	24 x 24 x 7/8"
15/16" Square Lay-in		565	24 x 48 x 7/8"
7/8" Thick - 15/16" Square Lay-in			
Made-to-Order Sizes		Width	Length
CIRRUS® High NRC		12" - 24"	24" - 48"
CIRRUS®	1	574	24 x 24 x 3/4"
15/16" Square Lay-in		574HRC	24 x 24 x 3/4"
		533	24 x 48 x 3/4"
		533HRC	24 x 48 x 3/4"
3/4" Thick - 15/16" Square Lay-in			
Made-to-Order Sizes		Width	Length
CIRRUS®		12" - 24"	24" - 48"

3-4
WEEKS
order to ship

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Durability	Recycle Program	30-Yr Warranty
NRC + CAC =	NRC CAC	AC	Fire	Light	Anti-Mold/Mildew	Sag	VOC	CleanAssure™	Fog	Durability	Recycle Program	30-Yr Warranty
0.75	35	BETTER	170	Class A	0.84	*	Std	*	*	Std	*	10-Yr
0.75	35	BETTER	170	Class A	0.84	*	Std	*	*	Std	*	10-Yr
N/A	N/A	N/A	N/A	Class A	0.84	*	Std	*	*	Std	*	10-Yr
0.70	35	BETTER	N/A	Class A	0.85	*	Std	*	*	Std	*	10-Yr
0.70	35	BETTER	N/A	Class A	0.85	*	Std	*	*	Std	*	10-Yr
N/A	N/A	N/A	N/A	Class A	0.85	*	Std	*	*	Std	*	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type A, Form A1.2, Pattern F; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. Excludes items 533, 533HRC, 565, and large sizes.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustic Performance
CAC testing conducted using Prelude® suspension system.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
R Factor - 1.9 (BTU units); R Factor - 0.33 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
533, 533HRC, 565 - 1.21 LBS/SF; 48 SF/CTN
563 - 1.33 LBS/SF; 40 SF/CTN
574, 574HRC - 1.10 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton, excludes Cirrus® High NRC panels

Metric Items Available
574M, 533M, 563M, 565M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.