

CIRRUS® Themes™ Critters™, Leaves™, Stars™, Things That Fly™ & Under the Sea™

Tegular
medium texture



Cirrus® Themes™ Critters™ panels with Suprafine® XL 9/16\"/>

Medium texture panels with playful designs for a fun addition to your projects.

KEY SELECTION ATTRIBUTES

- A variety of lighthearted panel designs on classic Cirrus texture; can be spot-painted
- Cirrus® Themes™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Coordinating plain panels available
- Mold- and mildew-resistant surface
- USDA-certified Biobased Product – 91%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)



Cirrus® Themes™ Stars™ panels with Suprafine XL 9/16\"/>



Cirrus® Themes™ Leaves™ panels with Suprafine XL 9/16\"/>



Cirrus® Themes™ Things That Fly™ panels with Suprafine XL 9/16\"/>



Cirrus® Themes™ Under The Sea™ panels with Suprafine XL 9/16\"/>

CIRRUS® Themes™ Critters™, Leaves™, Stars™, Things That Fly™ & Under the Sea™

Tegular
medium texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 91%

SUSTAIN™
High Performance
Sustainable Ceiling Systems
Declare®

RECYCLED
CONTENT
UP TO
72%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
CIRRUS® Themes™ 15/16" Angled Tegular	13	See Below	24 × 24 × 3/4" □
9/16" Beveled Tegular	29, 44, 48, 52, 56	See Below	24 × 24 × 3/4" □

PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
N/A	N/A	N/A	Class A	0.85 *	•	Std	•	Std	•	10-Yr
N/A	N/A	N/A	Class A	0.85 *	•	Std	•	Std	•	10-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

All images shown in plan view.

CIRRUS Themes Critters	CIRRUS Themes Leaves	CIRRUS Themes Stars	CIRRUS Themes Things That Fly	CIRRUS Themes Under the Sea	Plain Panel
S500/S550 S501/S551 S502/S552 S503/S553 S510/S560 S512/S562	S600/S650 S601/S651 S602/S652 S603/S653 S604/S654 S605/S655	S400/S450 S401/S451 S410/S460 S411/S461 S412/S462 S413/S463 S414/S464 S420/S470 S421/S471	S700/S750 S701/S751 S702/S752 S703/S753 S704/S754 S705/S755 S706/S756 S707/S757 S708/S758	S800/S850 S801/S851 S802/S852 S803/S853 S804/S854 S805/S855	S299/S295

Must use Item S295 or S299 for Coordinating Plain Panel

CIRRUS Themes Critters	CIRRUS Themes Leaves	CIRRUS Themes Stars	CIRRUS Themes Things That Fly	CIRRUS Themes Under The Sea
15/16" Angled Tegular	15/16" Angled Tegular	15/16" Angled Tegular	15/16" Angled Tegular	15/16" Angled Tegular
S550 S551 S552 S553 S560 S562 S295	S500 S501 S502 S503 S650 S651 S652 S653 S654 S655 S295	S450 S451 S460 S461 S462 S463 S464 S470 S471 S295	S400 S401 S410 S411 S412 S413 S414 S420 S421 S295	S750 S751 S752 S753 S754 S755 S756 S757 S758 S295
9/16" Beveled Tegular	9/16" Beveled Tegular	9/16" Beveled Tegular	9/16" Beveled Tegular	9/16" Beveled Tegular
S500 S501 S502 S503 S510 S512 S299	S600 S601 S602 S603 S650 S651 S652 S653 S654 S655 S299	S450 S451 S460 S461 S462 S463 S464 S470 S471 S295	S400 S401 S410 S411 S412 S413 S414 S420 S421 S295	S700 S701 S702 S703 S704 S705 S706 S707 S708 S299

SUSPENSION SYSTEMS

15/16" Prelude®	9/16" Silhouette® 1/4" Reveal	Silhouette® 1/8" Reveal	Suprafine®	Interlude® XL® HRC
-----------------	-------------------------------	-------------------------	------------	--------------------

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies.

ASTM E1264 Classification
Type A, Form A1.2, Pattern F, I; Fire Class A

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.9 (BTU units); R Factor – 0.33 (Watts units)

Warranty

Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton

All design panels – 1.38 LBS/SF; 8 SF/CTN
S295 – 1.09 LBS/SF; 48 SF/CTN
S299 – 1.17 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/cirrusthemes
BPCS-4332-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard