

DESIGNER™

Square Lay-in & Tegalur
coarse texture



Declare.

RECYCLED
CONTENT
UP TO
42%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	3rd Party CDPH	Ecosystem Health	EPD
		Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

\$\$\$\$



Designer™ Lay-in panels with Prelude® XL 15/16" suspension system

Coarse-texture panels; economical option with standard acoustical performance.

KEY SELECTION ATTRIBUTES

- Standard sound absorption
- Cost-effective
- Designer™ is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
DESIGNER™ 15/16" Square Lay-in	1	735	24 × 24 × 5/8"
		734	24 × 48 × 5/8"
15/16" Angled Tegalur	13	737	24 × 24 × 5/8"


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 30	N/A	Class A	0.81	N/A	Std	*	Std	Std	*	1-Yr
0.55 30	N/A	Class A	0.81	N/A	Std	*	Std	Std	*	1-Yr
0.55 33	N/A	Class A	0.81	N/A	Std	*	Std	Std	*	1-Yr

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type A, Form A1.2, Pattern F; Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

1-Year Limited Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton
734 – 0.80 LBS/SF; 80 SF/CTN
735, 737 – 0.80 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
735M, 734M, 737M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/designer
BPCS-3024-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) area registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard