

FINE FISSURED™ Second Look®

Scored Tegular
medium texture



Declare.

RECYCLED
CONTENT

UP TO
56%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

\$\$\$\$



Fine Fissured Second Look II panels with Suprafine XL 9/16" suspension system

Economical panels; Scored plank or geometric visual with standard acoustical performance.

KEY SELECTION ATTRIBUTES


- Fine Fissured™ Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Geometric scored visuals
- Economical option to create a designer look
- Mold- and mildew-resistant surface
- 10-Year replacement panel available for item 1761
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant



COLOR



FACE VIEW



Second Look® I



Second Look® II



Second Look® III

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)		
FINE FISSURED™ Second Look®	11	1760	24 × 48 × 3/4"		Second Look I
15/16" Angled Tegular		1761	24 × 48 × 3/4"		Second Look II
		1861	24 × 48 × 3/4"		Second Look II
		1762	24 × 48 × 3/4"		Second Look III
9/16" Angled Tegular	27	1765	24 × 48 × 3/4"		Second Look I
		1766	24 × 48 × 3/4"		Second Look II

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =				Anti-Mold/Mildew	Sag Resistant					
0.55 35 *	N/A	Class A	0.82	*	*	*	Std	Std	*	*
0.55 35 *	N/A	Class A	0.82	*	*	*	Std	Std	*	*
0.55 35 *	N/A	Fire Guard™	0.82	*	*	*	Std	Std	*	*
0.55 35 *	N/A	Class A	0.82	*	*	*	Std	Std	*	*
0.55 30	N/A	Class A	0.82	*	*	*	Std	Std	*	*
0.55 30	N/A	Class A	0.82	*	*	*	Std	Std	*	*

SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® suspension system. Details at armstrongceilings.com/warranty

Design Consideration

Do not mix Fine Fissured™ Second Look® panels with standard Fine Fissured panels in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

Weight; Square Feet/Carton
0.75 LBS/SF; 80 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available

1761M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/finefissured
BPCS-3027-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

