

# FINE FISSURED™ FINE FISSURED™ High NRC

Tegular  
medium texture



**TOTAL  
ACOUSTICS®**  
Sound Absorption (NRC)  
+ Sound Blocking (CAC)



**SUSTAIN®**  
High Performance  
Sustainable  
Ceiling Systems

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Fine Fissured Tegular panels with Prelude XL suspension system



See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)

Economical panels; non-directional with standard or Total Acoustics® panel performance.

## KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Fine Fissured panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Four new colors
- Mold- and mildew-resistant surface
- Options provide excellent combination of acoustical performance NRC up to 0.75, CAC up to 35, and Articulation Class 170
- Fine Fissured™ School Zone® items help comply with ANSI S12.60 Classroom Guidelines
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- 10-Year replacement panel available for items 1732, 1734
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant




## COLORS Due to printing limitations, shade may vary from actual product.



Item 1732 is available in colors.  
All other items are available in White only.  
Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.

## DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Fine Fissured™ Beveled Tegular
2. Fine Fissured™ Angled Tegular
3. Fine Fissured™ Tegular with Suprafine® 9/16" suspension system

# FINE FISSURED™ FINE FISSURED™ High NRC

Tegular  
medium texture



Declare.

RECYCLED  
CONTENT

UP TO  
**73%**

LEED V5

Ecomedes Data

## COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No. ♦	Dimensions (Inches)
FINE FISSURED™ High NRC	13	1756	24 × 24 × 7/8" □
15/16" Angled Tegular		1757	24 × 48 × 7/8" □
9/16" Beveled Tegular	29, 44, 48, 52, 56	1758	24 × 24 × 7/8" □
		1759	24 × 48 × 7/8" □
FINE FISSURED™ 15/16" Angled Tegular	12	1732__	24 × 24 × 5/8" □
		1833	24 × 24 × 5/8" □
		1733	24 × 48 × 5/8" □

## PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.75 *	35 *	BETTER ( )))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.75 *	35 *	BETTER ( )))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.75 *	35 *	BETTER ( )))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.55 *	35 *	N/A	N/A	Class A	0.82* *	*	*	*	*	Std	*	*	*
0.55 *	35 *	N/A	N/A	Fire Guard™	0.82 *	*	*	*	*	Std	Std	*	*
0.55 *	35 *	N/A	N/A	Class A	0.82 *	*	*	*	*	Std	Std	*	*

MORE ITEMS ►


Red Numbers are Fire Guard items.

<sup>1</sup> Total Acoustics\* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

♦ Add 2-letter color suffix to item number when specifying or ordering (e.g., 1732 | V)

\* Light reflectance value for white panels only

## SUSPENSION SYSTEMS



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL\* labeled).

Fire Guard™: A fire-resistant ceiling when used in applicable UL assemblies. (Class A).

### ASTM E1264 Classification

Type A, Form A1.2, Pattern D; Fire Class A

### Humidity/Sag Resistance

HumiGuard™ Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications (excludes items 1757 and 1759).

### Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Acoustical Performance

CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

### High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

### Insulation Value

R Factor – 1.5 (BTU units); R Factor – 0.26 (Watts units)

### Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

### 30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

### Weight; Square Feet/ Carton

1732 – 0.70 LBS/SF; 64 SF/CTN  
1733 – 0.70 LBS/SF; 80 SF/CTN  
1833 – 1.05 LBS/SF; 48 SF/CTN  
1756, 1758 – 1.08 LBS/SF; 40 SF/CTN  
1757, 1759 – 1.08 LBS/SF; 48 SF/CTN

### Minimum Order Quantity

1 carton

### Metric Items Available

1732M, 1733M, 1756M, 1757M, 1758M, 1759M – Metric items subject to extended lead times and minimum quantities.

TechLine 877 276-7876

armstrongceilings.com/finefissured

**Armstrong®**  
World Industries

MINERAL FIBER – Standard

# FINE FISSURED™ FINE FISSURED™ High NRC

Tegular  
medium texture



Declare.

RECYCLED  
CONTENT

UP TO  
**73%**

LEED V5

Ecomedes Data

## COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

## VISUAL SELECTION

## PERFORMANCE SELECTION

\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
FINE FISSURED™ 15/16" Angled Tegular	1	1834	24 × 48 × 5/8"

9/16" Beveled Tegular	29, 44, 48, 52, 56	1734	24 × 24 × 5/8"
-----------------------	--------------------	------	----------------

1835	24 × 24 × 5/8"
------	----------------

Made-to-Order Sizes	Width	Length
FINE FISSURED™	12" - 30"	18" - 72"

School Zone® FINE FISSURED™ 15/16" Angled Tegular	13	1717	24 × 24 × 3/4"
---	----	------	----------------

1820	24 × 24 × 3/4"
------	----------------

1824	24 × 48 × 3/4"
------	----------------

UL Classified Acoustics	Total Acoustics¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.55	35	N/A	N/A	Fire Guard™	0.82	*	*	*	*	Std	*	*	*
0.55	35	N/A	N/A	Class A	0.82	*	*	*	*	Std	Std	*	*
0.55	35	N/A	N/A	Fire Guard	0.82	*	*	*	*	Std	Std	*	*
0.70	40	BETTER	N/A	Class A	0.82	*	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard	0.82	*	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard	0.82	*	*	*	*	Std	*	*	*

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

MINERAL FIBER – Standard

# FINE FISSURED™ FINE FISSURED™ High NRC

Tegular  
medium texture



Declare.

RECYCLED  
CONTENT

UP TO  
**73%**

LEED V5

Ecomedes Data

## COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
School Zone® FINE FISSURED™ 9/16" Beveled Tegular	29, 44, 48, 52, 56	1719	24 × 24 × 3/4" □
		1821	24 × 24 × 3/4" □

Made-to-Order Sizes	Width	Length
School Zone® FINE FISSURED™	12" - 30"	18" - 72"

**4-6**  
WEEKS  
order to ship

## PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics	Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.70	40	BETTER	N/A	Class A	0.82	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard™	0.82	*	*	*	Std	*	*	*

Red Numbers are Fire Guard items.

<sup>1</sup> Total Acoustics\* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS

15/16"	9/16"
Prelude® XL® Prelude® XL® Fire Guard™	Silhouette® 1/4" Reveal
	Silhouette® 1/8" Reveal
	Suprafine® Suprafine® XL® Fire Guard™
	Interlude®

## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL\* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

**ASTM E1264 Classification**  
Type A, Form A1.2, Pattern D; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 1.5 (BTU units); R Factor – 0.26 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
1820, 1821 – 1.31 LBS/SF; 48 SF/CTN  
1717, 1719 – 1.25 LBS/SF; 48 SF/CTN  
1834 – 1.05 LBS/SF; 64 SF/CTN  
1734 – 0.70 LBS/SF; 64 SF/CTN  
1835 – 1.05 LBS/SF; 48 SF/CTN  
1824 – 1.20 LBS/SF; 64 SF/CTN

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

**Metric Items Available**  
1820M, 1821M, 1717M, 1719M, 1834M, 1734M, 1824M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.