

FINE FISSURED™

Tile
medium texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

Fine Fissured tile with Prelude® Concealed 15/16" suspension system

Tiles have a grid-hiding, monolithic visual; non-directional with standard acoustical performance and concealed or tongue-and-groove installation options.

KEY SELECTION ATTRIBUTES

- 12" x 12" concealed tile option provides grid-hiding monolithic installation
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Fine Fissured panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

FINE FISSURED™

Tile
medium texture



Declare.

RECYCLED
CONTENT

UP TO
56%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
FINE FISSURED® Tile	66	746	12 × 12 × 5/8" □
Concealed			
Tongue-and-Groove	63	741	12 × 12 × 1/2" □

PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =											
0.55 35	N/A	Class A	0.82	*	*	*	*	Std	*	*	*
0.55 N/A	N/A	Class A	0.82	*	*	*	*	Std	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Splines not included in carton. Not recyclable when glue-up installation method is used.

SUSPENSION SYSTEM

15/16" Concealed
Prelude® Concealed or Adhesive

ADHESIVE

Tongue-and-Groove

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight: Square Feet/Carton
741 – 0.75 LBS/SF; 40 SF/CTN
746 – 0.90 LBS/SF; 40 SF/CTN

Minimum Order Quantity
1 carton