

FISSURED™

Square Lay-in & Tegular
medium texture

RECYCLED
CONTENT

LEED V5

Ecomedes Data

UP TO
41%

Declare.

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health
	HPD	Ecosystem Health
	3 rd Party CDPH	Circular Economy
OCCUPANT EXPERIENCE		Acoustics

\$\$\$\$

Economical panels; Directional with standard acoustical performance.

KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)











Fissured Angled Tegular panels with Prelude® XL® 15/16" suspension system

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.


armstrongceilings. com/suspdwgs		Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/ Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
					NRC +	CAC	=									
FISSURED™ Square Lay-in		1	756	24 × 24 × 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
15/16" Square Lay-in			896	24 × 24 × 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
			755	24 × 48 × 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
			895	24 × 48 × 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
FISSURED™ Tegular		12	705	24 × 24 × 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
15/16" Angled Tegular			815	24 × 24 × 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
																
5/8" Thick – 15/16" Square Lay-in & Tegular																
Made-to-Order Sizes			Width	Length	N/A	N/A	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
			12" - 30"	18" - 72"												

4-6
WEEKS
order to ship

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value

755, 756, 895, 896 – R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)
705, 815 – R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

1-Year Limited Warranty

Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton

705 – 0.69 LBS/SF; 64 SF/CTN 815 – 1.08 LBS/SF; 48 SF/CTN
755 – 0.66 LBS/SF; 96 SF/CTN 895, 896 – 1.09 LBS/SF;
756 – 0.67 LBS/SF; 64 SF/CTN 64 SF/CTN

Minimum Order Quantity

1 carton, excludes made-to-order panels

Metric Items Available

756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.