

TUNDRA®
Square Lay-in & Tegular
medium texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

Tundra panels with Suprafine XL 9/16" suspension system

Medium-texture panels that are impact- and scratch-resistant, with standard sound absorption and high sound blocking.

KEY SELECTION ATTRIBUTES

- Tundra panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Durable
 - Impact-resistant
 - Scratch-resistant
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1



2

1. Tundra® Beveled Tegular
2. Tundra with Suprafine® XL 9/16" suspension system

TUNDRA®

Square Lay-in & Tegular medium texture



Declare.

RECYCLED CONTENT
UP TO
35%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
TUNDRA®	1	301	24 × 24 × 5/8"	
15/16" Square Lay-in		302	24 × 48 × 5/8"	
15/16" Beveled Tegular	15	303	24 × 24 × 5/8"	
		305	24 × 48 × 5/8"	
9/16" Beveled Tegular	29, 44, 48, 52, 56	304	24 × 24 × 5/8"	
Made-to-Order Sizes				

4-6
WEEKS
order to ship

5/8" Thick – 15/16" Square Lay-in, 9/16" & 15/16" Beveled Tegular

Width	Length
24"	24" - 48"

PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	DURABILITY Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
NRC + CAC =											
0.50 33	N/A	Class A	0.86 *	*	*	N/A	*	*	Std	*	*
0.50 35 *	N/A	Class A	0.86 *	*	*	N/A	*	*	Std	*	*
0.50 33	N/A	Class A	0.86 *	*	*	N/A	*	*	Std	*	*
0.50 35 *	N/A	Class A	0.86 *	*	*	N/A	*	*	Std	*	*
0.50 33	N/A	Class A	0.86 *	*	*	N/A	*	*	Std	*	*
N/A N/A N/A		Class A	0.86 *	*	*	N/A	*	*	Std	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed, high-density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type A, Form A1.2, Pattern E; Fire Class A

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Acoustical Testing
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

Insulation Value
R Factor – 1.7 (BTU units)
R Factor – 0.30 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
301, 302, 305 – 1.09 LBS/SF; 64 SF/CTN
303, 304 – 1.10 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
302M, 303M, 305M, 304M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/tundra
BPCS-3038-925

LEED® is a trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a trademark of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard

