ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Square Lay-in fine texture







CAD/Revit® drawings at: armstrongceilings.com/cadrevit



Ultima® Health Zone™ Square Lay-in panels with Prelude® XL® 15/16" suspension system

Perfect for office, education, and healthcare spaces

Fine texture mineral fiber ceiling; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew BioBlock® Plus performance resists the growth of odor and stainproducing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanability impact-, scratch-, and soil-resistant
- CleanAssure[™] safe for use with disinfectant cleaners
- Clean + Simple Ultima® panels are part of the Sustain® portfolio and are free of Red List chemicals for better indoor air quality
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems
- Long-lasting water-repellency; washable and scrubbable
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth

TYPICAL APPLICATIONS

Healthcare:

- · Patient rooms
- · Treatment rooms
- · Nurses' stations
- · Emergency rooms
- Corridors
- · Lavatories and restrooms
- · Kitchen/food prep areas

Education Office

Clean Rooms (item 1935)

COLOR



DETAILS





- 1. Ultima® Health Zone™ Square Lay-in
- Ultima® Health Zone™ High NRC Square Lay-in panels with Clean Room™ 15/16" suspension system



Square Lay-in fine texture

USDA CERTIFIED BIOBASED PRODUCT

SUSTAIN* Sustainable Ceiling Systems

GREENGUARD Gold Certified (details below) Declare.



Calculate sustainability with Green Genie® armstrongceilings.com/greengenie

LOCATION DEPENDENT

PERFORMANCE SELECTION Dots represent high level of performance. VISUAL SELECTION

\$\$\$\$

| | | | | | | | | e t | Bio- Humi- Block+ Guard+ | w. ons | CleanAssure™ Disinfectable Panels | | | DURABILITY | | | | | nty | | |
|--|---------------------|-------------------|----------------------------|----------|-------------------|-----------------|--------------------|------------------|-----------------------------|--|--------------------------------------|--------------------------------|-------------|------------|-------------|-----------|-------|--------|---------|------|----------------|
| armstrongceilings com/suspdwgs | | Item No. | Dimensions (Inches) | Acou | ssified ustics | Total Acoustics | Articulation Class | Fire Performance | Light Reflect | Anti- Bacterial/ Mold/ Mildew | Sag Resistant | Certified Low VOC Emissions | Spray Spray | Wipe | Water Repel | Mash Wash | Scrub | Impact | Scratch | Soil | 30-Yr Warranty |
| ULTIMA® Health Zone" High NRC 15/16" Square Lay-in | 1, 6 | 1445 | 24 × 24 × 7/8" | 0.80 | 35 | BEST | 170 | Class (| 0.86 | + | ٠ | • | ٠ | • | • | • | • | • | ٠ | • | • |
| | | 1448* | 24 × 48 × 7/8" | 0.80 | 35 | BEST (i)) | 170 | Class (| 0.86 | + | ٠ | 0 | • | ٠ | • | • | 0 | 0 | • | • | • |
| ULTIMA Health Zone 15/16" | 1, 6 | 1935 | 24 × 24 × 3/4" | 0.70 | 38 | BETTER | N/A | Class (| 0.86 | + | ٠ | ٠ | ٠ | ٠ | ٠ | ٠ | ۰ | ٠ | ٠ | • | • |
| Square Lay-in | | 1938* | 24 × 48 × 3/4" | 0.70 | 38 | BETTER (III) | N/A | Class (| 0.86 | + | • | ۰ | • | 0 | • | ۰ | ۰ | ٠ | ٠ | • | • |
| | | 3/4" or | 7/8" Thick - 15/16" Squ | are Lay- | in | | | | | | | | | | | | | | | | |
| Made-to-Order Sizes FAS | tn Min | Width (short s | Length ide) (long side) | N/A | N/A | N/A | N/A | Class (| 0.86 | + | ٠ | ۰ | ۰ | ٠ | ٠ | ۰ | ۰ | ٠ | ٠ | • | • |
| | VEEKS er to ship | 4" - 30' | 12" - 72" | | | | | | | | | | | | | | | | | | |
| Visit the product page online and see "Configure an Item" to | • | | | | | | | | | | | | | | | | | | | | |

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Item does not have painted edges

verify capabilities. Questions? email Techline@armstrongceilings.com

SUSPENSION SYSTEMS

15/16





Clean Room (Steel or Aluminum)

PHYSICAL DATA

Wet-formed mineral fiber with DuraBrite® acoustically

transparent water-repellent membrane Surface Finish

DuraBrite with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification

Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions

PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
Iblic UL 2818 **GREENGUARD Gold Certified** Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES

Standard 189; ANSI/GBI Green Building Assessment Protocol

Acoustical Performance CAC testing conducted using Prelude suspension system.

Primary (Embodied) Energy See all LCA information on our EPDs.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

ŪĹ

GREENGUARD

R Factor - 2.9 (BTU units) R Factor - 0.445 (Watts units)

Cleaning and Disinfecting Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton 1448, 1938 – 1.08 lbs/SF; 48 SF/ctn 1445 – 1.0 lbs/SF; 40 SF/ctn 1935 – 1.0 lbs/SF; 48 SF/ctn

Minimum Order Quantity

TechLine / 1877 276-7876 armstrongceilings.com/healthzone MINERAL FIBER – Standarc