

# ULTIMA® ULTIMA® High NRC

Square Lay-in  
fine texture




CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Ultima Square Lay-in panels with Prelude XL 15/16" suspension system

*A ceiling that saves energy! Learn more*



Smooth-texture panels that are washable, impact- and scratch-resistant with a non-directional visual; offers both Sustain® and Total Acoustics® panel performance for flexible spaces.

## KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Ultima® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface




- High sound absorption options available up to 0.85 NRC
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1910HRC, 1913HRC 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 95%
- Items available with AirGuard® coating which actively removes formaldehyde from indoor air
- Item 1910 available with Create!™ printed images and patterns

## COLOR



White  
(WH)

## DETAILS



1. Ultima® Square Lay-in
2. Ultima® Square Lay-in with Prelude® XL 15/16" suspension system

- Non-directional visual reduces scrap and installation time
- Compatible with the TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag
- 10-Year replacement panel available for items 1910, 1913
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant



## TYPICAL APPLICATIONS

- Offices – closed spaces for privacy and confidentiality; open spaces for focus, collaboration, and teaming
- Healthcare – assists in addressing HIPAA, HCAHPS, and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail



*Ultima Templok  
Energy Saving  
Ceilings*





# ULTIMA® ULTIMA® High NRC

Square Lay-in  
fine texture



RECYCLED  
CONTENT  
UP TO  
**87%**

**LEED V5**

Ecomedes Data

## COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® with AirGuard™ Coating 15/16" Square Lay-in		1900*	24 x 24 x 3/4" □
AirGuard™ Coating actively removes formaldehyde from indoor air.		1903*	24 x 48 x 3/4" □

## PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics		Total Acoustics¹		Articulation Class		Fire Performance		Light Reflect		Bio-Block		Humi-Guard+		CleanAssure™ Disinfectable Panels		DURABILITY					Recycle Program	
NRC	CAC	NRC	CAC	N/A	Class	Fire	Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty				
0.75	35	BETTER	N/A	Class	0.88	*	*	*	*	*	*	*	*	*	*	*	*	*	*			

¹ Total Acoustics\* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

\* Declare label does not apply to these items.

## SUSPENSION SYSTEMS

15/16"	Blizzard White – Suspension System Finish A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.
--------	---

## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

**Surface Finish**  
DuraBrite scrim with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL\* labeled).

**ASTM E1264 Classification**  
Type A, Form A2.2, Pattern E;  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
CAC testing conducted using Prelude® XL\* suspension system.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

**Insulation Value**  
R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight: Square Feet/ Carton**  
1900, 1903, – 1.08 LBS/SF; 48 SF/CTN

**Minimum Order Quantity**  
1 carton