

ULTIMA® ULTIMA® High NRC

Tegular
fine texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit




DESIGNFLEX®
A New World of Choice
for Ceiling Systems

new A ceiling that
saves energy!
Learn more



Ultima Beveled Tegular panels with Silhouette 1/4" reveal 9/16" suspension system



Smooth-texture panels that are washable, impact- and scratch-resistant with a non-directional visual.
Offer both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include shapes and made-to-order sizes available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Ultima® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- High sound absorption options available up to 0.85 NRC
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim

- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: items 1911HRC, 1912HRC, 1914HRC, 1915HRC. 71% Pre-consumer; 15% Post-consumer
- USDA-Certified Biobased Product – 95%
- Items available with AirGuard® coating which actively removes formaldehyde from indoor air
- Item 1912 available with Create!™ printed images and patterns
- Non-directional visual reduces scrap and installation time
- Compatible with the TechZone® Ceiling Systems

- 30-Year Limited System Warranty against visible sag (excludes items 1905 and 1929), mold, and mildew
- 10-Year replacement panel available for items 1911, 1912, 1914, 1915
- Available with factory-cut holes for USAI® trimless downlight fixture integration.
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant




COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Ultima® Beveled Tegular
2. Ultima® with Suprafine® 9/16" suspension system
3. Ultima® with Silhouette® XL® 9/16" suspension system with 1/4" reveal



*Ultima Templok
Energy Saving
Ceilings*

TechLine 877 276-7876
armstrongceilings.com/ultima

Armstrong®
World Industries

Tegular
fine texture



UP TO
87%

LEED v5

Ecomedes Data

COMMON MATERIALS FRAMEWORK			
Human Health	Declare Label HPD	Climate Health	EPD
	3rd Party CDPH	Ecosystem Health	EPD
		Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$

[illegible]

MINERAL FIBER - Standard

ULTIMA® ULTIMA® High NRC

Regular
fine texture



SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

RECYCLED
CONTENT

UP TO
87%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
ULTIMA® 15/16" Beveled Regular	15	1422	6 × 48 × 3/4"	
		1917	12 × 24 × 3/4"	
		1993	12 × 48 × 3/4"	
		1994	12 × 60 × 3/4"	
		1995	12 × 72 × 3/4"	
		1911	24 × 24 × 3/4"	
		1911HRC	24 × 24 × 3/4"	
		1951	24 × 24 × 3/4"	
		1894	24 × 24 × 3/4"	
		4334	30 × 30 × 3/4"	
9/16" Beveled Regular	29, 44, 48, 52, 56	1914	24 × 48 × 3/4"	
		1914HRC	24 × 48 × 3/4"	
		1985	24 × 60 × 3/4"	
		4337	30 × 60 × 3/4"	
		1981	24 × 72 × 3/4"	
		1423	6 × 48 × 3/4"	
		1427	6 × 60 × 3/4"	
		1916	12 × 24 × 3/4"	
		1996	12 × 48 × 3/4"	
		1997	12 × 60 × 3/4"	
9/16" Beveled Regular	29, 44, 48, 52, 56	1998	12 × 72 × 3/4"	
		1912	24 × 24 × 3/4"	
		1912HRC	24 × 24 × 3/4"	
		1952	24 × 24 × 3/4"	
		1895	24 × 24 × 3/4"	
		1915	24 × 48 × 3/4"	
		1915HRC	24 × 48 × 3/4"	
		1986	24 × 60 × 3/4"	
		4336	30 × 60 × 3/4"	
		1982	24 × 72 × 3/4"	

HRC items not included in made-to-order panels.

HRC items not included in made-to-order panels.

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program
NRC	CAC	NRC CAC							
N/A	N/A	N/A	Class A	0.88	*	*	*	Fog	30-Yr Warranty
N/A	N/A	N/A	Class A	0.88	*	*	*	Wash	
0.65*	N/A	N/A	Class A	0.88	*	*	*	Impact	
0.65*	N/A	N/A	Class A	0.88	*	*	*	Scratch	
0.65*	N/A	N/A	Class A	0.88	*	*	*	Soil	
0.75	35	BETTER	Class A	0.88	*	*	*		
0.60	40	GOOD	Class A	0.88	*	*	*		
0.60	40	GOOD	Fire Guard™	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
N/A	N/A	N/A	Class A	0.88	*	*	*		
N/A	N/A	N/A	Class A	0.88	*	*	*		
N/A	N/A	N/A	Class A	0.88	*	*	*		
0.65*	N/A	N/A	Class A	0.88	*	*	*		
0.65*	N/A	N/A	Class A	0.88	*	*	*		
0.65*	N/A	N/A	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.60	40	GOOD	Class A	0.88	*	*	*		
0.60	40	GOOD	Fire Guard	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		
0.75	35	BETTER	Class A	0.88	*	*	*		

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

* Item not UL tested

TechLine 877 276-7876

armstrongceilings.com/ultima

Armstrong®
World Industries

MINERAL FIBER – Standard

ULTIMA® ULTIMA® High NRC

Tegular
fine texture



RECYCLED
CONTENT
UP TO
87%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
9/16" Beveled Tegular	29, 44, 48, 52, 56	1905 1905HRC	30 × 30 × 3/4" 30 × 30 × 3/4"
		1929 1929HRC	30 × 54 × 3/4" 30 × 54 × 3/4"
3/4" Thick – 15/16" & 9/16" Beveled Tegular			
Made-to-Order Sizes		Width (short side)	Length (long side)
Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com		4" – 30"	12" – 72"
ULTIMA® with AirGuard™ Coating	15	1901*	24 × 24 × 3/4"
15/16" Beveled Tegular		1904*	24 × 48 × 3/4"
9/16" Beveled Tegular	29, 44, 48, 52, 56	1902*	24 × 24 × 3/4"
AirGuard™ Coating actively removes formaldehyde from indoor air.		1906*	24 × 48 × 3/4"

¹ Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)


* Declare label does not apply to these items.

PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics		Total Acoustics ¹		Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program	30-Yr Warranty
NRC	CAC	NRC	CAC	Fire	Light	Anti-Mold/Mildew	Sag Resistant			Fog	Wash	Impact	Scratch	Soil	Recycle	
0.75	35	BETTER	Class A	0.88	*	Std	*			*	*	*	*	*	*	
0.75	35	BETTER	Class A	0.88	*	Std	*			*	*	*	*	*	1-Yr	
regular																
N/A	N/A	N/A	Class A	0.88	*	*	*		*	*	*	*	*	*	*	
0.75	35	BETTER	Class A	0.88	*	*	*		*	*	*	*	*	*	*	
0.75	35	BETTER	Class A	0.88	*	*	*		*	*	*	*	*	*	*	
0.75	35	BETTER	Class A	0.88	*	*	*		*	*	*	*	*	*	*	
0.75	35	BETTER	Class A	0.88	*	*	*		*	*	*	*	*	*	*	

SUSPENSION SYSTEMS



Blizzard White – Suspension System Finish
A color and texture coordinated suspension system to complement Ultima® ceiling panels for a monolithic look and feel.

PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish
DuraBrite with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type A, Form A2.2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. (Excludes items 1905 and 1929).

Anti-Mold/Mildew
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® XL* suspension system for 15/16" edge detail and Silhouette* suspension system for 9/16" edge detail.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value
R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)
2081, 2081, 2084, 2085 – R Factor – 2.9 (BTU units); 0.445 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton
1945 – 1.14 LBS/SF; 48 SF/CTN
1941, 1942 – 1.125 LBS/SF; 40 SF/CTN
1944, 1942HRC – 1.125 LBS/SF; 48 SF/CTN
1433, 1434 – 1.05 LBS/SF; 60 SF/CTN
1436, 1437 – 1.04 LBS/SF; 72 SF/CTN
2081, 2082 – 1.0 LBS/SF; 40 SF/CTN
2084, 2085 – 1.0 LBS/SF; 48 SF/CTN

1431 – 1.06 LBS/SF; 62.5 SF/CTN
1917, 1993 – 1.05 LBS/SF; 24 SF/CTN
1422, 1423 – 1.08 LBS/SF; 24 SF/CTN
1905, 1905HRC, 4334 – 1.05 LBS/SF; 62.5 SF/CTN
1911, 1911HRC, 1912, 1912HRC, 1914, 1914HRC, 1915 – 1.05 LBS/SF; 48 SF/CTN
1916, 1996 – 1.05 LBS/SF; 48 SF/CTN
1427 – 1.07 LBS/SF; 24 SF/CTN
1929, 1929HRC – 1.02 LBS/SF; 68 SF/CTN
1895, 1952, 1951 – 1.31 LBS/SF; 48 SF/CTN
1901, 1902, 1904, 1906, 1894 – 1.08 LBS/SF; 48 SF/CTN
1997, 1994 – 1.05 LBS/SF; 30 SF/CTN
1998, 1995 – 1.05 LBS/SF; 36 SF/CTN
1981, 1982 – 1.08 LBS/SF; 72 SF/CTN
1985, 1986 – 1.08 LBS/SF; 80 SF/CTN
4336, 4337 – 1.05 LBS/SF; 75 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
1941M, 1944M, 1945M, 1905M, 1912M, 1912MHR, 1914M, 1915M, 1916M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/ultima
BPCS-3039-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; USAI Lighting is a registered trademark of USAI Lighting, LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard