



FELTWORKS®

Acoustical Ceiling Panels
medium texture



SUSTAIN®
High Performance
Sustainable
Ceiling Systems




FAST134
Select Items Ship Fast
armstrongceilings.com/fast134



FeltWorks® Acoustical Ceiling Panels in White

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Soft visual and excellent noise control with versatile installation options for design flexibility.

KEY SELECTION ATTRIBUTES

- Available in three standard, nominal sizes: 24" × 48", 48" × 48" and 48" × 96"
- Quick and easy retrofit acoustical solution
- Excellent sound absorption – NRC up to 0.90
- Sustainable Beyond Standard: Custom sizes and all standard panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Mold- and mildew-resistant surface
- No need to field-finish cut edges with color throughout panels
- Custom sizes available from 18" × 18" up to 54" × 120"
- No visible fasteners with adhesive or magnet installation options
- FeltWorks acoustical panels are lightweight and easy to install in any ceiling application. Many install options:
 - Attachment with adhesive to drywall or cement
 - Attachment with magnets to metal furring or drywall grid
 - Visible attachment with screw and washer to metal furring or drywall grid


TYPICAL APPLICATIONS

- Exposed structure
- Open plenum offices
- Drywall spaces requiring acoustical correction
- Retail
- Hospitality

COLORS Due to printing limitations, shade may vary from actual product.



NOTE: Shade variance in finished products of certain colors may occur, as shown below.



DETAILS



- Square Panel Edges (48 × 96 × 1" ONLY)
- Beveled Panel Edges (24 × 48 × 1" and 48 × 48 × 1" ONLY)
- 1" diameter magnet (back of panel and no visible fasteners)
- Magnetic attachment to metal furring
- 1" washer and screw (front of panel)

TechLine 877 276-7876
armstrongceilings.com/feltworks

Armstrong®
World Industries



FELTWORKS®

Acoustical Ceiling Panels

medium texture



SUSTAIN
High Performance
Sustainable Ceiling Systems

Declare.

LEED V5

COMMON MATERIALS FRAMEWORK

Human Health **Declare Label**
HPD
3rd Party CDPH

Climate Health

EPD

Ecosystem Health

EPD

Circular Economy

OCCUPANT EXPERIENCE



Acoustics



INSTALLATION DETAILS





MOUNTING D-20: SCREW AND WASHER ATTACHMENT TO METAL FURRING



Metal furring layout (3 rows per panel) with recommended 2" gap between panels for magnet or screw & washer installation



MOUNTING D-20: MAGNET ATTACHMENT TO DRYWALL GRID



Magnet attachment to back of FeltWorks panel




COMMON MATERIALS FRAMEWORK		Climate Health	EPD
Human Health	Declare Label	Ecosystem Health	EPD
	HPD		
	3rd Party CDPH	Circular Economy	
OCCUPANT EXPERIENCE		Acoustics	✓



INSTALLATION DETAILS



MOUNTING D-20: MAGNET ATTACHMENT TO METAL FURRING



MOUNTING A: ADHESIVE ATTACHMENT



Adhesive attachment

