

Fire Resistive Ceiling Systems

Edge Profile	Item No.	Dimensions	UL Classified Acoustics		Total Acoustics ¹ NRC CAC	Fire Rating	Light Perfect	Bio-Block® Anti-Mold/ Mildew	Sag Resist	Certified Low VOC Emissions	Recycle Program
			NRC	CAC							
CEILING PANELS											
Ceramaguard® 15/16" Square Lay-In	605	24 x 48 x 5/8"	N/A	40	N/A	Fire Guard™	0.86	•	HumiGuard® Max	•	
Ceramaguard® Fine Fissured™ 15/16" Square Lay-In	607	24 x 24 x 5/8"	0.55	38	N/A	Fire Guard	0.79	•	HumiGuard Max	•	
	608	24 x 48 x 5/8"	0.55	40	N/A	Fire Guard	0.79	•	HumiGuard Max	•	
Cirrus® 9/16" Beveled Tegular	577	24 x 24 x 3/4"	0.35	35	N/A	Fire Guard	0.85	•	HumiGuard® Plus	•	•
Cirrus 15/16" Angled Tegular	578	24 x 24 x 3/4"	0.35	35	N/A	Fire Guard	0.85	•	HumiGuard Plus	•	•
Clean Room™ VL (Unperforated) 15/16" or 1-1/2" Square Lay-In	868	24 x 24 x 5/8"	N/A	40	N/A	Fire Guard	0.80	•	HumiGuard Plus	N/A	N/A
	870	24 x 48 x 5/8"	N/A	40	N/A	Fire Guard	0.80	•	HumiGuard Plus	N/A	N/A
Cortega® 15/16" Square Lay-In	824	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.80	N/A	Std	•	•
	823	24 x 48 x 5/8"	0.55	35	N/A	Fire Guard	0.80	N/A	Std	•	•
Cortega 15/16" Angled Tegular	816	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.80	N/A	Std	•	•
Cortega® Second Look® II 15/16" Angled Tegular	2758	24 x 48 x 3/4"	0.55	40	N/A	Fire Guard	0.81	N/A	Std	•	•
Dune™ 15/16" Square Lay-In	1850	24 x 24 x 5/8"	0.50	35	N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
	1851	24 x 48 x 5/8"	0.50	35	N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Dune 15/16" Angled Tegular	1853	24 x 24 x 5/8"	0.50	35	N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Dune 9/16" Beveled Tegular	1852	24 x 24 x 5/8"	0.50	35	N/A	Fire Guard	0.81	•	HumiGuard Plus	•	•
Fine Fissured™ 15/16" Square Lay-In	1831	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1830	24 x 48 x 5/8"	0.55	35	N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fine Fissured 15/16" Angled Tegular	1833	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1834	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fine Fissured 9/16" Beveled Tegular	1835	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.82	•	HumiGuard Plus	•	•
Fissured 15/16" Square Lay-In	896	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.79	N/A	Std	•	•
	895	24 x 48 x 5/8"	0.55	35	N/A	Fire Guard	0.79	N/A	Std	•	•
Fissured 15/16" Angled Tegular	815	24 x 24 x 5/8"	0.55	35	N/A	Fire Guard	0.79	N/A	Std	•	•

Dots represent high level of performance.

REFERENCE – FIRE RESISTANCE

Fire Resistive Ceiling Systems

Edge Profile	Item No.	Dimensions	UL Classified Acoustics			Total Acoustics ¹ NRC CAC	Fire Rating	Light Reflect	Bio-Block® Anti-Mold/ Mildew	Sag Resist	Certified Low VOC Emissions	Recycle Program
			NRC	+	CAC							
CEILING PANELS (CONT.)												
Fine Fissured™ Second Look® 15/16" Angled Tegular	1861	24 x 48 x 3/4"	0.55	•	35	N/A	Fire Guard™	0.82	•	HumiGuard® Plus	•	•
School Zone® Fine Fissured™ 15/16" Square Lay-In	1810	24 x 24 x 3/4"	0.70	•	40	BETTER ()))	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1811	24 x 48 x 3/4"	0.70	•	40	BETTER ()))	Fire Guard	0.82	•	HumiGuard Plus	•	•
School Zone Fine Fissured 15/16" Angled Tegular	1820	24 x 24 x 3/4"	0.70	•	35	BETTER ()))	Fire Guard	0.82	•	HumiGuard Plus	•	•
	1824	24 x 48 x 3/4"	0.70	•	35	BETTER ()))	Fire Guard	0.82	•	HumiGuard Plus	•	•
School Zone Fine Fissured 9/16" Beveled Tegular	1821	24 x 24 x 3/4"	0.70	•	35	BETTER ()))	Fire Guard	0.82	•	HumiGuard Plus	•	•
Ultima® 15/16" Beveled Tegular	1894	24 x 24 x 3/4"	0.60	•	40	GOOD ()))	Fire Guard	0.88	•	HumiGuard Plus	•	•
Ultima 9/16" Beveled Tegular	1895	24 x 24 x 3/4"	0.60	•	40	GOOD ()))	Fire Guard	0.88	•	HumiGuard Plus	•	•
VL (Perforated) 15/16" or 1-1/2" Square Lay-In	869	24 x 24 x 5/8"	0.55	•	35	N/A	Fire Guard	0.78	•	HumiGuard Plus	N/A	N/A
	871	24 x 48 x 5/8"	0.55	•	35	N/A	Fire Guard	0.78	•	HumiGuard Plus	N/A	N/A

Product Name	Item No.	Description	Rout Spacing	Dimensions (Inches)	LOAD TEST DATA		Seismic Category	PACKAGING	
					L/360 4 Ft.	L/360 5 Ft.		Pcs/Ctn	LFt/Ctn
SUSPENSION SYSTEMS									
Prelude® XL® FireGuard™	8031	12' HD Main Beam	6" O.C.	144 x 15/16 x 1-11/16"	16.73	8.73	•	20	240
	8300	12' ID Main Beam	6" O.C.	144 x 15/16 x 1-11/16"	13.5	6.35	•	20	240
	XL8341	4' Cross Tee	12" O.C.	48 x 15/16 x 1-11/16"	16.89	N/A	•	60	240
	XL8340	4' Cross Tee	12" O.C.	48 x 15/16 x 1-11/16"	12.25	N/A	•	60	240
	XL8323	2' Cross Tee	N/A	24 x 15/16 x 1-3/8"	36.0 at 2'	N/A	•	60	120
	XL8320	2' Cross Tee	N/A	24 x 15/16 x 1-11/16"	61.33 at 2'	N/A	•	60	120
Prelude® Plus XL® FireGuard™	HD8201_ _	12' HD Main Beam	N/A	144 x 15/16 x 1-11/16"	16.73	N/A	•	20	240
	XL8240_ _	4' Cross Tee	N/A	48 x 15/16 x 1-1/2"	12.75 at 2'	N/A	•	60	240
	XL8223_ _	2' Cross Tee	N/A	24 x 15/16 x 1-1/2"	38.63 at 2'	N/A	•	60	120
Suprafine® XL® FireGuard™	8501	12' HD Main Beam	6" O.C.	144 x 9/16 x 1-11/16"	16.86	10.62	•	20	240
	8500	12' ID Main Beam	6" O.C.	144 x 9/16 x 1-11/16"	12.75	5.74	•	20	240
	XL8540	4' Cross Tee	12" O.C.	48 x 9/16 x 1-11/16"	10.34	N/A	•	60	240
	XL8520	2' Cross Tee	N/A	24 x 9/16 x 1-11/16"	51.83	N/A	•	60	120

Dots represent high level of performance.

REFERENCE – FIRE RESISTANCE