Translucent INFUSIONS™

Wall Panels smooth texture



Infusions™ Walls 24" x 96" in Refined Tangerine

Wall System available in translucent colors and patterns that can be hung individually or in a group.

KEY SELECTION ATTRIBUTES

- Coordinate with Armstrong® ceilings or other interior finishes including Infusions™ Partitions, Lay-in Panels, and Canopies, SoundScapes® Blades and Shapes, or Create!™ ceilings
- · Standard products create a custom look
- . CleanAssure™ family of products includes disinfectable panels, suspension systems, and trim
- · Factory-drilled to accept Point Support hardware kit
- Aluminum Point Support Kit offers contemporary sleek visual
- · Panels and installation hardware packaged in one complete kit


COLORS Due to printing limitations, shade may vary from actual product.

Patterns*





















Red Arbor

* Due to the unique nature of the woven fabric used in these products, color may vary from panel to panel.

Solids


























Blue (TPB)



Iris (TSI)



Bliss (TBB)







(TRK)



(TRR)



Refined

Lagoon (TRL)















Translucent INFUSIONS™

Wall Panels smooth texture




VISUAL SELECTION DEDECDMANCE

VISUAL SELECTION	PERFORIVIANCE			
				CleanAssure™ Disinfectable Walls
				Wipe
	ltem No. ◆	Dimensions (Inches)	PCS/CTN	
INFUSIONS™ Walls	5824	24 × 96 × 1/4"	2	•
◆ When specifying or orde	ring, include the appropriate 3	8-letter color suffix (e.g., 5824 <u>T C C.)</u>		

ACCESSORIES

Item No.	Description	Color	PCS/CTN	
5848	Infusions Wall Panel Hardware Kit	Aluminum	16 Point Supports	

NOTE: Panel kit does not include hardware. Infusions Wall panel hardware kit must be ordered separately.



PHYSICAL DATA

Material PETG

Surface Finish

Smooth

Fire Performance Infusions panels have been tested according to NFPA 286 and are equivalent to Class A Interior Finish as defined by the International Building Code.

Contact TechLine at 1 877 276-7876 for specific U.S. and Canadian fire performance data.

Installation and Design Considerations Do not allow panel edges to get wet.

Infusions panels are not approved for exterior application.

Color may vary from panel to panel on patterned products.

Wall anchor hardware is provided by others. A minimum gap of $1/4^{\circ}$ is required between panels. Panels are pre-drilled for Point Supports.

Panels can be damaged by exposure to high temperatures. Panel temperature should not be permitted to exceed 100°F. There is potential for limited deflection of panels.

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

Warranty Details at armstrongceilings.com

Weight; Pieces/Pack Panel weight – 27 LBS 2 pieces/pack (Bulk packed)

