

LEDGES®

Tegular
smooth texture



Ledges® I panels with Prelude® XL 15/16" suspension system



Ledges® II panels with Suprafine® XL 9/16" suspension system

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

The dimensional look of old-world plaster ceilings in two classic designs.

KEY SELECTION ATTRIBUTES

- Dimensional, sculptured visual
 - Affordable and practical alternative to embossed plaster panels
- Non-directional visual reduces installation time and scrap
 - Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

NOTE: Not recommended for areas requiring acoustical performance


COLOR



FACE VIEWS



Ledges® I panel



Ledges® II panel

DETAILS



1. Ledges® I Flush Tegular
2. Ledges® II Flush Tegular
3. Ledges® I with Prelude® 15/16" suspension system
4. Ledges® II with Suprafine® 9/16" suspension system

LEDGES®

Tegular
smooth texture

RECYCLED
CONTENT

LEED V5

Ecomedes Data

UP TO
43%

Declare.

COMMON MATERIALS FRAMEWORK

| | | |
|---------------------|----------------|------------------|
| Human Health | Declare Label | Climate Health |
| | | Ecosystem Health |
| | 3rd Party CDPH | Circular Economy |
| OCCUPANT EXPERIENCE | | Acoustics |

VISUAL SELECTION

PERFORMANCE SELECTION

\$\$\$\$

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) |
|--------------------------------------|------------|----------|---------------------|
| LEDGES® I 15/16" Flush Tegular | 3 | 8011 | 24 × 24 × 3/4" |
| LEDGES® II 9/16" Flush Tegular | 25 | 8013 | 24 × 24 × 3/4" |

| UL Classified Acoustics | | Total Acoustics¹ | Fire Performance | Light Reflect | Anti-Mold/ Mildew | Sag Resistant | Certified Low VOC Emissions | Durability | Recycled Content | Recycle Program | Warranty |
|-------------------------|------|------------------|------------------|---------------|-------------------|---------------|-----------------------------|------------|------------------|-----------------|----------|
| NRC + | CAC | = | | | | | | | | | |
| N/A | 35 * | N/A | Class A | 0.80 | N/A | Std | N/A | Std | Std | * | 1-Yr |
| N/A | 35 | N/A | Class | 0.80 | N/A | Std | N/A | Std | Std | * | 1-Yr |

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type A, Form A1.2, Pattern G; Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

1-Year Limited Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
8011 – 0.90 LBS/SF; 48 SF/CTN
8013 – 0.90 LBS/SF; 32 SF/CTN

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/ledges
BPCS-3544-925

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard