

METALWORKS™

Vector® and Vector Exterior
smooth texture




FAST134
Select Items Ship Fast
armstrongceilings.com/fast134

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



MetalWorks™ Vector exterior and interior panels



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Durable, steel panels offer a 1/4" reveal and 100% downward accessibility.

KEY SELECTION ATTRIBUTES




- Now available in 17 Effects™ wood-look finishes for interior and exterior applications
- Exclusive Vector® panel edge profile installs on new or existing 15/16" exposed tee suspension system resulting in a thin 1/4" reveal

- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Panels can be used to create continuous looks or clouds using Axiom® trim or Effects™ Wood-looks trim



- Select products included in the FAST134 program – ready to ship in 4 weeks or less
- Exterior system available, tested to meet wind uplift Classes 30, 60, and 90

- Outstanding NRC with acoustical fleece or infill panel (0.65 – 0.90)
- Installs with minimal plenum clearance
- Plenum access per panel without the need of special tools



*Available in
4 weeks or less
order-to-ship!*

TechLine 877 276-7876
armstrongceilings.com/metalworks

Armstrong®
World Industries

METALWORKS™

Vector® and Vector Exterior
smooth texture

RECYCLED
CONTENT

LEED V5

UP TO
25%

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health

Circular Economy



OCCUPANT EXPERIENCE

Acoustics




MetalWorks™ Vector® – Extra Microperforated in Effects Wood Looks Cherry

STANDARD COLORS & FINISHES

Due to printing limitations, shade may vary from actual product.

MetalWorks™ (Interior, Exterior)



White
(WH, WH2)



Silver Grey
(SG, SG2)



Gun Metal Grey
(MY, MY2)

Effects™ Classic (Interior, Exterior) Dye-Sublimation



Effects Cherry
(FXCH, FXCH2)




Effects Dark
Cherry (FXDC, FXDC2)



Effects Oak
(FXOK, FXOK2)



Effects Walnut
(FXWN, FXWN2)



Effects Walnut
Espresso
(FXWE, FXWE2)



Effects™ Bold (Interior, Exterior) Dye-Sublimation



Effects Sea Salt
(FXSS, FXSS2)



Effects Ginger
(FXGR, FXGR2)



Effects Nutmeg
(FXNM, FXNM2)



Effects Poppy Seed
(FXPS, FXPS2)



Effects Peppercorn
(FXPC, FXPC2)



Effects Almond
(FXAL, FXAL2)



Effects™ Subtle (Interior, Exterior) Dye-Sublimation



Effects Sesame
(FXSE, FXSE2)




Effects Macadamia
(FXMA, FXMA2)



Effects Cinnamon
(FXCM, FXCM2)



Effects Flax
(FXFL, FXFL2)



Effects Cocoa Bean
(FXCB, FXCB2)



Effects Coriander
(FXCO, FXCO2)

NOTE: Effects colors are only available for unperforated and extra microperforated panels.

CUSTOM COLORS & FINISHES

Due to printing limitations, shade may vary from actual product.



Custom Colors
Available



Custom Wood-look
Finishes Available


For custom options contact ASQuote,
ASQuote@armstrongceilings.com

PERFORATION OPTIONS


(1:2 scale shown)




M1
(Unperforated)



M2
(Microperforated)



M3 (Extra
Microperforated)



Custom
Perforations
Available

DETAILS



1. MetalWorks™ Vector® Microperforated
2. MetalWorks™ Vector® Unperforated with
Prelude® XL® 15/16" suspension system



METALWORKS™

Vector® and Vector Exterior
smooth texture

RECYCLED
CONTENT

LEED V5

UP TO
25%

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health


Circular Economy

OCCUPANT EXPERIENCE

Acoustics

VISUAL SELECTION

Item No. ♦	Dimensions (Inches)	Perforations
METALWORKS™ Vector®	24" x 24"	M1, M2, M3
1/4" Reveal with 15/16" Vector®		



FAST
4 WEEKS
or Less

FAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

♦ When specifying or ordering, include the appropriate color, perforation and, if needed, coating suffix with the item number (e.g., 6466 M1 W H, 6466 M3 F X C H).

NOTE: Perforation M2 not available in Effects™ finishes as a standard option.

PERFORMANCE

Dots represent high level of performance.

Fire Performance (White only)	CleanAssure™ Disinfectable Panels	DURABILITY
Light Reflect	Fog Spray Wipe Wash Scrub Impact Soil	
Class A	0.77 (M1)	• • • • • • • •

ACOUSTICAL INFORMATION

Perforation	% Open Area	NRC	CAC
M1 Unperforated	-	-	36
M2 Micro-perforated	18.4%	0.70† 0.90*	31**
M3 Extra Micro-perforated	1.5%	0.65† 0.70*	33**

† No infill

* NRC 0.90 (microperforated) with optional fiberglass infill #8200T10. NRC 0.70 (extra microperforated) with optional BioAcoustic™ infill Item #5479 or 5823.


** With optional field-cut #770 mineral fiber backing (cannot be used in addition to fiberglass infill Item #8200T10).

ACCESSORIES Additional accessories, including moldings and perimeter trim, at armstrongceilings.com/mwaccessories

Item No. ♦	Description	Dimensions (Inches)	Pieces/Carton
5342 _ _ _ _	2" Effects™ Wood Looks Trim	120 x 3/4 x 2"	6
5344 _ _ _ _	4" Effects Wood Looks Trim	120 x 4 x 4"	6
5346 _ _ _ _	6" Effects Wood Looks Trim	120 x 6 x 6"	6
5479	BioAcoustic™ Infill Panel (Beige – Matte)	24 x 24 x 5/8"	12
5823	BioAcoustic™ Infill Panel (Black – Matte)	24 x 24 x 5/8"	12
6098 _ _	Edge Cap for Cut Vector Panels not available in Effects™ finishes, order in Black (BL)	Nominal 24" length	50
8200T10	1" Fiberglass Infill Bag (Black – Gloss)	24" x 24"	12
FXSPTHDC	Effects™ Hold-Down Clip for Cut Panel Installations	N/A	10

♦ When specifying or ordering, include the appropriate color, perforation and, if needed, coating suffix with the item number

SUSPENSION SYSTEMS

15/16" 
Prelude® XL®
Prelude XL for Exterior Applications

METALWORKS™

Vector® and Vector Exterior
smooth texture

RECYCLED
CONTENT

UP TO
25%

LEED V5

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health

Circular Economy




OCCUPANT EXPERIENCE


Acoustics




PANEL EDGE DETAILS



MetalWorks™ Vector® Panel



Spring Kerf



Access Kerf



Reverse Tegular Edges

PHYSICAL DATA

Material

Electrogalvanized Steel – 0.021" thickness

Surface Finish

Factory-applied powder-coated finish (post-coated for color)

Exterior: Factory-applied powder-coated finish (post-coated on both sides). Effects finish on face only.

Custom colors also available. Contact TechLine for custom color matching requests at 1 877 276-7876.

Fire Performance

Class A: ASTM E84 and CAN/ULC S102. Flame Spread

Index 25 or less. Smoke Developed Index 50 or less.

ASTM E1264 Classification

Fire Class – Class A

Unperforated – Type XX, Pattern G

Perforated – Type XX, Pattern C

Installation Consideration

For information about accessible faceted applications,

refer to installation instructions on our website

at armstrongceilings.com/installation.

Wind Uplift Performance

MetalWorks™ Vector® panels for exterior flat applications have been tested to meet wind uplift Classes 30, 60, and 90. There is no fleece on exterior panels. Visit armstrongceilings.com/metalworks or contact TechLine at 1 877 276-7876 for installation instructions and test documentation.

Seismic Restraint

MetalWorks™ Vector® panels have been engineered, tested, and approved for application in all seismic areas when installed per Armstrong Ceilings installation instructions.

Cleaning and Disinfecting

Cleaning and CDC approved disinfecting options available on armstrongceilings.com/cleaning

Warranty

Details at armstrongceilings.com/warranty

FAST134 Program Considerations

Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.

Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.

Distributor Truck Schedule Matters: We rely on distribution to help move products around the Country. When speed matters, work with your local distributor to ensure FAST134 service.

Stock vs Made-to-Order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.

Weight; Square Feet/Cartron

6466M1, 6466M3 – 1.15 lbs/SF; 40 SF/ctn

6466M2 – 1.10 lbs/SF; 40 SF/ctn

TechLine / 1 877 276-7876
armstrongceilings.com/metalworks
BPCS-5110-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

METALWORKS™ – Standard