

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture


SUSTAIN®
High Performance
Sustainable
Ceiling Systems
(PB Suffix Only)


**24/7
DEFEND™**
Solutions for Healthier,
Safer Spaces
CONTAIN CLEAN PROTECT

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit


DESIGNFlex™
A New World of Choice
for Ceiling Systems



▲ Optima® Tegular 24" x 24" panels with Suprafine® 9/16" suspension system

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Fine-textured panels with more large-size, standard panel options than any other product family. Offers high sound absorption.

KEY SELECTION ATTRIBUTES

- DESIGNFlex® options include shapes and made-to-order sizes available to ship in 3 weeks
- Optima® PB panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Items with PB suffix are manufactured with a plant-based binder
- Outstanding acoustical performance for open plan areas, both Articulation Class 180-200 and NRC 0.90-1.00
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Energy-saving high light-reflective finish
- Non-directional visual reduces scrap and installation time
- Sag-resistant large-size panels
- Compatible with TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Available with factory-cut holes for USAI® trimless downlight fixture integration.

COLOR



DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Optima® Square Tegular
2. Optima® Tegular with Prelude® 15/16" suspension system
3. Optima® Tegular with Interlude® XL® HRC 9/16" suspension system
4. Optima® Tegular with Silhouette® 9/16" suspension system with 1/8" reveal
5. Suprafine® ML, XL®, and XL® HRC with Blizzard White finish

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

Declare.
(PB Suffix Only)

SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC
UP TO **71% RECYCLED CONTENT**

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/excise producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT PB ONLY PB ONLY PB ONLY

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
OPTIMA® 15/16" Square Tegular		1402	6 x 48 x 1"	
		1406	6 x 60 x 1"	
		3264	12 x 24 x 1"	
		3278	20 x 60 x 1"	
		3250 3250PB	24 x 24 x 1"	
		3354	24 x 24 x 1"	
		3253	24 x 24 x 1-1/2"	
		3252 3252PB	24 x 48 x 1"	
		3281	24 x 72 x 1"	
		3282	24 x 96 x 1"	
		3258	30 x 30 x 1"	
		3286	30 x 60 x 1"	
		3255 3255PB	48 x 48 x 1"	

PERFORMANCE SELECTION Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program	30-Yr Warranty			
NRC + CAC =	AC	Class	Class	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty
N/A	N/A	N/A	N/A	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
N/A	N/A	N/A	N/A	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.90	26	N/A	200	Class 0.88	•	•	N/A	•	•	•	•	•	N/A	•
1.00	N/A	N/A	200	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•
0.95	N/A	N/A	190	Class 0.88	•	•	N/A	•	•	•	•	•	•	•

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima® items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

MORE ITEMS ▶

PHYSICAL DATA

Material
3354 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
(PB suffix items only)
GREENGUARD Gold Certified
This product has been UL validated to be Formaldehyde-Free. UL.COM/ECV.
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
Some items have CAC backing. CAC backing may be available as a special order. A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
3253 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)
3281, 3282 – R Factor – 3.0 (BTU units)
R Factor – 0.53 (Watts units)
All other items – R Factor – 4.0 (BTU units)
R Factor – 0.70 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight: Square Feet/Carton
1402 – 0.55 lbs/SF; 24 SF/ctn
1406 – 0.55 lbs/SF; 30 SF/ctn
3250, 3250PB – 0.46 lbs/SF; 48 SF/ctn
3252, 3252PB – 0.55 lbs/SF; 96 SF/ctn
3282 – 0.42 lbs/SF; 96 SF/ctn
3264 – 0.55 lbs/SF; 48 SF/ctn
3253 – 0.64 lbs/SF; 32 SF/ctn
3255, 3255PB – 0.55 lbs/SF; 96 SF/ctn
3258 – 0.55 lbs/SF; 75 SF/ctn
3278, 3286 – 0.55 lbs/SF; 100 SF/ctn
3281 – 0.55 lbs/SF; 72 SF/ctn
3282 – 0.42 lbs/SF; 96 SF/ctn
3354 – 0.47 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
3250M, 3252M, 3253M, 3354M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

OPTIMA®
OPTIMA® PB
 with Plant-based Binder
 Tegular
 fine texture



LEED WELL™ LBC
 UP TO **71%** RECYCLED CONTENT
 energy management ✓
 construction waste mgmt ✓
 regional materials ✓
 design for flexibility ✓
 EPD ✓
 recyclable/extended producer resp. ✓
 biobased materials ✓
 recycled content ✓
 sourcing of raw materials ✓
 material ingredient reporting ✓
 low emitting materials ✓
 lighting quality ✓
 acoustics ✓

Calculate sustainability with GreenGenie™
 armstrongceilings.com/greengenie

LOCATION DEPENDENT PB ONLY

PB ONLY PB ONLY

VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$



armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
OPTIMA® 9/16" Square Tegular 	26, 43, 47, 51, 55	1410	4 x 48 x 1"	
		1411	4 x 60 x 1"	
		1413	6 x 12 x 1"	
		1415	6 x 42 x 1"	
		1403	6 x 48 x 1"	
		1417	6 x 54 x 1"	
		1407	6 x 60 x 1"	
		1409	6 x 96 x 1"	
		3263	12 x 24 x 1"	
		3290	12 x 48 x 1"	
1414	12 x 96 x 1"			

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program	30-Yr Warranty
NRC + CAC =	AC	Class	Class	Class	Class	Class	Class	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
N/A	N/A	N/A	N/A	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
0.95	N/A	N/A	190	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
0.95	N/A	N/A	190	Class A	0.88	•	•	N/A	•	•	•	•	•	•	
0.95	N/A	N/A	190	Class A	0.88	•	•	N/A	•	•	•	•	•	•	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima® items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

FIBERGLASS – Standard

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

Declare®
(PB Suffix Only)

GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC

UP TO **71% RECYCLED CONTENT**

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT PB ONLY PB ONLY PB ONLY

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
OPTIMA® 9/16" Square Tegular		3276	20 x 54 x 1"
		3266	20 x 56 x 1"
		3277	20 x 60 x 1"
		3279	21 x 24 x 1"
		3251 3251PB	24 x 24 x 1"
		3254	24 x 24 x 1-1/2"


PERFORMANCE SELECTION Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Bio-Block	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program				
NRC + CAC =	AC	Class	Class	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Bio-Block	Humi-Guard+	Fog	Wash	Impact	Scratch	Soil	Recycle Program	30-Yr Warranty
0.95 *	N/A	N/A	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*
0.95 *	N/A	N/A	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*
0.95 *	N/A	190	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*
0.95 *	N/A	190	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*
0.95 *	N/A	190	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*
1.00 *	N/A	200	Class A	0.88 *	*	*	N/A	*	*	*	*	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima® items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

MORE ITEMS ▶

SUSPENSION SYSTEMS



Blizzard White – Suspension System Finish
A color and texture coordinated suspension system to complement Optima® ceiling panels for a monolithic look and feel. Available for: Prelude® XL® and XL® HRC, Suprafine ML, XL, and XL HRC, Silhouette® XL® 1/4" and 1/8" Reveal, Interlude® XL® HRC

ACCESSORIES (must be ordered separately)

435 Stabilizer Clip (3/4" & 1")
Recommended for panels 60" and greater in length
NOTE: Panels 60" up to 96" – One clip near mid-point of each long edge.
Panels 96" and over – Two clips at 1/3 points of each long edge.

PHYSICAL DATA

Material
3355 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions (PB suffix items only)
GREENGUARD Gold Certified
This product has been UL validated to be Formaldehyde-Free. UL.COM/ECV.
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC.

Insulation Value
3254 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1403 – 0.55 lbs/SF; 24 SF/ctn
1407 – 0.55 lbs/SF; 30 SF/ctn
1409 – 0.55 lbs/SF; 96 SF/ctn
1410 – 0.55 lbs/SF; 16 SF/ctn
1411 – 0.55 lbs/SF; 20 SF/ctn
1413 – 0.55 lbs/SF; 6 SF/ctn
1414, 3263, 3290 – 0.55 lbs/SF; 48 SF/ctn
1415 – 0.55 lbs/SF; 21 SF/ctn
3251 – 0.46 lbs/SF; 48 SF/ctn
1417 – 0.55 lbs/SF; 27 SF/ctn
1418 – 0.55 lbs/SF; 6 SF/ctn
3254 – 0.64 lbs/SF; 32.5 SF/ctn
3276 – 0.55 lbs/SF; 75 SF/ctn
3277 – 0.55 lbs/SF; 100 SF/ctn
3266 – 0.55 lbs/SF; 62.22 SF/ctn
3279 – 0.45 lbs/SF; 42 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
3251M, 3254M, 3256M, 3257M, 3355M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

FIBERGL ASS – Standard



OPTIMA® OPTIMA® PB

with Plant-based Binder
Regular
fine texture



SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

Declare.
(PB Suffix Only)

GREENGUARD
Gold Certified

LEED®
WELL™ LBC

UP TO **71%** RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT PB ONLY PB ONLY

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

VISUAL SELECTION

armstrongceilings.com/catdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
OPTIMA® 9/16" Square Regular	26, 43, 47, 51, 55	3355	24 x 24 x 1" □
		3257 3257PB	24 x 48 x 1" □
		3265 3265PB	24 x 60 x 1" □
		3261 3261PB	24 x 72 x 1" □
		3262 3262PB	24 x 96 x 1" □
		3283	27 x 30 x 1" □
		3268	28 x 30 x 1" □
		3269	28 x 60 x 1" □
		3259	30 x 30 x 1" □
		3284	30 x 54 x 1" □
		3289	30 x 56 x 1" □
		3285	30 x 60 x 1" □
		3287	42 x 48 x 1" □
		3288	44 x 48 x 1" □
		3256 3256PB	48 x 48 x 1" □
		3249	48 x 54 x 1" □

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program
NRC + CAC =	AC	Class	Class	Class	Class	Class	Class	Fog	Wash	Impact	Scratch	Soil	30-Yr Warranty	
0.90 26	N/A	200	Class A	0.88	.	.	N/A	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95*	N/A	190*	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	
0.95	N/A	190	Class A	0.88	.	.	N/A	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima® items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

* These items are not UL classified.



FIBERGLASS – Standard

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture



Declare.
(PB Suffix Only)

GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC

UP TO 71% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT PB ONLY PB ONLY PB ONLY

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie


VISUAL SELECTION

PERFORMANCE SELECTION Dots represent high level of performance.

armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)		UL Classified Acoustics	NRC + CAC =	Total Acoustics!	Articulation Class	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels					30-Yr Warranty
		Width	Length										Fog	Wash	Impact	Scratch	Soil	
Non-PB 1" Thick – 15/16" & 9/16" Square Tegular																		
Made-to-Order Sizes OPTIMA®		4" – 6"	9" – 96"	N/A	N/A	N/A	N/A	Class 0.88	•	•	•	N/A	•	•	•	•		
		6-1/2" – 48"	9" – 120"					A	•									
PB 1" Thick – 15/16" & 9/16" Square Tegular																		
1 Ctn Min FASTSIZE 3 WEEKS order to ship		4" – 6"	9" – 72"	N/A	N/A	N/A	N/A	Class 0.88	•	•	•	N/A	•	•	•	•		
		6-1/2" – 24"	9" – 96"					A	•									
		24-1/2" – 28"	9" – 72"															
		28-1/2" – 48"	9" – 48"															
Non-PB 1-1/2" Thick – 15/16" & 9/16" Square Tegular																		
		4" – 6"	9" – 96"	N/A	N/A	N/A	N/A	Class 0.88	•	•	•	N/A	•	•	•	•		
		6-1/2" – 48"	9" – 120"					A	•									

1 Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima® items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

SUSPENSION SYSTEMS



Blizzard White – Suspension System Finish

A color and texture coordinated suspension system to complement Optima® ceiling panels for a monolithic look and feel. Available for: Prelude® XL® and XL® HRC, Suprafine ML, XL, and XL HRC, Silhouette® XL® 1/4" and 1/8" Reveal, Interlude® XL® HRC

ACCESSORIES (must be ordered separately)

435 Stabilizer Clip (3/4" & 1")
Recommended for panels 60" and greater in length
NOTE: Panels 60" up to 96" – One clip near mid-point of each long edge.
Panels 96" and over – Two clips at 1/3 points of each long edge.

PHYSICAL DATA

Material
3355 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Clas A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type XII, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
(PB suffix items only)
GREENGUARD Gold Certified
This product has been UL validated to be Formaldehyde-Free.
UL.COM/ECV.
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC.

Insulation Value
3254 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG UL 2818



30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight: Square Feet/Carton
3283 – 0.55 lbs/SF; 57.5 SF/ctn
3249, 3256, 3256PB, 3257, 3257PB, 3262, 3262PB – 0.55 lbs/SF; 96 SF/ctn
3259 – 0.64 lbs/SF; 75 SF/ctn
3261, 3261PB – 0.55 lbs/SF; 72 SF/ctn
3265, 3265PB, 3285 – 0.55 lbs/SF; 100 SF/ctn
3268 – 0.55 lbs/SF; 70 SF/ctn
3269 – 0.55 lbs/SF; 93.33 SF/ctn
3284 – 0.55 lbs/SF; 90 SF/ctn
3287 – 0.55 lbs/SF; 112 SF/ctn
3288 – 0.55 lbs/SF; 117.33 SF/ctn
3355 – 0.47 lbs/SF; 48 SF/ctn
3289 – 0.40 lbs/SF; 93.33 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
3251M, 3254M, 3256M, 3257M, 3355M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.