


fine texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFlex®
A New World of Choice
for Ceiling Systems

plus capabilities
to do more



Optima PB Vector panels with Prelude® XL® 15/16" suspension system

armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Fine-textured panels, with a 1/4" reveal, and downward accessibility; ideal for projects where plenum space is limited. Offers high sound absorption.

KEY SELECTION ATTRIBUTES



- Optima® PB Vector® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- DesignFlex® options include made-to-order sizes available to ship in 3 weeks
- 1/4" reveal between acoustical panels results in a monolithic appearance
- Vector Trim Kit in Blizzard White finish for easy installation and bright visual
- Downward accessible for minimal plenum height
- Outstanding acoustical performance for open plan areas, both Articulation Class 180 and NRC 0.80-0.90
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Washable Scratch-resistant Soil-resistant
- Energy-saving high light-reflective finish
- Items with PB suffix are manufactured with a plant-based binder
- Item 3901 available in Create!™ printed images and patterns
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

DETAILS



1. Optima PB Vector
2. Optima PB Vector with Prelude 15/16" suspension system
3. Optima PB Vector with fixture trim

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	
OCCUPANT EXPERIENCE		Acoustics	

fine texture

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
OPTIMA® Vector®	73	1466	6 × 48 × 7/8"
		1466PB	
1/4" Reveal with 15/16" Square Lay-in		1467	6 × 96 × 7/8"
		1467PB	
		3902	12 × 24 × 7/8"
		3902PB	
		3903	12 × 24 × 7/8"
		3903PB	
		3900	24 × 24 × 7/8"
		3900EPB	
		3901	24 × 24 × 7/8"
		3901PB	
		3908	24 × 48 × 7/8"
		3908PB	
		3906	24 × 72 × 7/8"
		3906PB	
		3907	24 × 96 × 7/8"
		3907PB	
		3904	30 × 30 × 7/8"
		3904PB	
		3905	30 × 30 × 7/8"
		3905PB	
		3909	48 × 48 × 7/8"
		3909PB	

7/8" Thick – 1/4" Reveal with 15/16" Vector


Made-to-Order Sizes

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

Width	Length
4" – 30"	9" – 120"
30-1/16" – 48"	30-1/16" – 48"

SUSPENSION SYSTEM



Prelude®

TRIM KITS FOR VECTOR® PANELS

Item No.	Color	Length	Substrate	PCS/CTN
VETK4ZW	Blizzard White	4"	Steel	24
VETK6ZW	Blizzard White	6"	Steel	24
VETK24ZW	Blizzard White	24"	Steel	24
VETK48ZW	Blizzard White	48"	Steel	24
VETK96ZW	Blizzard White	96"	Steel	24

Length 4" – 96"

Made-to-Order Sizes & Colors

4-6
WEEKS
order to ship

PHYSICAL DATA

Material

Fiberglass with DuraBrite® acoustically transparent membrane
3901PB, 3903PB, 3905PB – Fiberglass with DuraBrite acoustically transparent membrane; CAC backing

Surface Finish

DuraBrite scrim with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification

Type B, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

(PB suffix items only)

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL™ Building Challenge, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details

Some items have CAC backing. CAC backing may be available as a special order.

Insulation Value

R Factor – 3.5 (BTU units)

R Factor – 0.62 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton

1466, 1466PB – 0.58 LBS/SF; 16 SF/CTN
1467, 1467PB – 0.58 LBS/SF; 42 SF/CTN
3900, 3901, 3902, 3903, 3900PB, 3901PB, 3902PB, 3903PB – 0.58 LBS/SF; 48 SF/CTN
3904, 3905, 3904PB, 3905PB – 0.59 LBS/SF; 75 SF/CTN
3908, 3908PB – 0.56 LBS/SF; 96 SF/CTN
3909, 3909PB – 0.60 LBS/SF; 64 SF/CTN
3906, 3906PB – 0.57 LBS/SF; 72 SF/CTN
3907, 3907PB – 0.56 LBS/SF; 96 SF/CTN

Minimum Order Quantity

1 carton

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$

UL Classified Acoustics		Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY				30-Yr Warranty
NRC	+ CAC =		AC	Fire	Light	Anti-Mold/Mildew	Sag Resistant		Fog	Wash	Scratch	Soil		
N/A	N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	
N/A	N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	
N/A	N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	
N/A	26	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.80	26	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.80	26	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
0.90	N/A	N/A	180	Class A	0.88	*	*	*	*	*	*	*	*	
Factor														
N/A	N/A	N/A	N/A	Class A	0.88	*	*	*	*	*	*	*	*	

ACCESSORIES (must be ordered separately)

Item No.

441		Border Clip for Vector panels (required for installations with the suspension system resting on the wall molding).
442		Hold-down Clip for Vector® panels (for all installations)
7425 (24"), 7431 (30"), 7445 (48"), 7461 (60")		Stabilizer Bars
522		Midpoint Clip (Needed for panels over 30" wide)
7870		Spring Border Clip (For installations with the panel resting on the wall molding)