

# OPTIMA®

Wall Panels  
fine texture

**LEED® WELL | LBC**

UP TO **71%** RECYCLED CONTENT

Calculate sustainability with Ecomedes [armstrongceilings.com/ecomedes](http://armstrongceilings.com/ecomedes)

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT



Wall panels with a bright surface that provide excellent sound absorption.

### KEY SELECTION ATTRIBUTES

- Smooth surface
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning))
- Durability
  - Washable
  - Scratch-resistant
  - Soil-resistant

### COLOR



Optima® Acoustic Wall Panels

### VISUAL SELECTION

	Substrate	Finish	Item No.	Dimensions (Inches)
Optima®	Fiberglass	DuraBrite®	3154	48 × 96 × 1"

### PERFORMANCE

Dots represent high level of performance.

CleanAssure™ Disinfectable Walls	NRC RATING	
Fog	A Mount	D Mount
•	0.80	0.90

For performance and physical data, [armstrongceilings.com/optimawalls](http://armstrongceilings.com/optimawalls)

### INSTALLATION ACCESSORIES

	Description	Item No.	Dimensions (Inches)	Color
C Channel	Extruded PVC Plastic	3107	1 × 96 × 1"	White
H Channel	Extruded PVC Plastic	3108	1-5/8 × 96 × 1"	White

A Mounting – Mounting directly against existing surface; D-20 Mounting – Mounting spaced 3/4" from existing surface using 1" x 4" furring strips

