

OPTIMA®  
Wall Panels  
fine texture

RECYCLED  
CONTENT

UP TO  
71%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK	
Human Health	Climate Health
	Ecosystem Health
	Circular Economy
OCCUPANT EXPERIENCE	Acoustics



Optima® Acoustic Wall Panels

Wall panels with a bright surface  
that provide excellent sound absorption.

KEY SELECTION ATTRIBUTES

- Smooth surface
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](https://armstrongceilings.com/cleaning))
- Durability
  - Washable
  - Scratch-resistant
  - Soil-resistant

COLOR






VISUAL SELECTION

	Substrate	Finish	Item No.	Dimensions (Inches)
Optima®	Fiberglass	DuraBrite®	3154	48 × 96 × 1"

PERFORMANCE

Dots represent high level of performance.

CleanAssure™ Disinfectable Walls	NRC RATING	
Fog	A Mount	D Mount
		
*	0.80	0.90

For performance and physical data, [armstrongceilings.com/optimawalls](https://armstrongceilings.com/optimawalls)

INSTALLATION ACCESSORIES

	Description	Item No.	Dimensions (Inches)	Color
C Channel	Extruded PVC Plastic	3107	1 × 96 × 1"	White
H Channel	Extruded PVC Plastic	3108	1-5/8 × 96 × 1"	White

A Mounting – Mounting directly against existing surface; D-20 Mounting – Mounting spaced 3/4" from existing surface using 1" × 4" furring strips

