

PRELUDE® Plus XL® Fire Guard™

PRELUDE® XL® for Exterior Applications

Exposed Tee System



UP TO **30%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

| | | | | | | | | | | | | | |
|-------|-------------------|-----------------------------|--------------------|------------------------|-----|------------------------------------|---------------------|------------------|---------------------------|-------------------------------|------------------------|------------------|-----------|
| LEED® | energy management | construction waste to reuse | regional materials | design for flexibility | EPD | recyclable/extended producer resp. | bio-based materials | recycled content | sourcing of raw materials | material ingredient reporting | low emitting materials | lighting quality | acoustics |
|-------|-------------------|-----------------------------|--------------------|------------------------|-----|------------------------------------|---------------------|------------------|---------------------------|-------------------------------|------------------------|------------------|-----------|

LOCATION DEPENDENT

A 15/16" suspension system for severe environmental performance.



Prelude® Plus XL® suspension system

KEY SELECTION ATTRIBUTES

- **Seismic Rx®** Suspension System saves time and money; ICC-ES approach to installations (ESR-1308)
- Prelude® Plus XL® Fire Guard™ and Prelude® XL® for Exterior Applications are part of the Sustain™ portfolio and meets the most stringent sustainability compliance standards today – White only
- Systems conform to ASTM C635 for Severe Environmental Performance
- Rotary-stitched during manufacture for torsional strength and stability
- 10-Year Limited Warranty; 30-Year Limited Warranty with **HumiGuard® Plus** or **HumiGuard® Max** products
- XL® staked-on end detail provides secure locked connection
- **PeakForm®** profile increases strength and stability
- **SuperLock™** main beam clip engineered for secure connection and fast, accurate alignment
- 10-year replacement items available



PRELUDE® XL® For Exterior Applications

- Minimum G90 hot-dipped galvanized steel with prefinished G90 steel capping
 - Suitable for wind uplift applications with appropriate bracing
- #### PRELUDE® Plus XL® Fire Guard™
- Systems are minimum G60 hot-dipped galvanized steel with prefinished aluminum capping for enhanced corrosion resistance

TYPICAL APPLICATIONS

PRELUDE Plus XL Fire Guard

- Locker rooms
- Food preparation areas

PRELUDE XL For Exterior Applications


- Non-exposed exterior corridors
- Drive-thru areas
- Indoor parking garages
- Use with Woodworks® Linear Solid Wood Panels for Exterior

COLORS

Fire Guard™



Exterior



VISUAL SELECTION

| Face Profile | Item No. ♦ | Description | Dimensions (Inches) | Hanger Spacing* Lbs./LFT | | |
|---|-----------------------|--------------------------|------------------------|--------------------------|-------|-------|
| | | | | 2 Ft. | 4 Ft. | 5 Ft. |
| Prelude® Plus XL® Fire Guard™ (Red Numbers are Fire Guard Items) | | | | | | |
| 15/16" | HD8201 _ _ | 12' HD Main Beam | 144 x 15/16 x 1-11/16" | 12.75 | 16.73 | – |
| 15/16" | XL8240 _ _ | 4' Cross Tee | 48 x 15/16 x 1-1/2" | 12.75 | – | – |
| 15/16" | XL8223 _ _ | 2' Cross Tee | 24 x 15/16 x 1-1/2" | 38.63 | – | – |
| Molding | | | | | | |
| 7/8" | HD7801 _ _ | 10' Hemmed Angle Molding | 120 x 7/8 x 7/8" | – | – | – |
| Prelude XL for Exterior Applications | | | | | | |
| 15/16" | 7301G90A _ _ | 12' HD Main Beam | 144 x 15/16 x 1-11/16" | – | 16.50 | 6.92 |
| 15/16" | XL7341G90A _ _ | 4' Cross Tee | 48 x 15/16 x 1-11/16" | – | 16.59 | – |
| 15/16" | XL7321G90A _ _ | 2' Cross Tee | 24 x 15/16 x 1-11/16" | – | 74.38 | – |
| Molding | | | | | | |
| 7/8" | HD7801G90 _ _ | 10' Hemmed Angle Molding | 120 x 7/8 x 7/8" | – | – | – |
| Accessories | | | | | | |
| 2" | BACG90A | Wind Uplift Clip | N/A | – | – | – |
| | UHDC | Universal Hold-down Clip | N/A | – | – | – |

PERFORMANCE

| Fire Guard | Seismic Category |
|------------|------------------|
| • | • |
| • | • |
| • | • |

Dots represent high level of performance.

PACKAGING

| Pcs./ Ctn. | LFT/ Ctn. |
|------------|-----------|
| 20 | 240 |
| 60 | 240 |
| 60 | 120 |
| 30 | 300 |
| 20 | 240 |
| 60 | 240 |
| 60 | 120 |
| 30 | 300 |
| 200 | – |
| 1000 | – |

* Simple Span

♦ Add 2-letter color suffix to item number when specifying or ordering. Available in White Steel and Tech Black (ex. HD7801G90A **BL**)

ASTM Class
HD – Heavy-duty
ID – Intermediate-duty
LD – Light-duty


DETAILS For more information on Prelude Plus XL Fire Guard, see submittal BPCS-3156.



PRELUDE XL Main Beam



PRELUDE XL Cross Tee



TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: suspension systems)
BPCS-3156-520

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing LLC
and/or its affiliates © 2020 AWI Licensing LLC
Printed in the United States of America

