

new PUEBLO™
PUEBLO High NRC
 Square Lay-in & Tegular
 smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Pueblo Beveled Tegular panels with Suprafine® XL® 9/16" suspension system

Smooth texture acoustical panel with good sound absorption and sound-blocking performance for a wide variety of open-plan spaces.

KEY SELECTION ATTRIBUTES


- Good combination of sound absorption and sound blocking; up to NRC 0.90 and CAC 30
- Pueblo™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- Smooth, white surface
- Product can be recycled through the Armstrong Ceilings Recycling Program
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
 (WH)

DETAILS



1. Pueblo Square Lay-in
2. Pueblo Beveled Tegular



PUEBLO™

PUEBLO High NRC

Square Lay-in & Tegular
smooth texture



LEED® WELL | LBC

70% RECYCLED CONTENT

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie



LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
PUEBLO™ High NRC	1	1864	24 × 24 × 1"
15/16" Square Lay-in		1865	24 × 48 × 1"
9/16" Beveled Tegular	1	1866	24 × 24 × 1"
		1867	24 × 48 × 1"
15/16" Beveled Tegular	1	1868	24 × 24 × 1"
		1869	24 × 48 × 1"
PUEBLO™	1	1812	24 × 24 × 3/4"
15/16" Square Lay-in		1837	24 × 48 × 3/4"
9/16" Beveled Tegular	1	1813	24 × 24 × 3/4"
		1838	24 × 48 × 3/4"
15/16" Beveled Tegular	1	1814	24 × 24 × 3/4"
		1839	24 × 48 × 3/4"


PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

UL Classified Acoustics	Total Acoustics	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycle Program	30-Yr Warranty
0.90 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.90 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.90 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.90 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.90 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.70 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.70 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.70 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*
0.70 + 30 =	N/A	Class A	0.82	*	*	*	Std	*	*

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber with acoustically transparent membrane.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL® labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude XL suspension system for 15/16" edge detail and Silhouette suspension system for 9/16" edge detail.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



Insulation Value
1812, 1813, 1814, 1837, 1838, 1839 - R Factor - 2.1 (BTU units)
1864, 1865, 1866, 1867, 1868, 1869 - R Factor - 2.9 (BTU units)
R Factor - 0.445 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1812, 1837 - 1.08 LBS/SF; 48 SF/CTN
1813, 1814, 1838, 1839 - 1.05 LBS/SF; 48 SF/CTN
1866, 1868 - 1.09 LBS/SF; 32 SF/CTN
1867, 1869 - 1.09 LBS/SF; 48 SF/CTN
1864 - 1.12 LBS/SF; 32 SF/CTN
1865 - 1.12 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

Tech Line / 1 877 276-7876
armstrongceilings.com/pueblo
BPCS-6266-1023

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a trademark of the International Living Future Institute; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2023 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER - Standard

