

# RANDOM FISSURED™

Square Lay-in  
medium texture

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Random Fissured™ panels with Prelude® XL® 15/16" suspension system

Economical, medium-textured panels with an easy-to-clean, durable surface that offer standard to good sound absorption.

## KEY SELECTION ATTRIBUTES

- High sound absorption (perforated panels only)
- Easy-to-clean, durable surface – Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

## COLOR



White  
(WH)

# RANDOM FISSURED™

Square Lay-in  
medium texture

RECYCLED  
CONTENT

UP TO  
**71%**



LEED V5

Ecomedes Data

## COMMON MATERIALS FRAMEWORK


Human Health	Climate Health
	Ecosystem Health
	Circular Economy
OCCUPANT EXPERIENCE	Acoustics

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
RANDOM FISSURED™ (Perforated)	1	2908	24 × 24 × 5/8" 
15/16" Square Lay-in			

2910	24 × 48 × 5/8" 
------	--

RANDOM FISSURED™ (Unperforated)	1	2909	24 × 24 × 5/8" 
15/16" Square Lay-in			


2911	24 × 48 × 5/8" 
------	--

5/8" Thick – 15/16" Square Lay-in (Perforated & Unperforated)																
Made-to-Order Sizes	<div>3-4 WEEKS order to ship</div>	Width	Length	N/A	N/A	N/A	Class A	0.71	*	*	N/A	*	*	*	*	*
		12" – 30"	12" – 60"													

**3-4 WEEKS**  
order to ship

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

## SUSPENSION SYSTEM



## PHYSICAL DATA

**Material**  
Fiberglass with vinyl facing

**Surface Finish**  
Scrubable vinyl film facing (UV protected)

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type B, Form A2.2, Pattern G; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Acoustical Details**  
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

**Insulation Value**  
R Factor – 2.6 (BTU units)  
R Factor – 0.46 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
0.17 LBS/SF; 128 SF/CTN

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

**Metric Items Available**  
Items 2908M, 2910M, 2909M, 2911M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.