



School Zone® Fine Fissured™ Templok®

Square Lay-In
medium texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



School Zone® Fine Fissured™ Templok Square Lay-In panels with Prelude XL 15/16" suspension system

Learn How Templok
Ceilings Save Energy!



Medium-texture mineral fiber ceiling combines excellent acoustical performance, energy savings and enhanced thermal comfort using advanced Phase Change Material (PCM) technology.

KEY SELECTION ATTRIBUTES

- Saves up to 15% energy*
- Improve thermal comfort with ceilings that help regulate indoor temperatures
- Provides up to 35 BTUs/SF of passive cooling*
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Exceptional sound-blocking performance for enhanced speech privacy: CAC 40
- High sound absorption – products can help comply with ANSI S12.60 classroom guidelines
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Non-directional visual reduces scrap and installation time
- Mold- and mildew-resistant surface
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

* Measured cooling energy savings in lab test. Results may vary. See Templok Technical Guide.

TYPICAL APPLICATIONS

- Schools
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Libraries/band rooms
- Corridors

COLOR



White
(WH)

DETAILS



1. School Zone Fine Fissured Templok Square Lay-In panel
2. School Zone Fine Fissured Templok back of panel



Save up to 50% in Tax Credits

Templok® ceilings may qualify for Investment Tax Credits (ITC) under Inflation Reduction Act of 2022, Section 48E

Learn more at armstrongceilings.com/saveontemplok



School Zone® Fine Fissured™ Templok®

Square Lay-In
medium texture

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
School Zone® Fine Fissured™ Templok® 15/16" Square Lay-in	29, 44, 48, 52, 56	1713TEMP (Field Panel Only – cannot be cut)	24 × 24 × 1"	
		1713 Use 1713 for borders and cutting needs. See School Zone Fine Fissured Data Page for Product Details	24 × 24 × 3/4"	

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)
** Consult a code official in your jurisdiction for mechanical code compliance.

RECYCLED
CONTENT

UP TO
22%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

EPD

Ecosystem Health

EPD

Circular Economy

OCCUPANT EXPERIENCE

Acoustics

ENERGY AND ATMOSPHERE

Reduced Peak Thermal Loads

Energy Efficiency

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

NRC	CAC	Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Spray	Recycle Program	30-Yr Warranty
0.70	40	BETTER	Class A**	0.82	*	Std	*	*	*	*	*
0.70	35	BETTER	Class A	0.82	*	*	*	*	*	*	*

SUSPENSION SYSTEMS

15/16"



Prelude® XL®

PHYSICAL DATA

Material

Wet-formed mineral fiber with virgin PVC with salt hydrate

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 450 or less.

ASTM E1264 Classification

Type A, Form A1.2, Pattern D

Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Anti-Mold/Mildew

Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Thermal Energy Storage Capacity

Stores a minimum of 35 BTU/SF from 62°F to 83°F per ASTM C1784-20

VOC Emissions

Compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Prelude XL suspension system for 15/16" edge detail.

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Twenty (20) Year Limited Thermal Energy Storage Capacity Warranty

Weight: Square Feet/Cartron
2.55 LBS/SF; 16 SF/CTN

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/templok
BPCS-7265-925

LEED® is a registered trademark of the U.S. Green Building Council; Living Building Challenge® (LBC) is a registered trademark of the International Living Future Institute®; WELL® and WELL Building Standard are trademarks of the International WELL Building Institute; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard