

SHASTA®
Square Lay-in
medium texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Shasta panel with Prelude® XL® 15/16" suspension system

Economical, medium-textured panels with an easy-to-clean, durable surface.

KEY SELECTION ATTRIBUTES

- High sound absorption (perforated panels only)
- Easy-to-clean, durable surface – Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR



White
(WH)



Tech Black
(BL)

Black ceilings are dye lotted and should be segregated by dye lot.

SHASTA®

Square Lay-in
medium texture

LEED® WELL | LBC



UP TO **71% RECYCLED CONTENT**

energy management construction waste mgmt regional materials design for flexibility EPD recyclable/excise producer resp. biobased materials recycled content sourcing of raw materials material ingredient reporting low emitting materials lighting quality acoustics

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/cat/dwgs	Susp. Dwg.	Item No. ♦	Dimensions (Inches)
SHASTA® (Perforated) 15/16" Square Lay-in 	1	2904	24 x 24 x 5/8" <input type="checkbox"/>
		2906	24 x 48 x 5/8" <input type="checkbox"/>
SHASTA® (Unperforated) 15/16" Square Lay-in 	1	2905	24 x 24 x 5/8" <input type="checkbox"/>
		2907	24 x 48 x 5/8" <input type="checkbox"/>

PERFORMANCE SELECTION


Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Water Repel	Wash	Scrub	Impact	Soil	Recycled Content	Recycle Program	30-Yr Warranty
NRC	+ CAC =														
0.70	N/A	N/A	Class A	0.72*	•	•	N/A	N/A	•	•	•	•	•	N/A	•
0.70	N/A	N/A	Class A	0.72*	•	•	N/A	N/A	•	•	•	•	•	N/A	•
0.50	N/A	N/A	Class A	0.72*	•	•	N/A	•	•	•	•	•	•	N/A	•
0.50	N/A	N/A	Class A	0.72*	•	•	N/A	•	•	•	•	•	•	N/A	•
Made-to-Order Sizes															
		5/8" Thick – 15/16" Square Lay-in (Perforated & Unperforated)													
		Width	Length	N/A	N/A	N/A	Class A	0.72*	•	•	N/A	N/A	•	•	•
		12" - 30"	12" - 60"												

3-4 WEEKS
order to ship

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. * Light reflectance value for white only.
♦ Add 2-letter color suffix to item number when specifying or ordering (e.g., 2906 B L).

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
2904, 2906 – Type XII, Form 1, Pattern E C
2905, 2907 – Type XII, Form 1, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
0.17 lbs/SF; 128 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
Items 2904M, 2906M, 2905M, 2907M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

