

SHASTA®
Square Lay-in
medium texture

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Shasta panel with Prelude® XL® 15/16" suspension system

Economical, medium-textured panels with an easy-to-clean, durable surface.

KEY SELECTION ATTRIBUTES

- High sound absorption (perforated panels only)
- Easy-to-clean, durable surface – Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical acoustical solution
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White
(WH)

SHASTA®

Square Lay-in
medium texture

RECYCLED
CONTENT

UP TO
71%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Climate Health
	Ecosystem Health
	Circular Economy
OCCUPANT EXPERIENCE	Acoustics

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
SHASTA® (Perforated) 15/16" Square Lay-in 	1	2904	24 × 24 × 5/8"
		2906	24 × 48 × 5/8"
SHASTA® (Unperforated) 15/16" Square Lay-in 	1	2905	24 × 24 × 5/8"
		2907	24 × 48 × 5/8"

PERFORMANCE SELECTION

Dots represent high level of performance.

NRC	UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Humi-Guard+	Water Repel	Wash	Scrub	Impact	Soil	Recycled Content	30-Yr Warranty
0.70	N/A	N/A	Class A	0.72	*	*	N/A	*	*	*	*	*	*
0.70	N/A	N/A	Class A	0.72	*	*	N/A	*	*	*	*	*	*
0.50	N/A	N/A	Class A	0.72	*	*	*	*	*	*	*	*	*
0.50	N/A	N/A	Class A	0.72	*	*	*	*	*	*	*	*	*

Made-to-Order
Sizes


3-4
WEEKS
order to ship

5/8" Thick – 15/16" Square Lay-in (Perforated & Unperforated)

Width	Length	N/A	N/A	N/A	Class A	0.72	*	*	N/A	*	*	*	*	*	*
12" – 30"	12" – 60"														

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics, Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification
Type B, Form B3, Pattern F; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
R Factor – 2.6 (BTU units)
R Factor – 0.46 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton
0.17 LBS/SF; 128 SF/CTN

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
Items 2904M, 2906M, 2905M, 2907M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/shasta
BPCS-3697-925

LEED® is a registered trademark of the U.S. Green Building Council; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

FIBERGLASS