


TECTUM® DesignArt™ – Lines High NRC Direct-Attach Wall Panels coarse texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Visit our online pattern gallery at:
armstrongceilings.com/patterngallery

Mix and match Shapes and
Lines for a truly unique visual!



Tectum DesignArt – Lines High NRC Direct-Attach wall Signals panels in Natural (TNA)


armstrongceilings.com/designart

Transform interior spaces with a three-dimensional visual by combining texture, routed patterns, and colors with acoustical, sustainable Tectum® DesignArt™ – Lines High NRC Direct-Attach wall panels.

KEY SELECTION ATTRIBUTES

- new** • Tectum DesignArt – Lines High NRC Direct-Attach panels are the first of their kind to have a proprietary factory-applied acoustical backer, adding sound absorption that is certified by UL®
- new** • Excellent sound absorption – NRC 0.60 (1" panel, D-20 mounting)
- 29 standard routed panels for 24" × 24" and 24" × 48" Direct-Attach walls
- Available in 24 standard nature-inspired colors and Natural
- Products in the Tectum DesignArt portfolio are made to work together
- Precision routing of lines allows for seamless connections between compatible panel face designs
- Tectum DesignArt – Lines panels have UL-certified acoustics with testing and reporting that align with industry-wide best practices
- Great retrofit solution for noise reduction
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (standard colors only)
- Part of the Sustain® portfolio, and meeting the most stringent industry sustainability compliance standards today
- All edges are beveled and painted
- Variety of made-to-order color options available
- Touch up paint available for the 24 standard colors
- Available for ceiling applications
- Panels can be mechanically fastened to a wide variety of surfaces including masonry, drywall, drywall grid system, wood, and more
- USDA Biobased content: 98%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

DETAILS




1. Tectum DesignArt – Lines High NRC Direct-Attach panel in Polar. Edges are beveled and painted.
2. Tectum DesignArt – Lines High NRC Direct-Attach panel with proprietary acoustical backer

TECTUM® DesignArt™ – Lines High NRC

Direct-Attach Wall Panels
coarse texture




LEED V5		
COMMON MATERIALS FRAMEWORK		
Human Health	Declare Label HPD	Climate Health EPD
	3rd Party CDPH	Ecosystem Health EPD
OCCUPANT EXPERIENCE		Circular Economy
		Acoustics



Visit our online pattern gallery at armstrongceilings.com/patterngallery
Use our recommended colors, or choose from 24 standard colors, in addition to Natural to create your own one-of-a-kind pattern!

COLORS Due to printing limitations, shade may vary from actual product.



* For custom options contact ASQuote, ASQuote@armstrongceilings.com
Custom color panels and any panels greater than 1" thick are not included in Sustain® portfolio.

VISUAL SELECTION

Item No.	Dimensions W x L x H (Inches)
TECTUM® DesignArt™ – Lines High NRC	24 x 24 x 1" <input type="checkbox"/>
	24 x 48 x 1" <input type="checkbox"/>
Long Edges Beveled/ Short Edges Beveled	

PERFORMANCE Dots represent high level of performance.

Fire Rating	Bio-Block	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	30-Yr Warranty
Class A	•	•	•	•	•

ACOUSTICAL INFORMATION


Panel Thickness	UL® Classified Acoustics	Mounting Method
1"	0.60	D-20

TECTUM® DesignArt™ – Lines

High NRC

Direct-Attach Wall Panels
coarse texture


FACE PROFILES




Currents
6347D11T10




Rings
6347D04T10




Arcs
6347D03T10




Bands
6347D08T10




Steps
6347D07T10




Illusions
6347D09T10




Currents B
6347D49T10




Rings B
6347D45T10




Retro
6347D43T10




Retro B
6347D44T10




Bands B
6347D46T10




Bands C
6347D47T10




Illusions B
6347D48T10




Droplets
6347D13T10




Tilts
6347D15T10




Decos
6347D10T10




Signals
6347D14T10




Strings
6347D12T10




Droplets B
6347D51T10




Contours
6347D53T10




Tilts B
6347D40T10




Tilts C
6347D41T10




Tilts D
6347D42T10




Signals B
6347D52T10




Strings B
6347D50T10




Hatches
6347D01T10




Checkers
6347D06T10



Rays
6347D05T10



Levels
6347D54T10



Precision Routing Allows for Mixing and Matching

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 6347D54T10 I P Q).

TechLine 877 276-7876

armstrongceilings.com/designart

Armstrong®
World Industries




PARTITIONS & WALLS

TECTUM® DesignArt™ – Lines High NRC


Direct-Attach Wall Panels
coarse texture

SYSTEM INSTALLATION DETAILS



① Routing for Lines with Beveled Edge

Mounting D-20



② Acoustical Mounting Methods

ACCESSORIES

Item No. ♦	Description	Quantity
5456GAL1 _ _ _	Touch up paint	1 gallon
8187L16TWH†	#6 × 1-5/8" Painted Head – Sharp point Screws	1000/CTN
8188L16TWH†	#6 × 1-5/8" Painted Head – Drill point Screws	1000/CTN
8189L22TWH	2-1/4" Painted Head – CMU Screws	500/CTN

♦ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 5456GAL1 I P Q). Consult installation instructions for fastener guidance.

† Touch up paint is available to paint screw heads in field if desired or specified.

NOTE: Projects may require alternative screw lengths and types depending on site conditions. Please consult installation instructions for guidance.

PHYSICAL DATA

Material

Tectum® DesignArt™ – Lines High NRC panels have an acoustical fleece.

Surface Finish

Factory-applied latex paint on abuse-resistant silicate surface coating. Natural finish is unpainted but, after coating is applied, panels may appear light in color.

Panels are painted on the edge, however due to fibrous texture of panels, certain angles and lighting conditions will make edge appear less or more painted.

Can be field painted up to 6 times without impacting acoustic or fire performance. See installation instructions for details on paint and application method.

Fire Performance

Class A, Flame Spread Index 25 or less and Smoke Developed Index 50 or less when tested in accordance with ASTM E84.

CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less and Smoke Developed Index of 50 or less (painted, face only).

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Humidity/Sag Resistance

HumiGuard® Plus performance panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Wall panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Installation Considerations

Panels must be mechanically attached to approved substrate per installation instructions.

Use caution and wear appropriate hand, eye, and dust mask protection when cutting and installing Tectum wall panels. Refer to installation instructions for complete details and cutting recommendations.

Tectum DesignArt - Lines High NRC Direct-Attach panels must be installed using the D-20 method to reach its full acoustical potential.

Primary (Embodied) Energy

See all LCA information on our EPDs.

Application Considerations

Low angle lighting exaggerates variation inherent to the manufacturing process and is not recommended for Tectum installations.

Design Considerations

Color variation among panels is common due to the natural characteristics of the wood.

Wood fibers may appear orange on natural-colored panels due to the characteristics of the wood.

Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dye-lotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

Seismic Restraint

Tectum Direct-Attach wall panels are approved for application in all seismic areas when installed per the seismic guidelines in the Armstrong Ceiling and Wall Installation Instructions.

Design & Pre-Construction Service

For complimentary design and pre-construction assistance, contact ProjectWorks® or visit armstrongceilings.com/projectworks

Cleaning and Disinfecting

Cleaning and CDC-approved disinfecting options available on armstrongceilings.com/cleaning

Warranty

30-Year Warranty. Details at armstrongceilings.com/warranty

Weights and Sold By

1" – 1.65 LBS/SF

Panels sold by the piece. Other accessory elements quantities noted above.

