

TECTUM® DesignArt® – Shapes

Direct-Attach Wall Panels
coarse texture




SUSTAIN®
High Performance
Sustainable
Ceiling Systems




Tectum DesignArt – Shapes Direct-Attach wall panels in pattern TDSH-0006 in standard colors

CAD/Revit® drawings at:
armstrong.com/cadrevit



Visit our online pattern gallery at:
armstrong.com/patterngallery

Mix and match Shapes and
Lines for a truly unique visual!




armstrong.com/designart

Transform interior spaces by combining texture, shapes, patterns, and colors with sustainable, acoustical Tectum® DesignArt® – Shapes Direct-Attach wall panels.


KEY SELECTION ATTRIBUTES

- 30 standard Shapes direct-attach wall panels available in 24 new standard colors, and Natural
- Products in the Tectum DesignArt portfolio are made to work together
- Available for ceiling and wall applications
- Tectum DesignArt – Shapes panels have UL® Certified acoustics with testing and reporting that align with industry-wide best practices
- Great retrofit solution for noise reduction
- Excellent sound absorption – NRC up to 0.85 (1" panel, C-40 Mounting)
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (standard colors only)
- Sustainable Beyond Standard: Custom sizes in 1" thickness and all standard panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- All edges are beveled and painted
- Touch up paint for standard colors available
- Panels can be mechanically fastened to a wide variety of surfaces including masonry, drywall, drywall grid system, wood, and more
- USDA Biobased content: 98%
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLORS Due to printing limitations, shade may vary from actual product.



DETAIL



Tectum DesignArt – Shapes Direct-Attach panel in Polar. Edges are beveled and painted

* Due to manufacturing processes, the face of Natural (TNA) panels may appear whiter than the back and edges.

** Colors that are pre-qualified to meet Sustain portfolio requirements are available upon request. Other made-to-order colors must be evaluated if sustainability criteria is required. Lead time will increase.

TECTUM® DesignArt® – Shapes

Direct-Attach Wall Panels
coarse texture



The mark of responsible forestry

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 98%



SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare.

LEED V5

COMMON MATERIALS FRAMEWORK	Climate Health	EPD
Human Health	Declare Label HPD	EPD
	3rd Party CDPH	FSC®
OCCUPANT EXPERIENCE	Acoustics	✓

VISUAL SELECTION

	Item No.	Dimensions W x L x H (Inches)
TECTUM® DesignArt® – Shapes Beveled Edges	See below	See below



PERFORMANCE

Dots represent high level of performance.


Fire Rating	Bio-Block	Humi-Guard+	Anti-Mold/Mildew	Sag Resist	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Impact	Scratch	30-Yr Warranty
Class A	*	*	*	*	*	*	*	*	*	*

ACOUSTICAL INFORMATION


Panel Thickness	UL Classified Acoustics NRC	Mounting Method
1"	0.40	A
	0.45	D-20
	0.80	C-20
	0.85	C-40

30° SHAPES

Isosceles Triangles
Nominal Dimensions




Item No. ◆	Description
5420T11T10 _ _ _	Isosceles Triangle




Item No. ◆	Description
5420T12T10 _ _ _	Isosceles Triangle

45° SHAPES

Right Triangles
Nominal Dimensions




Item No.	Description
5420T01T10 _ _ _	Right Triangle




Item No.	Description
5420T02T10 _ _ _	Right Triangle

Parallelograms


Nominal Dimensions




Item No.	Description
5420P01T10 _ _ _	Right Parallelogram



Item No.	Description
5420P02T10 _ _ _	Right Parallelogram



Item No.	Description
5420P03T10 _ _ _	Left Parallelogram



Item No.	Description
5420P04T10 _ _ _	Left Parallelogram

MORE ITEMS ▶





◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 5420R01T10 I P Q). Consult installation instructions for fastener guidance.

TECTUM® DesignArt® – Shapes



Direct-Attach Wall Panels
coarse texture

60° SHAPES

Right Triangles



Nominal Dimensions	Item No. ♦	Description
	5420T05T10 ___	Right Triangle – Right
	5420T06T10 ___	Right Triangle – Right
	5420T07T10 ___	Right Triangle – Left
	5420T08T10 ___	Right Triangle – Left

Parallelograms



Nominal Dimensions	Item No. ♦	Description
	5420P05T10 ___	Parallelogram
	5420P06T10 ___	Parallelogram

60° SHAPES



Hexagons

Nominal Dimensions	Item No. ♦	Description
	5420H01T10 ___	Hexagon
	5420H02T10 ___	Hexagon

Trapezoids

Nominal Dimensions	Item No. ♦	Description
	5420Z01T10 ___	Trapezoid
	5420Z02T10 ___	Trapezoid

Equilateral Triangles

Nominal Dimensions	Item No. ♦	Description
	5420T03T10 ___	Equilateral Triangle
	5420T04T10 ___	Equilateral Triangle

♦ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 5420R01T10 I.P.Q.). Consult installation instructions for fastener guidance.

MORE ITEMS ▶



PARTITIONS & WALLS

TECTUM® DesignArt® – Shapes


Direct-Attach Wall Panels
coarse texture

90° SHAPES


Squares & Rectangles

Nominal Dimensions


Item No. ♦ Description




542OR01T10 ___ Square




542OR02T10 ___ Rectangle




542OR03T10 ___ Rectangle



542OR04T10 ___ Rectangle



542OR05T10 ___ Square




542OR06T10 ___ Rectangle

360° SHAPES


Circles

Nominal Dimensions


Item No. ♦ Description




542OC01T10 ___ Circle



542OC02T10 ___ Circle



542OC03T10 ___ Semicircle



542OC04T10 ___ Semicircle


♦ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 542OR01T10 I P Q). Consult installation instructions for fastener guidance.





PARTITIONS & WALLS

TECTUM® DesignArt® – Shapes

Direct-Attach Wall Panels
coarse texture




Tectum® DesignArt® – Shapes, pattern TDSH-0006



Tectum DesignArt – Shapes, pattern TDSH-0006




Tectum DesignArt – Shapes, pattern TDSH-0001




Tectum DesignArt – Shapes, pattern TDSH-0004




Tectum DesignArt – Shapes, pattern TDSH-0009



Tectum DesignArt – Shapes, pattern TDSH-0011



Tectum DesignArt – Lines and Tectum DesignArt – Shapes, pattern TDSL-0001



Tectum DesignArt – Lines and Tectum DesignArt – Shapes, pattern TDSL-0002

Visit our online pattern gallery at armstrong.com/patterngallery
Use our recommended colors, or choose from 24 standard colors, in addition to Natural to create your own one-of-a-kind pattern!

TECTUM® DesignArt® – Shapes

Direct-Attach Wall Panels
coarse texture


ACCESSORIES

Item No. ◆	Description	Quantity
5456GAL1 _ _ _	Touch up paint	1 gallon
8187L16TWH†	#6 × 1-5/8" Painted Head – Sharp point Screws	1000/ctn
8188L16TWH†	#6 × 1-5/8" Painted Head – Drill point Screws	1000/ctn
8189L22TWH	2-1/4" Painted Head – CMU Screws	500/ctn

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural; TPO = Polar (e.g. 5456GAL1 T P O). Consult installation instructions for fastener guidance.
† Touch up paint is available to paint screw heads in field if desired or specified.

NOTE: Projects may require alternative screw lengths and types depending on site conditions. Please consult installation instructions for guidance.


FURRING STRIP LAYOUT




Furring strip spacing will vary depending on the scale of the shapes. Furring strip layouts are included on the Bill of Materials in our online pattern gallery at armstrong.com/patterngallery.

ACOUSTICAL MOUNTING METHODS


Mounting A




Mounting D-20



Mounting C-20



Mounting C-40



Patterns can be installed with adjacent panel edges touching, or with negative space between panels where the wall substrate is visible. Furring installation enhances acoustics, but is not recommended for discontinuous patterns, such as those with a circle shape.

PHYSICAL DATA

Material

FSC® certified (FSC® C007626) Cementitious Wood Fiber; FSC® certified. For more information about FSC certified fire-retardant products, or to view our FSC-certification letter, contact TechLine at 1 877 276-7876.

Surface Finish

Factory-applied latex paint on abuse-resistant silicate surface coating. Natural finish is unpainted but, after coating is applied, panels may appear light in color.

Panels are painted on the edge, however due to fibrous texture of panels, certain angles and lighting conditions will make edge appear less or more painted.

Can be field painted up to 6 times without impacting acoustic or fire performance. See installation instructions for details on paint and application method.

Fire Performance

Class A. Flame Spread Index 25 or less and Smoke Developed Index 50 or less when tested in accordance with ASTM E84.

CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less and Smoke Developed Index of 50 or less (painted, face only).

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Humidity/Sag Resistance

HumiGuard® Plus performance panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.

Installation Considerations

Panels must be mechanically attached to approved substrate per installation instructions.

Use caution and wear appropriate hand, eye, and dust mask protection when cutting and installing Tectum panels. Refer to installation instructions for complete details and cutting recommendations.

Primary (Embodied) Energy

See all LCA information on our EPDs.

Application Considerations

Low angle lighting exaggerates variation inherent to the manufacturing process and is not recommended for Tectum installations.

Design Considerations

Color variation among panels is common due to the natural characteristics of the wood.

Wood fibers may appear orange on natural-colored panels due to the characteristics of the wood.

Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dyelotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

Seismic Restraint

Tectum Direct-Attach wall panels are approved for application in all seismic areas when installed per the seismic guidelines in the Armstrong Ceiling and Wall Installation Instructions.

Design & Pre-Construction Service

For complimentary design and pre-construction assistance, contact ProjectWorks® or visit armstrong.com/projectworks

Cleaning and Disinfecting

Cleaning and CDC-approved disinfecting options available on armstrong.com/cleaning

Warranty

30-Year Warranty. Details at armstrong.com/warranty

Weights and Sold By

1" – 1.65 lbs/SF

Panels sold by the piece. Other accessory elements quantities noted above.

TechLine / 1 877 276-7876
armstrong.com/designart

BPCS-6638-526

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge™ (LBC) are registered trademarks of the International Living Future Institute™; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; FSC® is a registered trademark of Forest Stewardship Council®, A.C., license code FSC-C007626; Revit® is a registered trademark of Autodesk, Inc.; UL is a registered trademark of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2026 AWI Licensing LLC

Armstrong®
World Industries



PARTITIONS & WALLS