




Backer Clip



WoodWorks Grille - Classics Custom Installation - in Dark Cherry

These warm, natural wood ceilings offer installation flexibility and a variety of design options.

KEY SELECTION ATTRIBUTES

- · 10 new standard finishes on solid poplar new are tinted to replicate naturally occurring wood tones
- Panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Coordinating solid wood trims in 4" and 6" depths
- The natural warmth of wood can contribute to biophilic designs and building certification standards like the WELL™ v2 "Nature and Place" feature
- · Select products included in the FAST134 program - ready to ship in 4 weeks or less
- · Installation with dowel or flat backer, or backer and dowel combination
- Integrated downlighting solutions from USAI® Lighting sit perfectly flush with the panel face for a sleek visual
- · Integrate linear lights seamlessly with the Integrated Light Connection Clip and lights from Backlight® srl and XAL®
- · Lighting solutions are certified for fit and finish and engineered to be supported by standard Armstrong suspension systems for use in all areas, including seismic D, E, F zones
- · CleanAssure[™] family of products includes disinfectable panels, suspension systems, and trim
- · Custom slat sizes and finishes available for every project
- · Install in the ceiling, on the wall,
- or create ceiling-to-wall transitions · FSC® certified wood options available as a premium quoted option

Now, Lighting Integration Made Easy



DOWNLIGHTING: WoodWorks Grille – Classics panel with USAI® Micro[™] downlight fixture. Integration details at armstrongceilings.com/downlighting



LINEAR LIGHTING: WoodWorks Grille - Classics panels in Maple with 5-1/4" x 95" linear light fixture. Integration details at armstrongceilings.com/linearlighting



WOODWORKS[®] Grille – Classics Solid Wood Ceiling Panels Backer, Dowel, and Backer & Dowel Combination

С Ш For LEED contribution contact TechLine V V SUSTAIN ш esp. High Performance Sustainable Ceiling Systems Declare. LOCATION PREMIUM DEPENDENT OPTION

FINISH RANGES ON SOLID POPLAR

Our tinted finishes allow the natural character of the poplar to shine through. The images here reflect the visual range that is likely within our product. Installers will want to lay out panels before installing to achieve preferred aesthetic.



Due to printing limitations, shade may vary from actual product. * Painted White finish is not included in the Sustain® portfolio.

Light Cherry (GLC)

Dark Cherry (GDC)


WITH INFILL PANEL



White (GWH)*

Maple (GMP)

STANDARD PANEL CONFIGURATIONS





armstrongceilings.com/woodworksgrille

TechLine 877 276-7876

WOODWORKS® Grille - Classics

Solid Wood Ceiling Panels Backer, Dowel, and Backer & Dowel Combination

SUSTAIN" High Performance Sustainable Ceilling Systems Declare.

				C	C	C	
ems	ME	energy management	construction waste mgmt	regional materials	design for flexibility	EPD	
				LOCA DEPE	TION NDENT		

PERFORMANCE

CleanAssure[™]

0

Participased photosect photosec

ACOUSTICAL INFORMATION

Performance determined by perforation size.

V

esp.

For LEED contribution contact TechLine

VISUAL SELECTION

								ctable	Panels	Is Performance determined by perforation Dots represent high level of performance		
	ltem No.	Custom	Slat Sizes A	Available		Dimensions Nominal W x L x H* (Inches) Custom Sizes Available	% Open Area	Fog	Spray	Wipe	Infill Panel Item No.	NRC
WOODWORKS® Grille – Classics	7263	5/8" W	1-3/8" H	6 slats	1-3/8"	12 × 96 × 1-7/8" Backer Only 12 × 96 × 1-3/8" Dowel Only	69%	٠	۰	0	5823 or 6657	0.75
Backer, Dowel, and Backer & Dowel Combination	7264	5/8" W	1-3/8" H	8 slats	7/8"	12 × 96 × 1-7/8" Backer Only 12 × 96 × 1-3/8" Dowel Only	58%	0	0	0		
	7265	5/8" W	2-1/4" H	6 slats	1-3/8"	12 × 96 × 2-3/4" Backer Only 12 × 96 × 2-1/4" Dowel Only	69%	۰	0	0	SUFFIX GUID	E
	7266	5/8" W	2-1/4" H	8 slats	7/8"	12 × 96 × 2-3/4" Backer Only 12 × 96 × 2-1/4" Dowel Only	58%	۰	0	0		
	7091	5/8" W	3-1/4" H	5 slats	1-3/4"	12 × 96 × 3-3/4" Backer & Dowel 12 × 96 × 3-1/4" Dowel Only	74%	۰	•	0	Backer Only = B	0
	7092	5/8" W	3-1/4" H	6 slats	1-3/8"	12 × 96 × 3-3/4" Backer & Dowel 12 × 96 × 3-1/4" Dowel Only	58%	۰	۰	0		
	7093	5/8" W	4-1/4" H	5 slats	1-3/4"	12 × 96 × 4-3/4" Backer & Dowel 12 × 96 × 4-1/4" Dowel Only	74%	۰	•	0	Dowel Only = D	
	7094	1" W	2-1/4" H	4 slats	2"	12 × 96 × 2-3/4" Backer Only 12 × 96 × 2-1/4" Dowel Only	67%	۰	•	0	Backer & Dowel Combination = I	
	7095	1" W	3-1/4" H	4 slats	2"	12 × 96 × 3-3/4" Backer Only 12 × 96 × 3-1/4" Dowel Only	67%	۰	•	0		
	7096	1" W	4-1/4" H	4 slats	2"	12 × 96 × 4-3/4" Backer & Dowel 12 × 96 × 4-1/4" Dowel Only	67%	۰	•	0	Ŷ	
	7097	1-1/4" W	3-1/4" H	3 slats	2-3/4"	12 × 96 × 3-3/4" Backer Only 12 × 96 × 3-1/4" Dowel Only	69%	۰	0	0		
	7098	1-1/4" W	4-1/4" H	3 slats	2-3/4"	12 × 96 × 4-3/4" Backer & Dowel 12 × 96 × 4-1/4" Dowel Only	69%	٠	۰	•		
	7099	1-1/4" W	5-1/4" H	3 slats	2-3/4"	12 × 96 × 5-3/4" Backer & Dowel 12 × 96 × 5-1/4" Dowel Only	69%	0	•	•		

FAST134 program items ready to ship from manufacturer in 4 weeks or less. Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

♦ When specifying or ordering please include the installation type and color suffixes (e.g., 7092 <u>B</u> <u>D</u> <u>C</u> <u>L</u> <u>C</u> – 6 slats 3-1/4" Backer & Dowel in Light Cherry). Installation suffixes: B0 = Backer, D0 = Dowel, BD = Backer & Dowel Combination

 NOTE: For additional color and size options, or curved applications options with flexible Backers (special order), call TechLine at 1 877 276 7876.
 * Actual panel length is 95" NOTE: Panel backers are black. Custom backer colors available.

WITH INFILL PANEL



WOODWORKS® Grille - Classics

Solid Wood Ceiling Panels Backer, Dowel, and Backer & Dowel Combination


C,	ED° LBC							For	LEED	contri	bution	contac	t Tech	Line		
)	<u>ب</u> ۲			V	V	V		V	V		V	V	V		C	
SUSTAIN" High Performance ainable Ceiling Systems	WEI	energy management	construction waste mgmt	nal rials	design for flexibility		recyclable/ extended producer resp.	ased rials	FSC® (for wood)	sled ent	sourcing of raw materials	material ingredient reporting	low emitting/ materials	ty	acoustics	
Declare.		energy manage	constr waste	regional materials	desig	EPD	recyclabl extended producer	biobased materials	FSC [®] (for v	recycled content	sourcing raw mate	material ingrediei reportin	low emitt materials	lighting quality	acou	
				LOCA DEPEI	TION NDENT				PREMI OPTIO						WITH INFILL PANEL	


ACCESSORIES

			Dimensions Nominal W x L		
	ltem No.♠	Description	(Inches) Custom Sizes Available	Color	Pcs/ Ctn
Suspension Systems	7301	Prelude® XL® 12' HD Main Beam	15/16 × 144 × 1-11/16"	Black	20
Systems	XL7341	Prelude XL 4' Cross Tee	15/16 × 48 × 1-11/16"	Black	60
	XL7328	Prelude XL 2' Cross Tee	15/16 × 24 × 1-3/8"	Black	60
Acoustical nfill Panels	5823	BioAcoustic [™] Infill Panel	24 × 24 × 5/8"	Black Matte	12
	6657	BioAcoustic Infill Panel	11 × 48 × 5/8"	Black Matte	12
Accessories	5672	Junction – 1-3/8"	1-1/2 × 96 × 2"	All finishes	Bulk
	5674 [End Cap – 1-3/8"	3/4 × 96 × 2"	All finishes	Bulk
	5675	End Cap - 2-1/4"	3/4 × 96 × 2-3/4"	All finishes	Bulk
	7170	End Cap – 3-1/4"	3/4 × 96 × 3-3/4"	All finishes	Bulk
	7171	End Cap – 4-1/4"	3/4 × 96 × 4-3/4"	All finishes	Bulk
	7172	End Cap – 5-1/4"	3/4 × 96 × 5-3/4"	All finishes	Bulk
	5687	Backer Clip	3/8 × 11/16 × 7/8"	N/A	250 pcs/pail
	5457GAL1	WoodWorks® Grille Solid End-Stain (Gallon)	N/A	All finishes	1 Gallon
	5457QT1	WoodWorks Grille Solid End-Stain (Quart)	N/A	All finishes	1 Quart
	5688	Dowel Clip	3/8 × 7/8 × 7/8"	N/A	250 pcs/pail
	5671 =	Ledger	1 × 96 × 1/4"	All finishes	Bulk
	7891	12-Gauge Soft Hanger Wire	144" Length	N/A	140
	6459BL	Uptight Clip	5-1/2" x 1-3/4"	Black	25
	RC2BL	RC2 Radius Clip	N/A	Black	205
	7239	Adjustable Trim Clip	-	N/A	50

When specifying or ordering, include the 3-letter color suffix that coordinates with your WoodWorks ceiling: (e.g., 5671 <u>G M P</u>). NOTE: For integration with Axiom[®] trim (Black recommended for use with Solid Wood).

SUSPENSION SYSTEMS (Heavy-duty)





TechLine 877 276-7876 armstrongceilings.com/woodworksgrille



WOODWORKS[®] Grille – Classics Solid Wood Ceiling Panels


Backer, Dowel, and Backer & Dowel Combination




Prelude® XL® Heavy-Duty Suspension System

Backe

SYSTEM INSTALLATION DETAILS




Ceiling Dowel Assembly



Ceiling Backer Assembly

#6 x 1-1/4" bugle head Hi-Lo drywall screw



Wall Backer Assembly

Slat sizes over 2-1/4" are not recommended for wall applications. Contact TechLine for details at 1877 276-7876.

PHYSICAL DATA

Material

Dowel, Slats, Backers, and Tegular panels - solid Poplar Surface Finish

Clear or tinted semi-gloss coating on all finishes except White (GWH), which has a lacquer finish.

Fire Performance Class C: ASTM E84 surface burning characteristics. Flame Spread Index 200 or less. Smoke Developed Index 450 or less.

Fire performance will vary between wood species. Flame stop coating is available as a custom option. Contact

ASQuote@armstrongceilings.com for details. These panels, as with other architectural features located at the ceiling, may obstruct or skew the planned fire sprinkler water distribution pattern, or possibly delay or accelerate the activation of the sprinkler or fire detection systems by channeling heat from a fire either toward or away from the device. Consult a fire protection engineer, NFPA 13, and local codes for guidance where automatic fire detection and suppression systems are present.

Application Considerations

Variation among panels may occur due to the natural characteristics of the wood and grain.

Design Considerations

Custom slat and panel sizes available. For installations where slat alignment is critical, please see the WoodWorks Grille - Forté product line.

Screw Attachment Detail

NOTE: See WoodWorks® Grille installa-

tion instructions for details on faceted and seismic installations at

armstrongceilings.com/woodworks

Backer & Dowel For slat heights over 5", both dowels and backers are required for stability. Backer height is 1/2". Panel backers are black. Custom backer colors available

Infill Panel Use

If no infill panel is used, unfinished parts of the suspension system and Axiom[®] trim will be visible from below. Site Conditions

It is very important that panels are climatized prior to installation. Relative humidity between 25% and 55%, and temperatures between 50°F and 86°F, must be maintained.

Installation Consideration When junction accessory is not used, the result will be a 1" gap between slat lengths.

Seismic Restraint

WoodWorks Grille – Classics panels have been engineered, tested, and approved for application in all seismic areas when installed per Armstrong Ceilings installation instructions.

Cleaning and Disinfecting Cleaning and CDC approved disinfecting options available on amstrongceilings.com/cleaning

FAST134 Program Considerations

Size of Job Matters: Big jobs, over 2500 SF or 50 pieces for shapes/vertical elements will have longer lead times.

2-1/4" Slat

Location Matters: Transit time not included. We are ready to ship in 1 week on FAST1 items. However, transit to the states west of Wyoming may add time.

Distributor Truck Schedule Matters: We rely on distribution to help move products around the country. When speed matters, work with your local distributor to ensure FAST134 service.

Stock vs Made-to-Order Matters: FAST3 & FAST4 items are made-to-order and will ship direct to distributor. FAST1 (stocked items) will go through distribution and depend on distributor truck schedules.

Warranty

Details at armstrongceilings.com/warranty

Weight

7263 - 0.8 lbs/SF 7264 - 1.64 lbs/SF 7094 - 14 lbs/SF 7265 - 1.3 lbs/SF 7266 - 1.8 lbs/SF 7097 - 1.9 lbs/SF 7095 - 3.06 lbs/SF 7091 - 2.24 lbs/SF 7092 - 1.9 lbs/SF 7098 - 2.5 lbs/SF 7096 - 4.05 lbs/SF 7093 - 2.1 lbs/SF 7099 - 4 54 lbs/SE

LEED" is a registered trademark of the U.S. Green Building Council; Declare" and Living Building Challenge" (LBC) are registered trademarks of the International Living Future Institute"; WELL" and WELL Building Standard" are trademarks of the International WELL Building Institute; XAL" is a registered trademark of XAL (mbH, Inc.; Backlight srl is a trademark of BACKLIGHT srl; Revit" is a registered trademark of XAL (mbH, Inc.; registered trademark of Forest Stewardship Council", A.C., license code FSC-C007626; all other trademarks used herein are the property of AWI Licensing LLC nd/or its affiliates © 2023 AWI Licensing LLC



Techl ine / 1877 276-7876 armstrongceilings.com/woodworksgrille BPCS-5106-223



WoodWorks Grille - Classics panels in Maple with 5-1/4" x 95" linear light fixture

VISUAL SELECTION

Seamlessly integrate linear light fixtures from Backlight[®] srl and XAL[®] with standard or made-to-order WoodWorks[®] Grille – Classics Backeronly panels using Integrated Light Connection Clips that suspend lights directly from the suspension system. This eliminates the need for independent support of the fixture or modification of the suspension system.

KEY SELECTION ATTRIBUTES


- Engineered and tested clip and suspension system seamlessly integrate lighting with grid
- Install lights seamlessly for WoodWorks Grille Backer Only Panels
- Low-profile, pre-engineered light fixture in coordinating 2", 3-1/4", and 5-1/4" widths from Backlight srl and XAL for a flush. sleek visual
- · Approved for use in all seismic categories

DESIGN CONSIDERATIONS

- Length of lights are designed to coordinate with the length of panels
- Lights must run parallel with slat direction and are not for use in perimeter panels
- Reveal between light and slats will coordinate
 with the reveal from slat to slat
- Modified panels are required to leave outside slats intact (slats along edges cannot be removed)
- Coordination between ceiling contractor and electrician is required for installation

	Item No.		Description	Coordinating WoodWorks Grille – Classics Panel Item No.	Panel Field Modification Required*	Compatible Partner Light Fixture Dimensions W x L (Inches)	Clips Required per Light Fixture
VoodWorks	8171WGBOC01	PA	1-3/8" Integrated Light Connection Clip	7263B0	Remove 1 slat	2" x 95"	4
Grille – Classics					Remove 2 slats	3-1/4" x 95"	4
		\odot			Remove 3 slats	5-1/4" x 95"	4
				7264B0	Remove 1 slat	2" x 95"	4
					Remove 2 slats	3-1/4" x 95"	4
					Remove 2 slats	5-1/4" x 95"	4
	8171WGBOC02	- •	2-1/4" Integrated Light Connection Clip	7094BO	Remove 1 slat	2" x 95"	4
			5 5 1		Remove 2 slats	3-1/4" x 95"	4
		\mathbf{a}			Remove 2 slats	5-1/4" x 95"	4
				7265B0	Remove 1 slat	2" x 95"	4
					Remove 2 slats	3-1/4" x 95"	4
					Remove 3 slats	5-1/4" x 95"	4
				7266B0	Remove 2 slats	2" x 95"	4
					Remove 3 slats	3-1/4" x 95"	4
					Remove 4 slats	5-1/4" x 95"	4
	8171WGBOC03	PP	3-1/4" Integrated Light Connection Clip	7266BO	Remove 1 slat	2" x 95"	4
					Remove 2 slats	3-1/4" x 95"	4
					Remove 2 slats	5-1/4" x 95"	4
		\odot		7097BO	No modification	2" x 95"	4
					Remove 1 slat	2" x 95"	4
					Remove 1 slat	3-1/4" x 95"	4
					Remove 1 slat	5-1/4" x 95"	4

* Made-to-order panels that eliminate the need for field modification of standard panels are available via ASQuote@armstrongceilings.com Contact ASQuote@armstrongceilings.com for Backer & Dowel and Dowel Only panels to be used with integrated lighting solutions. NOTE: Items 8171WGBOC01, 8171WGBOC02, and 8171WGBOC03 are packaged 12 pcs/ctn



LIGHTING FIXTURES

Compatible with Backlight srl CHIARO light fixture and XAL® PANO Low-Profile Linear Plank light fixture




For detailed lighting information, contact your local Backlight srl or XAL® representative.



XAL®, CHIARO, and PANO are trademarks of XAL, Inc.; Backlight srl and PANO are trademarks of BACKLIGHT srl; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2023 AWI Licensing LLC



LIGHTING SOLUTIONS WOODWORKS® Grille - Classics Downlighting



Seamlessly integrate downlight fixtures from USAI® Lighting with standard WoodWorks® Grille - Classics Backer & Dowel or Backer-only panels. Attach lights directly from the suspension system, eliminating the need for independent support of the fixture or modification of the suspension system.

KEY SELECTION ATTRIBUTES

- Engineered and tested to seamlessly integrate lighting fixtures with grid
- Install lights seamlessly for WoodWorks Grille - Classics Backer & Dowel and Backer-only Panels. Custom Dowel-only solutions are possible through ASQuote.
- USAI Lighting fixtures provide different downlighting styles for design flexibility
- Approved for use in all seismic categories

DESIGN CONSIDERATIONS


- · Lights are designed to sit flush with the face of the WoodWorks panels
- · Coordination between ceiling contractor and electrician is required for installation

WoodWorks Grille - Classics panels with USAI Micro for WoodWorks - Vertical Slats light fixture


WOODWORKS GRILLE - CLASSICS - Backer & Dowel and Backer-only Panels

WOODWORKS Panel Item No.	Slat Width	Slat Height	Open Area Between Slats	Slats Per Panel	Coordinating USAI Fixture Family	Coordinating USAI Fixture Part Numbers	USAI Grid Mounting Bar Item No.	USAI Trim Yoke and Centering Spacer Item No.
7091BD*	5/8"	3-1/4"	1-3/4"	5	Micro [™] for WoodWorks – Vertical Slats (4 cell max)	MXGXX-VS	UA2	MXGVS-GL91
7093BD*	5/8"	4-1/4"	1-3/4"	5	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL93
7096BD*	1"	4-1/4"	2"	4	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL96
7098BD*	1-1/4"	4-1/4"	2-3/4"	3	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL98
7099BD*	1-1/4"	5-1/4"	2-3/4"	3	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL99
7094BO	1"	2-1/4"	2"	4	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL94
7095BO	1"	3-1/4"	2"	4	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL95
7097BO	1-1/4"	3-1/4"	2-3/4"	3	Micro for WoodWorks – Vertical Slats (8 cell max)	MXGXX-VS	UA2	MXGVS-GL97

NOTE: Refer to lighting partner cut sheets for light location considerations No panel field modification is required for USAI Micro light integration with WoodWorks Grille – Classics panels. *Trimming dowels is recommended for access, unless remote driver is used.



USAI® Micro[™] for WOODWORKS -Vertical Slats Fixture Housing



USAI Grid Mounting Bars Item UA2

LIGHTING FIXTURES Compatible with USAI Micro for WoodWorks – Vertical Slats lighting fixtures.



For detailed lighting information, contact your local USAI Lighting representative.

TechLine / 1877 276-7876 armstrongceilings.com/downlighting BPCS-5106-223 XAL® is a registered trademark of XAL Inc.; Backlight* sti is a registered trademark of BACKLIGHT srl; USAI® is a trademark of USAI Lighting, LLC; LEED® is a registered trademark of the U.S. Green Building Council; Revit* is a registered trademark of Autodesk, Inc.; FSC is a registered trademark of Forest Stewardship Council*, A.C., license code FSC-C007626; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2023 AWI Licensing LLC

