

Ultima® Templok® Ceiling Panels







High Performance Mineral Fiber



In Accordance with
ISO 14025 and ISO 21930:2017

Life Cycle Impact Categories (A1-A3) for 1 ft²

Cradle-to-Gate environmental impacts for 1 ft² of Ultima® Templok® ceiling panels

| | | | |
|--|--|--|--|
|  | Embodied Carbon (GWP₁₀₀) (excluding biogenic carbon) 7.52E-01 kg CO ₂ eq. |  | Embodied Carbon (GWP₁₀₀) (including biogenic carbon) 6.98E-01 kg CO ₂ eq. |
|  | Photochemical Oxidation Formation 2.90E-09 kg O ₃ eq. |  | Acidification Potential 2.17E-03 kg SO ₂ eq. |
|  | Ozone Depletion Potential 2.90E-09 kg CFC 11 eq. |  | Eutrophication Potential - Marine 1.55E-03 kg N eq. |

Ultima® Templok® Ceiling Panels with
Prelude® XL® Suspension System

Committed to Sustainability

Armstrong World Industries leads in delivering solutions that meet today’s most stringent industry sustainability standards. We are committed to environmental responsibility in all aspects of our business, and carbon reduction is part of our 2030 Company goals and ambitions. We were one of the first companies to create and publish the Environmental Product Declaration (EPD) in the ceiling industry. We have over a decade of experience using Life Cycle Assessment (LCA) to evaluate environmental impacts of our products starting with design, to raw materials, and through our operations. We are constantly working to optimize our operations and products to reduce their environmental impact. We believe the use of LCA and our commitment to transparency of our products’ carbon footprint is critical to contributing to decarbonization of the built environment.

Contents

| |
|--|
| Performance features like acoustics, light reflectance, and durability |
| Product application and use |
| Product ingredients and their sources |
| How the product is produced |
| LCA results, including global warming potential and primary energy usage |
| Total impacts over the product life cycle |

For more information visit
armstrongceilings.com/transparency







Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

1. CONTENT OF THE EPD

| | |
|--|---|
| EPD Program & Program Operator Name, Address, Logo, and Website | ASTM International – 100 Barr Harbor Drive West Conshohocken, PA, 19428, USA |
| General Program Instructions & Version Number | ASTM Program Operator for Product Category Rules (PCR) and Environmental Product Declarations (EPDs), General Program Instructions, Version: 8.0, Revised 04/29/20 |
| Manufacturer Name & Address | Armstrong World Industries 2500 Columbia Avenue Lancaster, PA 17603 |
| Declaration Number | EPD 1095 |
| Declared Product & Declared Unit | 0.093m ² (1ft ²) of installed ceiling panel, with a product Reference Service Life (RSL) of 30 years |
| Reference PCR & Version Number | PCR for Building-Related Products and Services – Part A: LCA Calculation Rules and Report Requirements, UL 10010, UL v.4.0, March 2022 PCR Guidance for Building-Related Products and Services – Part B: Non-Metal Ceiling and Interior Wall Panel EPD Requirements, UL Environment, v2, 04/2021 |
| Description of Product's Intended Application & Use (As Identified When Determining Product RSL) | Ultima® Templok® Ceiling Panels, PVC-free |
| Product RSL Description (if appl.) | 30 Years |
| Markets of Applicability | Commercial and Residential Interior Furnishing |
| Date of Issue | 12/16/2025 |
| Period of Validity | 5 years |
| EPD Type | Product-Specific |
| Dataset Variability | Industry Average Only |
| EPD Scope | Cradle to Gate with Options |
| Year(S) of Reported Manufacturer Primary Data | 2024 |
| LCA Software & Version Number | Sphera® for Experts, version 10.8.0.14 |
| LCI Database(S) & Version Number | MLC Database (formerly Gabi) 2025.1 |
| LCIA Methodology & Version Number | TRACI 2.2, CML v4.7 2016 |
| The Sub-Category PCR Review Was Conducted By: | Lindita Bushi, PhD (Chair) Tom Gloria, (PhD) Olivia Palmer |
| This Declaration Was Independently Verified In Accordance with ISO 14025: 2006. The UL Environment "Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report," Serves as the Core PCR. <input type="checkbox"/> Internal <input checked="" type="checkbox"/> External | Tim Brooke, ASTM International  |
| The EPD conforms with (select one): | <input checked="" type="checkbox"/> ISO 21930:2017 <input type="checkbox"/> EN 15804:2013+A1:2014 <input type="checkbox"/> EN 15804:2013+A2:2019 |
| This Life Cycle Assessment Was Conducted in Accordance with ISO 14044 and The Reference PCR by: | Armstrong World Industries, Inc. |
| This Life Cycle Assessment was Independently Verified in Accordance with ISO 14044 and the Reference PCR by: | Thomas Gloria, Ph.D. Industrial Ecology Consultants  |
| Limitations | |

Environmental declarations from different programs (ISO 14025) may not be comparable.

Comparison of the environmental performance of Non-Metal Ceiling and Wall System Products using EPD information shall be based on the product's use and impacts at the building level, and therefore EPDs may not be used for comparability purposes when not considering the building energy use phase as instructed under this PCR.

Full conformance with this PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible.

Example of variations: Different LCA software and background LCI datasets may lead to differences in results for upstream or downstream of the life cycle stages declared.





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

2. GENERAL INFORMATION

2.1 DESCRIPTION OF ORGANIZATION

Armstrong World Industries, Inc. (AWI) is a leader in the design and manufacture of innovative commercial and residential ceiling, wall and suspension system solutions in the Americas. At home, at work, in healthcare facilities, classrooms, stores, or restaurants, Armstrong World Industries offers interior solutions that help to enhance comfort, save time, improve building efficiency and overall performance, and create beautiful spaces.

2.2 PRODUCT DESCRIPTION

Smooth textured mineral fiber ceiling combines exceptional acoustical performance, energy savings and enhanced thermal comfort using advanced Phase Change Material (PCM) technology (UNSPSC Code 30161601 and CSI 09 51 00).

2.2.1 Product-Specific EPD

Ultima® Templok® ceiling panels are manufactured by Armstrong World Industries in Pensacola, Florida (32505) and Marietta, Pennsylvania (17547).

2.2.2 Product Identification


Ultima® Templok® fine-textured mineral fiber panels are washable, impact- and scratch-resistant, with exceptional acoustical performance. This product also features a Templok® panel adhered to the back containing advanced Phase Change Material (PCM) technology, which helps regulate indoor temperatures and improve thermal comfort for building occupants.

2.2.3 Product Specification

These products generally fall under ASTM E1264 Section 5.2 designation as Type A – Mineral base with painted finish.

2.2.4 Flow Diagram

Ultima® Templok® ceiling panels are made in a wet-formed process which is shown in the flow diagram below.





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

2.3 PRODUCT AVERAGE

2.3.2 Product-Specific EPD

This EPD is specific to Ultima® Templok® ceiling panels. A weighted average approach was applied. Inputs were developed based on 2024 production volumes and weights.

2.4 APPLICATION

The products covered by this EPD are designed to be installed in a suitable metal grid system.

2.5 MATERIAL COMPOSITION

Major raw materials used in ceiling panel manufacturing are summarized in the table below. No substances required to be reported as hazardous (per Part A Section 2.8.6 Table 4 of the PCR) are associated with the production of this product.

Table 1. Material Composition

| Material | Mineral Wool | Salt | Water | Perlite | Fiberglass | Corn Starch | Film |
|---------------------------------|--------------|--------|--------|---------|------------|-------------|------|
| Ultima® Templok® Ceiling Panels | 25-35% | 25-30% | 10-15% | 5-10% | 1-5% | 1-5% | 1-5% |

2.6 TECHNICAL REQUIREMENTS

Table 2. Technical Data

| Property | Test Method | Ultima® Templok® Ceiling Panels |
|---|------------------------|---------------------------------|
| Sound absorption coefficient (NRC) | ASTM C423 | 0.75 |
| Interzone attenuation of open office components (AC) | ASTM E1111, ASTM E1110 | – |
| Sound Transmission Class (STC) | ASTM E413, ASTM E90 | – |
| Sound attenuation between rooms sharing a common ceiling plenum (CAC) | ASTM E1414, ASTM E413 | 39 |
| Light reflectance | ASTM E1477 | 0.88 |
| Flame spread/smoke development | ASTM E84, ASTM E1264 | Class A |

2.7 PROPERTIES OF DECLARED PRODUCT AS DELIVERED

The final EPD is available on the Armstrong website (armstrongceilings.com/epd) and is under the Finish category in the EC3 Tool (buildingtransparency.org).

3. METHODOLOGICAL FRAMEWORK

This study provides life cycle inventory and environmental impacts relevant to Armstrong® ceilings. The LCA follows an attributional approach as outlined in ISO 21930 Section 7.1.1 – see also PCR Part A-6.

3.1 DECLARED UNIT

The declaration refers to the declared unit of 0.093 m² (1 ft²) of installed ceiling panel, as defined by the PCR.

3.2 FUNCTIONAL/DECLARED UNIT PROPERTIES

Table 3. Functional or Declared Unit Properties

| | Ultima® Templok® Ceiling Panels |
|---|---------------------------------|
| Declared Unit – m ² (ft ²) | 0.093 (1.0) |
| Declared Thickness – cm (in) | 2.54 (1.0) |
| Surface Weight – kg/0.093 m ² (lbs/ft ²) | 0.953 (2.10) |
| Density – kg/m ³ (lbs/ft ³) | 403.7 (25.2) |

3.3 SYSTEM BOUNDARY

The scope of the study includes production, installation, and end of life. Production of capital equipment, facilities, and infrastructure required for manufacture are outside the scope of this assessment. Details of inclusions and exclusions from the system boundary are listed below.

Table 4. Elements Included in the Cradle To Gate with Options Study

Includes

- Raw materials production (A1)
- Inbound transport of raw materials to production facility (A2)
- Manufacturing of panels (A3)
- Electricity and fuel combustion (A3)
- Packaging of final products (A3)
- Transportation to the job site (A4)
- Installation and installation waste (A5)
- Deconstruction – manual, no impact (C1)
- End of life, including transport (C2-C4)

Excludes

- Construction of capital equipment and other infrastructure flows
- Maintenance and operation of support equipment
- Human labor and employee transport
- Manufacture and transport of packaging materials not associated with final product
- Use Phase (B1 to B7)
- Benefits and loads beyond the system boundary (D)





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

3.4 PRODUCT-SPECIFIC CALCULATIONS FOR END-OF-LIFE PHASE (MODULES C1-C4)

At this time, there is no industry consensus for product-specific assumption behind reported scenarios for information in modules C1-C4. Armstrong facilitates ceiling panels recycling through our Takeback program. The recovery data is based on internal averages for commingled ceiling panels that arrived at Armstrong factories from the construction and demolition site at end of product life. Remaining panels were assumed to be landfilled as per standard industry practice.

3.5 REFERENCE SERVICE LIFE AND ESTIMATED BUILDING SERVICE LIFE

In accordance with the PCR, the Reference Service Life (RSL) for this study was assumed to be 30 years.

3.6 ALLOCATION

Allocation at the manufacturing plant was based on production volume. Allocation of background data (energy and materials) taken from the Sphera LCA FE database..

3.7 CUT-OFF RULES

No known flows are deliberately excluded from this EPD. The system boundary was defined based on relevance to the goal of the study. For the processes within the system boundary, all available energy and material flow data have been included in the model. In cases where no matching life cycle inventories are available to represent a flow, proxy data have been applied based on conservative assumptions regarding environmental impacts.

3.8 DATA SOURCES

Primary data for this study was collected from the manufacturing facility for 2024 and datasets for materials upstream from manufacturing were obtained from the GaBi database Sphera LCA FE database.

3.9 DATA QUALITY

The data quality ranges from good to very good. The temporal quality of the data is very good with both manufacturing-specific data and MLC Database (formerly GaBi) background data from 2024. Because primary and secondary data were collected specifically to the location of manufacture when possible, geographical representativeness is considered to be good.

3.10 PERIOD UNDER REVIEW

All the primary data in the scope of this analysis was collected from Armstrong manufacturing facilities during 2024.

3.11 COMPARABILITY AND BENCHMARKING

We do not have any data on comparable non-competitive products to report. Comparison of the environmental performance of construction works and construction products using EPD information shall be based on the product's use and impacts at the construction works level. In general, EPDs may not be used for comparability purposes when not considered in a construction works context. Given the PCR ensures products meet the same functional requirements, comparability is permissible provided the information given for such comparison is transparent and the limitations of comparability explained.

3.12 ESTIMATES AND ASSUMPTIONS

The datasets for materials upstream from manufacturing are from the Sphera LCA FE database. When inventories were not available for materials, conservative proxy datasets were chosen based on similarity of material. Additionally and consistent with the PCR, the following assumptions in Table 5 related to transport, installation, and deconstruction procedures were made.

Table 5. Transport, Installation, & Deconstruction Procedures

| | |
|--|--|
| Product transport from point of manufacture to building site | Mode: Diesel-powered truck/trailer Distance: 800 km |
| Product transport from building site to waste processing | Mode: Diesel-powered truck/trailer Distance: 35 km |
| Installation & deconstruction procedures | Manual (no operational energy use) |

3.13 UNITS

Units commonly used in the North American market are included in addition to the required SI units.





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

4. TECHNICAL INFORMATION & SCENARIOS

4.1 MANUFACTURING

The manufacturing process has been described in a simple flow chart in Section 2.2.4. When a product is manufactured at multiple locations, a volume-based averaging of the input parameters approach was used. Any manufacturing waste was reported in the primary data for this study.

4.2 PACKAGING

Armstrong® ceiling panels are packaged in cardboard, placed on wood pallets and wrapped in LDPE film for shipping. Specific parameter inputs can be found in Table 7.

The US Corrugated Packaging Alliance (CPA) dataset was used in the LCA study. This dataset was developed from the Life Cycle Assessment of U.S. Average Corrugated Panel. The U.S. average corrugated panel studied in the LCA consists of 66.8% liner board and 33,2 corrugated medium with an average basis weight of 131.6 lb./1000 ft² (msf 0.643 kg/m²). The industry average container-board utilized about 52% recovered fiber, primarily old, corrugated containers (OCC), with the balance supplied mostly by kraft and semi-chemical pulp.

The data set covers all relevant process steps/technologies over the supply chain of the represented cradle to gate inventory with a very good overall data quality. The inventory is based on industry data and is completed where necessary, with secondary data.

4.3 TRANSPORTATION

Transportation emissions and fuels throughout the life cycle phases are included in this study. Transportation associated with raw materials reflect the actual modes of transportation and mileage.

The following information specifies any transport after the manufacturing gate. Details of type of transport, type of vehicle, distance, type, and amount of energy carrier are listed. These values are consistent with industry standard assumptions.

Table 6. Transport to the Building Site (A4)

| Material | Ultima® Templok® Ceiling Panels | Unit |
|---|---------------------------------|------------|
| Fuel Type | – | Diesel |
| Liters of fuel (Diesel) | 42.19 | L/100km/m³ |
| Vehicle Type | – | Truck |
| Transport distance | 805 | km |
| Capacity utilization (including empty runs) | 67 | % |
| Gross density of products transported | 404 | kg/m³ |
| Capacity utilization volume factor | 0.87 | – |





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

4.4 PRODUCT INSTALLATION

The ceiling system must be installed in accordance with Armstrong Ceilings installation guidelines. Our ceiling system installation brochure, "Installing Suspended Ceilings", is a general application overview, covering essential steps of a basic suspended ceiling installation. You can reference this document at armstrongceilings.com/installationinstructions

The information in Table 7 shall be provided for all construction products to specify the end-of-life scenarios used for packaging or to support the development of the end-of-life scenarios for packaging at the construction works level where the module is not declared. Scenarios shall only model processes, for example, recycling systems that have been proven to be economically and technically viable.

It is assumed that the on-site scrap material will be sent to a landfill within 35 km (21.7 miles) of the jobsite. Production, transport, waste processing and disposal of 7% of installation waste are included in module A5, calculations for waste at the construction site.

Table 7. Installation Into The Building (A5)

| Name | Ultima® Templok® Ceiling Panels | Unit |
|--|---------------------------------|------------------------|
| Ancillary materials | 0 | kg |
| Net freshwater consumption specified by water source and fate (X m³ river water evaporated, X m³ city water disposed to sewer) | 0 | m³ |
| Other resources | 0 | kg |
| Electricity consumption | 0.4 | kWh |
| Other energy carriers | 0 | MJ |
| Product loss per declared unit | 0.067 | kg |
| Waste materials at the construction site before waste processing, generated by product installation | 0 | kg |
| Output materials resulting from on-site waste processing | 0 | kg |
| Mass of packaging waste specified by type | | |
| Plastic | 0.002 | kg |
| Metal | 0 | kg |
| Kraft | 0.0004 | kg |
| Cardboard | 0.008 | kg |
| Wood | 0.014 | kg |
| Biogenic carbon contained in packaging | 0.039 | kg CO ₂ eq. |
| Direct emissions to ambient air, soil and water | – | kg |
| VOC emissions | ≤ 0.5 | mg/m³ |

4.5 USE

A product's RSL depends on the product properties and reference in-use conditions. The default RSL assumed in this PCR is 30 years for both ceiling and wall products.

4.6 DISPOSAL

End of Life

The end-of-life phase for the ceiling panels was included in the study. End-of-life impacts include landfill disposal of ceiling panels.

Table 8. End of Life (C1-C4)

| Name | Ultima® Templok® Ceiling Panels | Unit |
|---|---|--------------------|
| Collection process (specified by type) | Collected separately | 0 kg |
| | Collected with mixed construction waste | 0 kg |
| Recovery (specified by type) | Reuse | 0 kg |
| | Recycling | 0.000 kg |
| | Incineration | 0 kg |
| | Incineration with energy recovery | 0 kg |
| | Energy conversion (specify efficiency rate) | 0 kg |
| Disposal (specified by type) | Product or material for final disposal | 0.858 kg |
| Removals of biogenic carbon (excluding packaging) | 0 | kg CO ₂ |

4.7 REUSE PHASE

Table 9. Reuse, Recovery, and/or Recycling Potentials (D), Relevant Scenario Information

| Name | Value | Unit |
|--|-------|------|
| Net energy benefit from energy recovery from waste treatment declared as exported energy in C3 (R>0.6) | 0 | MJ |
| Net energy benefit from thermal energy due to treatment of waste declared as exported energy in C4 (R<0.6) | 0 | MJ |
| Net energy benefit from material flow declared in C3 for energy recovery | 0 | MJ |
| Process and conversion efficiencies | – | |
| Further assumptions for scenario development | – | |



Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

5. ENVIRONMENTAL INDICATORS DERIVED FROM LCA

5.1 LCA RESULTS FROM LCIA

The Life Cycle Assessment (LCA) was performed according to ISO 14040 guidelines and follows the specific PCR instructions. The cradle-to-gate with options LCA consists of raw material production, transport of raw materials to production facility prior to processing, manufacturing of ceiling and wall panels, packaging; transportation to job site and installation, and end of life including disposal or recycling to Armstrong factories.

5.2 LCA RESULTS FROM LCIA

Life cycle impacts reported below are based on TRACI 2.2 methodology. Results are provided in reference to the declared unit. For the other impact categories, results are presented in the tables below using the ISO 21930 standard and for the declared unit. Because products include biobased content, they store or sequester carbon. Table 11 includes both Global Warming Potential (GWP) excluding biogenic and GWP including biogenic carbon. LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks. These six impact categories are globally deemed mature enough to be included in Type III environmental declarations. Other categories are being developed and defined and LCA should continue making advances in their development. However, the EPD users shall not use additional measures for comparative purposes.

Table 10. Description of the System Boundary Modules*

| (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED) | | | | EPD Type Cradle to Gate w/ Options | |
|---|----|------------------------|---|--|-----|
| Production | A1 | Raw Material Supply | | x | |
| | A2 | Transport | | x | |
| | A3 | Manufacturing | | x | |
| Construction | A4 | Transport to site | | x | |
| | A5 | Assembly/Install | | x | |
| Use | B1 | Use | B6 Operational Energy Use of Building Integrated System During Product Use | B7 Operational Water Use of Building Integrated System During Product Use | MND |
| | B2 | Maintenance | | | MND |
| | B3 | Repair | | | MND |
| | B4 | Replacement | | | MND |
| | B5 | Refurbishment | | | MND |
| | B6 | Operational Energy Use | | | MND |
| | B7 | Deconstruction | | | MND |
| End of Life | C1 | Deconstruction | | x | |
| | C2 | Transport | | x | |
| | C3 | Waste processing | | x | |
| | C4 | Disposal | | x | |
| Benefits & Loads Beyond System Boundary | | D | Reuse, Recovery, Recycling Potential | | MND |

* Results for modules A1-A3 results are aggregated, as described in the PCR.

Table 11. TRACI 2.2 Impact Assessment for 0.093 m² (1 ft²) of Ultima® Templok® Ceiling Panels *

| Parameter | Source | Unit | Product (A1-A3) | A4 | A5 | C2 | C4 |
|-------------------------|-----------|------------------------|-----------------|----------|-----------|----------|----------|
| GWP, excluding biogenic | TRACI 2.2 | kg CO ₂ eq. | 7.52E-01 | 6.21E-03 | 2.85E-03 | 1.51E-03 | 7.67E-02 |
| GWP, including biogenic | TRACI 2.2 | kg CO ₂ eq. | 6.98E-01 | 6.23E-03 | 1.25E-02 | 1.51E-03 | 1.09E-01 |
| ODP | TRACI 2.2 | kg CFC 11 eq. | 2.90E-09 | 1.78E-15 | -1.35E-14 | 4.31E-16 | 3.05E-14 |
| AP | TRACI 2.2 | kg SO ₂ eq. | 2.17E-03 | 1.78E-05 | -1.20E-06 | 4.26E-06 | 2.87E-04 |
| EP - marine | TRACI 2.2 | kg N eq. | 1.55E-03 | 1.61E-05 | -2.79E-06 | 3.84E-06 | 9.28E-05 |
| EP - freshwater | TRACI 2.2 | kg N eq. | 1.98E-06 | 5.13E-09 | 4.52E-08 | 1.24E-09 | 8.37E-07 |
| SFP | TRACI 2.2 | kg O ₃ eq. | 2.90E-09 | 1.78E-15 | -1.35E-14 | 4.31E-16 | 3.05E-14 |
| FFD | TRACI 2.2 | MJ Surplus | 9.65E+00 | 8.01E-02 | -2.85E-02 | 1.94E-02 | 1.47E-01 |

* Modules C1 and C3 are null





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

5.3 LCA RESULTS FROM LCI

Table 12. LCA Results – Resource Use for 0.093 m² (1 ft²) of Ultima® Templok® Ceiling Panels *

| Parameter | Unit | A1-A3 | A4 | A5 | C2 | C4 |
|---|----------------|-----------|----------|-----------|----------|----------|
| RPR _e Renewable primary resources used as energy carrier (fuel) | MJ, LHV | 1.87E+00 | 3.36E-03 | -1.59E-01 | 8.16E-04 | 2.15E-02 |
| RPR _m Renewable primary resources with energy content used as material | MJ, LHV | -5.79E-02 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRPRE Non-renewable primary resources used as an energy carrier (fuel) | MJ, LHV | 9.56E+00 | 8.09E-02 | -3.44E-02 | 1.96E-02 | 1.51E-01 |
| NRPRM Non-renewable primary resources with energy content used as material | MJ, LHV | -4.06E-01 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| SM Secondary materials | kg | 3.00E-02 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RSF Renewable secondary fuels | kg | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRDF Non-renewable secondary fuels | m ³ | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RE Recovered Energy | MJ, LHV | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| FW Use of net fresh water | m ³ | 4.76E-03 | 9.49E-04 | 8.80E-06 | 8.81E-07 | 2.70E-05 |

* Modules C1 and C3 are null

Table 13. LCA Results – Biogenic Carbon for 0.093 m² (1 ft²) of Ultima® Templok® Ceiling Panels *

| Parameter | Unit | Ultima® Templok® Ceiling Panels |
|--|-----------------------|---------------------------------|
| BCRP Biogenic Carbon Removal from Product | [kg CO ₂] | -0.070 |
| BCEP Biogenic Carbon Emission from Product | [kg CO ₂] | 0.026 |
| BCRK Biogenic Carbon Removal from Packaging | [kg CO ₂] | -0.039 |
| BCEK Biogenic Carbon Emission from Packaging | [kg CO ₂] | 0.015 |
| BCEW Biogenic Carbon Emission from Combustion of Waste from Renewable Sources Used in Production Processes | [kg CO ₂] | 0 |
| CCE Calcination Carbon Emissions | [kg CO ₂] | unk |
| CCR Carbonation Carbon Removals | [kg CO ₂] | unk |
| CWNR Carbon Emissions from Combustion of Waste from Non-Renewable Sources used in Production Processes | [kg CO ₂] | 0 |

* Modules C1 and C3 are null



Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017


Table 14. LCA Results – Output Flows & Waste Categories for 0.093 m² (1 ft²) of Ultima® Templok® Ceiling Panels *

| Parameter | Unit | A1-A3 | A4 | A5 | C2 | C4 |
|---|------|----------|----------|-----------|----------|----------|
| HWD Hazardous waste disposed | kg | 1.43E-06 | 1.34E-11 | -2.05E-10 | 3.25E-12 | 3.62E-11 |
| NHWD NHWD Non-hazardous waste disposed | kg | 5.28E-02 | 8.28E-06 | 9.62E-03 | 2.01E-06 | 4.25E-01 |
| RWD Radioactive waste disposal | kg | 5.90E-04 | 2.78E-07 | -2.11E-06 | 6.74E-08 | 1.67E-06 |
| HLRW HLRW High-level radioactive waste, conditioned, to final repository | kg | 7.04E-07 | 3.30E-10 | -2.26E-09 | 8.01E-11 | 1.89E-09 |
| ILLRW Intermediate- and low-level radioactive waste, conditioned, to final repository | kg | 5.89E-04 | 2.77E-07 | -2.11E-06 | 6.73E-08 | 1.67E-06 |
| CRU Components for re-use | kg | 3.00E+00 | 3.00E+00 | 4.00E+00 | 5.00E+00 | 6.00E+00 |
| MFR Materials for recycling | kg | 0.00E+00 | 0.00E+00 | 7.86E-03 | 0.00E+00 | 4.57E-03 |
| MER Materials for energy recovery | kg | 3.00E+00 | 3.00E+00 | 4.00E+00 | 5.00E+00 | 6.00E+00 |
| EE Recovered energy exported from the product system | MJ | 0.00E+00 | 0.00E+00 | 5.93E-03 | 0.00E+00 | 0.00E+00 |

* Modules C1 and C3 are null

6. LCA: INTERPRETATION

The ceiling life cycle covered in this study concluded that the ceiling panel manufacturing process and raw materials in the ceiling panel have the greatest impact on “carbon footprint” as represented by Global Warming Potential [GWP].





Ultima® Templok® Ceiling Panels

High Performance Mineral Fiber

In Accordance with
ISO 14025 and ISO 21930:2017

7. ADDITIONAL ENVIRONMENTAL INFORMATION

7.1 ENVIRONMENT & HEALTH DURING MANUFACTURING

Armstrong World Industries has a comprehensive environmental, health, and safety management program. Risk reduction begins in the product design process. All products go through a safety, health, and environmental review prior to sale. Armstrong also has a long-standing commitment to the safety and health of all our employees.

Armstrong World Industries is equally committed to reducing our environmental impact. As with safety goals, each manufacturing facility has environmental initiatives focused on responsible use of energy and water, and on waste reduction.

7.2 ENVIRONMENT & HEALTH DURING INSTALLATION

All recommendations shall be utilized as indicated by SDS and installation guidelines. Specific product SDS and installation instructions can be downloaded at:
armstrongceilings.com/pdbupimages-clg/217521.pdf

7.3 ENVIRONMENTAL ACTIVITIES & CERTIFICATIONS

All environmental certifications can be found at:
armstrongceilings.com

7.4 FURTHER INFORMATION

Additional Information can be found at:
armstrongceilings.com

8. PROJECT REPORT & SUPPORTING DOCUMENTATION

This study provides life cycle inventory and environmental impacts relevant to Armstrong® suspended ceilings. This report is intended to fulfill the reporting requirements in Section 5 of ISO 14044 and Product Category Rules Guidance for Building-Related Products and Services UL® Environments (2021) Part B: Non-Metal Ceiling and Interior Wall Panel EPD Requirements, UL® Environment, v.2 04/2021.

Armstrong World Industries has a robust internal Quality Assurance process that is based on industry-accepted best practices and is led by a team of quality professionals who have been certified by the American Society for Quality. The process involves several hundred different measures made throughout the manufacturing processes. In addition, our products are UL® labeled for fire and acoustical performance – a process which involves strict oversight by Underwriters Laboratories. The Armstrong Ceilings acoustical laboratory is ISO 17025 certified and is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

9. REFERENCE

Armstrong World Industries. [2025]. Ultima® Templok® Ceiling Panels Life Cycle Assessment Report [Internal unpublished report]

ASTM International General Program instructions, v8.0, April 29, 2020

CML v 4.7 August 2016

ISO 14025:2006 – Environmental labels and declarations – Type III environmental declarations – Principles and procedures

ISO 14040/Amd1:2020 – Environmental management – Life Cycle Assessment – Principles and framework

ISO 14044:2006/Amd2:2020/Environmental management – Life cycle assessment – Requirements and guidelines

ISO 21930:2017 – Sustainability in buildings and civil engineering works – Core rules for environmental product declarations of construction products and services

Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources using Environmental Chambers Version 1.2, January 2017

Product Category Rules for Building Related Products and Services –

Part A: LCA Calculation Rules and Report Requirements, UL 10010, UL v 4.0, March 2022

Product Category Rules Guidance for Building Related Products & Services –

Part B: Non-Metal Ceiling and Interior Wall Panel EPD Requirements, UL Environment, v2.04/2021

