

LEED® v4 & v4.1

How Armstrong® Templok® Ceilings Can Contribute to LEED



SUSTAINABLE PRODUCT SEARCH TOOL

24/7 access to LEED® information and documentation you need in the design or submittal process for any Armstrong® Ceiling and Wall System

Theme	Credit	LEED® Credit	Points	Armstrong Ceilings and Walls Contribution
Energy and Atmosphere				
Energy Performance	Energy & Atmosphere	Minimum Energy Performance	Required Prerequisite	Armstrong® Templok® ceilings can contribute to the reduction in energy use by contribution to a minimum level of energy efficiency for the building and its systems. Thermal mass can contribute to reduced EUI in appropriate climates. Include Templok ceilings in your energy simulation model to show potential savings.
Energy Performance	Energy & Atmosphere	Optimize Energy performance	BD&C – 1-18 pts C&I – 1-24 pts	Armstrong Templok ceilings can contribute to increasing levels of energy performance beyond the prerequisite standard. This solution is an energy efficiency measure that focuses on HVAC load reduction. Thermal mass can contribute to reduced EUI in appropriate climates.
Energy Performance	Energy & Atmosphere	Demand Response Grid Harmonization	BD&C 1-2 pt O+M – 1 pt	Case 1. Demand response program available Case 3. Permanent load shifting
Material and Resources				
Life Cycle Impacts	MRc BD&C MRc ID&C	Building Life Cycle Reduction Interiors Life Cycle Impact Reduction	BD&C – 3 ID&C – 1-3 Up to 5 pts	ARMSTRONG PRODUCT CARBON FOOT PRINT ID&C, Option 1 – Reuse of nonstructural elements: Specify Ultima Templok – Ultima panels are made of reclaimed ceilings that are returned to our recycling program with a high level of post-consumer recycled content. ARMSTRONG ACCESSIBLE CEILING SYSTEMS ID&C, Option 3 – Design for Flexibility: Specify Ultima Templok accessible and demountable ceiling system for easy reconfiguration and access to building systems.
Sourcing of Raw Materials	Material and Resources	Building Disclosure and Optimization – Responsible Sourcing of Raw Materials	BD&C – 1-2 ID&C – 1-2	Use products that meet responsible sourcing and extraction criteria: Extended Producer Responsibility: ARMSTRONG® RECYCLING PROGRAM – Armstrong is responsible for extended producer responsibility with our acoustical ceiling products. Armstrong mineral fiber and fiberglass ceiling products contribute to this credit. Bio-based Materials: ARMSTRONG BIOBASED PRODUCTS – Specify Armstrong mineral fiber panels that contain plant-based binders, or biobased alternatives to petroleum-based binders. Armstrong products are tested using ASTM D6866 and are noted in the USDA BioPreferred Database. Material Reuse: Armstrong products are designed for disassembly and are flexible and adaptable to your environment. Recycled Content: Specify Armstrong Templok ceilings which has a recycled content of 34% pre-industrial and 7% post-consumer content.
Material Ingredient Disclosure	MRc BD&C MRc ID&C	Building Disclosure and Optimization – Material Ingredients	BD&C – 1-2 ID&C – 1-2	HEALTH PRODUCT DECLARATIONS BD&C, Option 1: Material Ingredient Reporting: Health Product Declarations qualify for Manufacturer Inventory (1 Pt). All products and accompanying certifications are listed on our Transparency site www.armstrongceilings.com/transparency ; and on Mindful Materials.

Theme	Credit	LEED® Credit	Points	Armstrong Ceilings Contribution
Material and Resources				
Recycling Program	MRp; MRc	Construction Waste Management	Option 1 – Diversion (1 pt); Option 2 – Waste Prevention (1-2 pts)	<p>ARMSTRONG® CEILING RECYCLING PROGRAM – As you upgrade to more efficient energy measures, use the ceiling recycling program to reduce existing ceiling tile waste from your project.</p> <p>Add the Armstrong Ceiling Recycling Program to the Waste Management Plan to provide a solution to divert materials from the waste stream, increasing diversion percentage. Ceilings qualify as one nonstructural material. Available throughout the US and Canada.</p> <p>Option 1: Diversion</p> <p>Divert at least 50% of the total construction and demolition materials from landfills and incineration facilities.</p> <p>Option 2: Reduction in Total Waste</p> <p>Follow the Waste Management Plan and prevent waste through reuse and source reduction design strategies. Divert at least 50% of all renovation and demolition waste, if any. Generate less than 7.5 LBS/FT² (37.5 kg/m²) of waste materials from all new construction activities (2 points). Specify products with minimal waste; the Armstrong digital and preconstruction service team, ProjectWorks®, will reduce waste by optimizing project layouts.</p>
Regional Materials	MR credits	Regional Materials (Extracted, manufactured, and purchased within 100 miles)	200% base contributing cost	<p>ARMSTRONG® CEILING MANUFACTURING LOCATIONS</p> <p>Armstrong® Ultima® Templok® final point of assembly is Hilliard, OH. Use the Armstrong Ceilings Sustainable Product Search Tool to calculate mileage for manufacture and extraction locations; product meeting 100 mile criteria is valued at 200% of base cost.</p>
Indoor Environmental Quality				
VOC Emissions & Occupant Health and Comfort	EQc	Low Emitting Materials	BD&C – 1-3 ID&C – 1-3	<p>ARMSTRONG® LOW OR NO-ADDED FORMALDEHYDE CEILINGS</p> <p>Armstrong Ultima Templok ceilings meet the California Department of Public Health (CDPH Standard) v1.2.1 2017, and comply with VOC limits. All CDPH testing apply to both the office and school testing scenarios. VOC Certificates of compliance are available on the Armstrong® ceilings Transparency website.</p>
Occupant Health and Comfort	Indoor Environmental Quality	Thermal Comfort	BD&C 1 pt	<p>Templok ceilings provide thermal mass to help stabilize temperature fluctuations and improves building's ability to satisfy ASHRAE 55-2017 thermal comfort design.</p>
Lighting	EQc	Interior Lighting – Lighting Quality	BD&C – 1 ID&C – 1	<p>ARMSTRONG® HIGH LIGHT-REFLECTANT CEILINGS AND WALLS</p> <p>Choose Armstrong Ultima Templok ceilings (LR.88) to aid in improving lighting quality in the space.</p>
Acoustics & Occupant Health and Comfort	EQc	Acoustic Performance (now all Rating Systems)	BD&C – 2 ID&C – 2	<p>ARMSTRONG® ACOUSTICAL CEILINGS</p> <p>Sound Transmission: Choose Armstrong Ultima Templok ceiling to meet the composite sound transmission class (STC_c) ratings or noise isolation class (NIC) for adjacent spaces.</p> <p>Reverberation Time: Armstrong acoustical ceilings absorb sound, contributing to the reduction of Reverberation Time and increased speech intelligibility for all room types and applications.</p>

LEED® is a trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
©2024 AWI Licensing LLC



Armstrong®
World Industries