SHASTA®

Square Lay-in
medium texture

UP TO **71%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management	construction waste mgmt	regional materials	design for flexibility	EPD	recyclable/ extended producer resp.	biobased materials	recycled content	sourcing of raw materials	material ingredient reporting	low emitting/ materials	lighting quality	acoustics
✓	✓	✓	✓		✓		✓	✓			✓	✓

▲ LOCATION DEPENDENT

$$$$

Shasta® panel with Prelude® 15/16" suspension system (Pgs. 279-280)

This economical panel provides sound absorption with a medium-textured, easy-clean, durable vinyl surface.

KEY SELECTION ATTRIBUTES

- Excellent sound absorption (perforated options)
- Easy-clean, durable surface
- Economical
- 30-Year Limited System Warranty against visible sag, mold and mildew

TYPICAL APPLICATIONS

- Discount/grocery stores
- Locker rooms
- Utility rooms
- Lavatories/restrooms

COLOR

White (WH)

Tech Black (BL)

VISUAL SELECTION

PERFORMANCE Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 295-299 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	UL Classified Acoustics NRC	+ CAC	= Total Acoustics[1]	Fire Rating	Light Reflect	Anti-Mold & Mildew (Inherent)	Sag Resist (Humi-Guard+)	Certified Low VOC Emissions	Water Repel (Durability)	Wash (Durability)	Scrub (Durability)	Impact (Durability)	Soil (Durability)	Recycled Content	Recycle Program	30-Yr Warranty
SHASTA® (Perforated)																			
15/16" Square Lay-in	1	**2904**	24 x 24 x 5/8" ☐	0.70 •	N/A	–	Class A	0.72	•	•	–	–	•	•	•	•	•	–	•
▭	1	**2906 _ _** ◆◆	24 x 48 x 5/8" ▭	0.70 •	N/A	–	Class A	0.72	•	•	–	–	•	•	•	•	•	–	•
	1	**Other Size Panels**	W: 12" – 30" / L: 12" – 60" 5/8" Thick	N/A	N/A	–	Class A	0.72	•	•	–	–	•	•	•	•	•	–	•
SHASTA (Unperforated)																			
15/16" Square Lay-in	1	**2905 _ _** ◆◆	24 x 24 x 5/8" ☐	0.50	N/A	–	Class A	0.72	•	•	–	•	•	•	•	•	•	–	•
▭	1	**2907**	24 x 48 x 5/8" ▭	0.50	N/A	–	Class A	0.72	•	•	–	•	•	•	•	•	•	–	•
	1	**Other Size Panels**	W: 12" – 30" / L: 12" – 60" 5/8" Thick	N/A	N/A	–	Class A	0.72	•	•	–	•	•	•	•	•	•	–	•

[1] Total Acoustics™ ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
◆◆ Add 2-letter color suffix to item number when specifying or ordering (e.g., 2906 B L).

SUSPENSION SYSTEMS

15/16"



Prelude®

PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubbable vinyl film facing (UV protected)

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled.)

ASTM E1264 Classification
2904, 2906 – Type XII, Form 1, Pattern E C
2905, 2907 – Type XII, Form 1, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels maintain superior sag resistance. Recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Fiberglass panels inherently inhibit the growth of mold and mildew.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
0.17 lbs/SF; 128 SF/ctn

Minimum Order Quantity
1 carton, excludes other size panels

Metric Items Available
Items 2904M, 2906M, 2905M, 2907M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine℠ / 1 877 276 7876
armstrongceilings.com/commceilings
(search: shasta)
BPCS-3697-615

LEED® is a registered trademark of the U.S. Green Building Council
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2015 AWI Licensing Company
Printed in the United States of America

Armstrong® CEILING SOLUTIONS